

ESA614: Computational Astrophysics

Assignment # 3

Name: Abraham Mathews

ID: SC22M077

Program: MS Astronomy and Astrophysics

Attached file *blazar_S0716.dat* contains the photometric observations of a blazar S50716+714.‡

Choose finely sampled block of data in timescale of a few hours around 5th Jan 2016 and 29th Jan 2016. Interpolate the magnitude vs time data with both Lagrange and Cubic Spline (use *scipy.interpolate* for spline) interpolation.

~~Choose the more appropriate interpolation method out of these two,~~ interpolate V, R, and I light curves. Obtain V-R and R-I colors.

- (i) Separately plot V-R and R-I colors vs R magnitude and see (visually) if there is correlation between color variation and flaring.
- (ii) Plot a color-color diagram (V-R vs R-I) of the blazar.

```

In [10]: from astropy.io import ascii
from astropy.table import Table
import matplotlib.pyplot as plt
from scipy import interpolate
import numpy as np

#plt.style.use('seaborn-bright')
plt.style.use('default')
fig = plt.figure(figsize = (10,10))

data = ascii.read("https://raw.githubusercontent.com/abrahammathews2000/Dataset_for_Gcolab/main/LabMockTest1/blazar_S0716.dat",delim
iter=' ')
data_order = data[data.argsort('date')] # To order in Ascending or
der
mask_date_index = (data_order['yr'] == 2016) & (data_order['month
'] == 1) & (data_order['day']>=5) & (data_order['day']<=6)
#mask_date_index = (data_order['yr'] >= 2011) & (data_order['yr']
<= 2018)

data_selected = data_order[mask_date_index]

mask_Rband = (data_selected['band'] == 'R')
mask_Iband = (data_selected['band'] == 'I')
mask_Vband = (data_selected['band'] == 'V')
data_selected_Rband = data_selected[mask_Rband]
data_selected_Iband = data_selected[mask_Iband]
data_selected_Vband = data_selected[mask_Vband]

#Spline Interpolate
x_min = min(data_selected_Rband['date'][0],data_selected_Iband['da
te'][0],data_selected_Vband['date'][0])
x_max = max(data_selected_Rband['date'][len(data_selected_Rband['d
ate'])-1],data_selected_Iband['date'][len(data_selected_Iband['dat
e'])-1],data_selected_Vband['date'][len(data_selected_Vband['date
'])-1])
x=np.linspace(x_min,x_max,5000)
#Rband
xRband = np.linspace(data_selected_Rband['date'][0],data_selected_
Rband['date'][len(data_selected_Rband['date'])-1],5000)
rBandSpline = interpolate.CubicSpline(data_selected_Rband['date'],
data_selected_Rband['mag'])
plt.plot(xRband,rBandSpline(xRband),label = 'Spline for R Band')
#Iband
xIband = np.linspace(data_selected_Iband['date'][0],data_selected_
Iband['date'][len(data_selected_Iband['date'])-1],5000)
iBandSpline = interpolate.CubicSpline(data_selected_Iband['date'],
data_selected_Iband['mag'])
plt.plot(xIband,iBandSpline(xIband),label = 'Spline for I Band')
#Vband
xVband = np.linspace(data_selected_Vband['date'][0],data_selected_
Vband['date'][len(data_selected_Vband['date'])-1],5000)
vBandSpline = interpolate.CubicSpline(data_selected_Vband['date'],
data_selected_Vband['mag'])
plt.plot(xVband,vBandSpline(xVband),label = 'Spline for V Band')

plt.scatter(data_selected_Rband['date'],data_selected_Rband['mag

```

```

    ],color='black',edgecolors = 'blue',label="R band (Data Points)",
    marker = 'o')
plt.scatter(data_selected_Iband['date'],data_selected_Iband['mag
'],color='black',edgecolors = 'orange',label="I band (Data Point
s)",marker = 's')
plt.scatter(data_selected_Vband['date'],data_selected_Vband['mag
'],color='black',edgecolors = 'green',label="V band (Data Point
s)",marker = 'v')

```

```


plt.legend(bbox_to_anchor = (1.05, 0.6))
plt.xlabel("Julian Date")
plt.ylabel("Magnitude (mag)")
plt.grid()

```

```

plt.show()

```




```

In [14]: # i)
# To plot V-R vs R magnitude
fig = plt.figure(figsize = (10,10))

plt.scatter(data_selected_Rband['mag'],(vBandSpline(data_selected_Rband['date'])-data_selected_Rband['mag']),label = 'V-R vs R',marker = 'o',edgecolors = 'black')

plt.title('V-R vs R')
plt.legend()
plt.xlabel("R (mag)")
plt.ylabel("V-R (mag)")
plt.grid()
plt.show()

```




```

In [12]: # i)
# To plot R-I vs R magnitude
fig = plt.figure(figsize = (10,10))

plt.scatter(data_selected_Rband['mag'],(data_selected_Rband['mag']-iBandSpline(data_selected_Rband['date'])),label = 'R-I vs R',marker = 'o',edgecolors = 'black')
plt.title('R-I vs R')
plt.legend()
plt.xlabel("R (mag)")
plt.ylabel("R-I (mag)")
plt.grid()
plt.show()

```



```

In [13]: # ii)
# To plot V-R vs R-I magnitude
fig = plt.figure(figsize = (10,10))

plt.scatter((data_selected_Rband['mag']-iBandSpline(data_selected_Rband['date'])),(vBandSpline(data_selected_Rband['date'])-data_selected_Rband['mag']),label = 'V-R vs R-I',marker = 'o',edgecolors = 'black')

plt.legend()
plt.title('V-R vs R-I')

plt.xlabel("R-I (mag)")
plt.ylabel("V-R (mag)")
plt.grid()
plt.show()

```

