

# Introduction to deep learning applications in biomedical data

---

MERJA HEINÄNIEMI


ASSOCIATE PROFESSOR IN BIOINFORMATICS

INSTITUTE OF BIOMEDICINE, SCHOOL OF MEDICINE



UNIVERSITY OF  
EASTERN FINLAND


# Short history – interesting future



Interesting new problems!

# Motivation: higher level features may better discriminate between classes


---



**Classical workflow:** data pre-processing, feature extraction, model learning and model evaluation

# Motivation: higher level features may better discriminate between classes

---



**Deep neural network workflow:** use a hierarchical structure to learn increasingly abstract feature representations from the raw data -> higher-level features to better discriminate between classes

# Data pre-processing: general

---

Some minimal pre-processing to consider:

- Numerical features zero-centred by subtracting their mean value
- Image pixels jointly by subtracting the mean pixel intensity per colour channel
- Another normalization is to standardize features to unit variance
- Skewed distribution -> log transformation or similar may be appropriate

! Validation and test data need to be normalized consistently with the training data. For example, features of the validation data need to be zero-centred by subtracting the mean computed on the training data, not on the validation data.

# Model architecture

---

**Let's focus on three often encountered:**

- a feedforward neural network with fully connected hidden layers – a good starting point for many problems
- convolutional architecture - well suited for multi- and high-dimensional data, such as two-dimensional images or abundant genomic data
- recurrent neural networks - capturing long-range dependencies in sequential data (text, DNA, RNA or protein sequence)

# Model architecture: simple features

*Like language, DNA/RNA/protein sequence can be presented to the model using one hot encoding*

... 1000 0100 0010 0001 ...  
A C G T

Encoding



Spatial processing


... AGAGACGTCGGC ...

DNA sequence




X-ray image

*Sequential models*





Sequential processing



EEG signal

*Extracting sub-parts of image*


# Model architecture: network alternatives






# Model architecture: output

---



# Model architecture: building blocks

---



---




Perceptrons (+++ labelled data!)  
Autoencoders  
Restricted Boltzmann machines

Convolution layers  
Nonlinear layers  
Pooling layers

Perceptrons  
Long short-term memory units (LSTM)  
Restricted Boltzmann machines  
Gated recurrent units

# Model architecture: examples

---



---

## *Various tasks*

Splice signal detection  
Protein secondary structure  
Cancer classification

## *Imaging data +++*

also Transcription factor motif  
DNA accessibility (multitask)


\*Multitask joint learning

## *Sequence data +++*

Protein secondary structure  
microRNA motif

# Model training: general

---

- Objective function
  - Parameter initialization
  - Learning rate and batch size
  - Learning rate decay
  - Momentum
  - Adaptive learning rate
  - Batch normalization
  - Analyzing the learning curve
  - Monitoring performance
- 

# Imbalanced data – issue in bioinformatics

---

most deep learning algorithms assume sufficient and balanced data BUT

- cost can be high to perform measurement
- unequal class distribution due to sample availability (cases vs controls)

Solutions that could be relevant in independent task:

- unsupervised pre-training
- transfer learning (pre-training with sufficient data from similar but different domains and fine-tuning with real data)

# Interpretation

---

- In biomedical domains, **it is not enough to simply produce good outcomes**
- visualizing a trained deep learning model:

e.g. Transcription factor motif:

DBN: choose the most class discriminative weight vector among those in the first layer


CNN (DeepBind): count nucleotide frequencies of positive input subsequences with high activation values

# Example DNA application 1

---

Data explained here, network solution in next lecture

A protein that **binds to DNA** can be measured from cells – signal across the genome with peaks at bound sites (ChIP-seq signal)



**Q: Which DNA sequence does it recognize?**


# Chromatin immunoprecipitation (ChIP)-seq

---

Signal (read counts) represents levels of immunoprecipitated DNA

- DNA bound by transcription factors
- or
- DNA at histones that are marked with a specific modification

Signal informative about *gene regulation*





# Example DNA application 1

---

A protein that **binds to DNA** can be measured from cells – signal across the genome with peaks at bound sites (ChIP-seq signal)




Measure where it bound and extract DNA sequence as input data



Q: Which DNA sequence does it recognize?

# ChIP-seq signal



Data from the ENCODE project – one of the first large-scale ChIP-seq efforts

# Example DNA application 1

---

Data explained here, network solution in next lecture

A protein that **binds to DNA** can be measured from cells – signal across the genome with peaks at bound sites (ChIP-seq signal)



Measure where it bound and extract DNA sequence as input data



Q: Which DNA sequence does it recognize?




# Example DNA application 2

---

Data explained here, network solution in next lecture


Many proteins **binds to DNA** can be measured from cells – signal across the genome with peaks at bound sites (ChIP-seq signal)



**Q: Can the binding profile (i.e. signal profile) at a given DNA location be predicted?**

Also so-called histone-markers (labels of active / inactive regions) and DNA accessibility markers can be measured generating similar signal across genome (ChIP-seq, DNase-seq aka DHS, ATAC-seq)

# Example DNA application 2




# Example DNA application 2

Data explained here, network solution in next lecture

Many proteins **binds to DNA** can be measured from cells – signal across the genome with peaks at bound sites (ChIP-seq signal)

Also so-called histone-markers (labels of active / inactive regions) and DNA accessibility markers can be measured generating similar signal across genome (ChIP-seq, DNase-seq aka DHS, ATAC-seq)

**Q: Can the binding profile (i.e. signal profile) at a given DNA location be predicted?**



# Example DNA application 2

Data explained here, network solution in next lecture

- Using trained model: **compare** DNA sequences that differ at certain position (mutation / natural variant i.e. SNP)

**Q: Can the binding profile (i.e. signal profile) at a given DNA location be predicted?**

Input:  
genomic sequences  
(1,000 bp)

...GCGTGGGTACGCTTA<sup>T</sup>TCGTCAAGCTTTAGCGT...  
...GCGTGGGTACGCTTA<sup>A</sup>TCGTCAAGCTTTAGCGT...

Variant position

