


[REMOVE ADS](#)

Attribute Reference

[Next >](#)

Attribute Reference

all HTML attributes and what elements they can be used within:

Attribute	Belongs to	Description
<u>accept</u>	<u><input></u>	Specifies the types of files that the server accepts (only for type="file")
<u>accept-charset</u>	<u><form></u>	Specifies the character encodings that are to be used for the form submission
<u>accesskey</u>	<u>Global Attributes</u>	Specifies a shortcut key to activate/focus an element
<u>action</u>	<u><form></u>	Specifies where to send the form-

Available at GoDaddy

GROW YOUR
BUSINESS WITH .AI

START TODAY


[REMOVE ADS](#)
async<script>

Specifies that the script is executed asynchronously (only for external scripts)

autocomplete<form>, <input>

Specifies whether the <form> or the <input> element should have autocomplete enabled

autofocus<button>, <input>,
<select>, <textarea>

Specifies that the element should automatically get focus when the page loads

autoplay<audio>, <video>

Specifies that the audio/video will start playing as soon as it is ready

bgcolor

Not supported in HTML 5.

Specifies the background color of an element. Use CSS instead

border

Not supported in HTML 5.

Specifies the width of the border of an element. Use CSS instead

charset<meta>, <script>

Specifies the character encoding

checked<input>

Specifies that an <input> element should be pre-selected when the page loads (for type="checkbox" or type="radio")

cite<blockquote>, , <ins>,
<q>

Specifies a URL which explains the quote/deleted/inserted text

classGlobal Attributes

Specifies one or more class names for an element (refers to a class in a style sheet)

color

Not supported in HTML 5.

Specifies the text color of an element. Use CSS instead

cols<textarea>

Specifies the visible width of a text area

contentGlobal Attributes

Gives the value associated with the http-equiv or name attribute

REMOVE ADS

contenteditableGlobal Attributes

Specifies whether the content of an element is editable or not

controls<audio>, <video>

Specifies that audio/video controls should be displayed (such as a play/pause button etc.)

coords<area>

Specifies the coordinates of the area

data<object>

Specifies the URL of the resource to be used by the object

data-*Global Attributes

Used to store custom data private to the page or application

datetime, <ins>, <time>

Specifies the date and time

default<track>

Specifies that the track is to be enabled if the user's preferences do not indicate that another track would be more appropriate

defer<script>

Specifies that the script is executed when the page has finished parsing (only for external scripts)

dirGlobal Attributes

Specifies the text direction for the content in an element

dirname<input>, <textarea>

Specifies that the text direction will be submitted

disabled
<button>, <fieldset>,
<input>, <optgroup>,
<option>, <select>,
<textarea>

Specifies that the specified element/group of elements should be disabled

download<a>, <area>

Specifies that the target will be downloaded when a user clicks on the hyperlink

[HTML5](#)[HTML5](#)

Specifies how the form data should

REMOVE ADS

be encoded when submitting it to the server (only for method="post")

[enterkeyhint](#)[Global Attributes](#)

Specifies the text of the enter-key on a virtual keyboard

[for](#)<label>, [<output>](#)

Specifies which form element(s) a label/calculation is bound to

[form](#)
[<button>](#), [<fieldset>](#),
[<input>](#), [<label>](#), [<meter>](#),
[<object>](#), [<output>](#),
[<select>](#), [<textarea>](#)

Specifies the name of the form the element belongs to

[formaction](#)[<button>](#), [<input>](#)

Specifies where to send the form-data when a form is submitted. Only for type="submit"

[headers](#)[<td>](#), [<th>](#)

Specifies one or more headers cells a cell is related to

[height](#)
[<canvas>](#), [<embed>](#),
[<iframe>](#), [](#), [<input>](#),
[<object>](#), [<video>](#)

Specifies the height of the element

[hidden](#)[Global Attributes](#)

Specifies that an element is not yet, or is no longer, relevant

[high](#)[<meter>](#)

Specifies the range that is considered to be a high value

[href](#)
[<a>](#), [<area>](#), [<base>](#),
[<link>](#)

Specifies the URL of the page the link goes to

[hreflang](#)[<a>](#), [<area>](#), [<link>](#)

Specifies the language of the linked document

[http-equiv](#)[<meta>](#)

Provides an HTTP header for the information/value of the content attribute

[id](#)[Global Attributes](#)

Specifies a unique id for an element



Tutorials ▼

References ▼

Exercises ▼



Sign In

[HTML](#)
[CSS](#)
[JAVASCRIPT](#)
[SQL](#)
[PYTHON](#)
[JAVA](#)
[PHP](#)
[W3.CSS](#)
[C](#)
[C++](#)

[HTML Attributes](#)
[Global Attributes](#)
[Specifies the mode of a virtual keyboard](#)
[REMOVE ADS](#)
ismap

Specifies an image as a server-side image map

kind<track>

Specifies the kind of text track

label<track>, <option>,
<optgroup>

Specifies the title of the text track

lang[Global Attributes](#)

Specifies the language of the element's content

list<input>

Refers to a <datalist> element that contains pre-defined options for an <input> element

loop<audio>, <video>

Specifies that the audio/video will start over again, every time it is finished

low<meter>

Specifies the range that is considered to be a low value

max<input>, <meter>,
<progress>

Specifies the maximum value

maxlength<input>, <textarea>

Specifies the maximum number of characters allowed in an element

media<a>, <area>, <link>,
<source>, <style>

Specifies what media/device the linked document is optimized for

method<form>

Specifies the HTTP method to use when sending form-data

min<input>, <meter>

Specifies a minimum value

multiple<input>, <select>

Specifies that a user can enter more than one value

muted<video>, <audio>

Specifies that the audio output of the video should be muted

[REMOVE ADS](#)
<output>, <param>,<select>, <textarea>novalidate<form>

Specifies that the form should not be validated when submitted

onabort<audio>, <embed>, ,
<object>, <video>

Script to be run on abort

onafterprint<body>

Script to be run after the document is printed

onbeforeprint<body>

Script to be run before the document is printed

onbeforeunload<body>

Script to be run when the document is about to be unloaded

onblur

All visible elements.

Script to be run when the element loses focus

oncanplay<audio>, <embed>,
<object>, <video>

Script to be run when a file is ready to start playing (when it has buffered enough to begin)

oncanplaythrough<audio>, <video>

Script to be run when a file can be played all the way to the end without pausing for buffering

onchange

All visible elements.

Script to be run when the value of the element is changed

onclick

All visible elements.

Script to be run when the element is being clicked

oncontextmenu

All visible elements.

Script to be run when a context menu is triggered

oncopy

All visible elements.

Script to be run when the content of the element is being copied

oncuechange<track>Script to be run when the cue changes in a <track> element



Tutorials ▼

References ▼

Exercises ▼



Sign In

[HTML](#)
[CSS](#)
[JAVASCRIPT](#)
[SQL](#)
[PYTHON](#)
[JAVA](#)
[PHP](#)
[W3.CSS](#)
[C](#)
[C++](#)

[ondblclick](#)

All visible elements.

Script to be run when the element is being double-clicked

[REMOVE ADS](#)
[ondrag](#)

All visible elements.

Script to be run when the element is being dragged

[ondragend](#)

All visible elements.

Script to be run at the end of a drag operation

[ondragenter](#)

All visible elements.

Script to be run when an element has been dragged to a valid drop target

[ondragleave](#)

All visible elements.

Script to be run when an element leaves a valid drop target

[ondragover](#)

All visible elements.

Script to be run when an element is being dragged over a valid drop target

[ondragstart](#)

All visible elements.

Script to be run at the start of a drag operation

[ondrop](#)

All visible elements.

Script to be run when dragged element is being dropped

[ondurationchange](#)
[<audio>](#), [<video>](#)

Script to be run when the length of the media changes

[onemptied](#)
[<audio>](#), [<video>](#)

Script to be run when something bad happens and the file is suddenly unavailable (like unexpectedly disconnects)

[onended](#)
[<audio>](#), [<video>](#)

Script to be run when the media has reach the end (a useful event for messages like "thanks for listening")

[onerror](#)
[<audio>](#), [<body>](#),
[<embed>](#), [](#), [<object>](#),
[<script>](#), [<style>](#), [<video>](#)

Script to be run when an error occurs

[onmouseover](#)
[REMOVE ADS](#)
oninput

All visible elements.

Script to be run when the element gets user input

oninvalid

All visible elements.

Script to be run when the element is invalid

onkeydown

All visible elements.

Script to be run when a user is pressing a key

onkeypress

All visible elements.

Script to be run when a user presses a key

onkeyup

All visible elements.

Script to be run when a user releases a key

onload
<body>, <iframe>, ,
<input>, <link>, <script>,
<style>

Script to be run when the element is finished loading

onloadeddata<audio>, <video>

Script to be run when media data is loaded

onloadedmetadata<audio>, <video>

Script to be run when meta data (like dimensions and duration) are loaded

onloadstart<audio>, <video>

Script to be run just as the file begins to load before anything is actually loaded

onmousedown

All visible elements.

Script to be run when a mouse button is pressed down on an element

onmousemove

All visible elements.

Script to be run as long as the mouse pointer is moving over an element

onmouseover

All visible elements.

Script to be run when a mouse pointer moves over an element

REMOVE ADS

onmouseup

All visible elements.

Script to be run when a mouse button is released over an element

onmousewheel

All visible elements.

Script to be run when a mouse wheel is being scrolled over an element

onoffline

<body>

Script to be run when the browser starts to work offline

ononline

<body>

Script to be run when the browser starts to work online

onpagehide

<body>

Script to be run when a user navigates away from a page

onpageshow

<body>

Script to be run when a user navigates to a page

onpaste

All visible elements.

Script to be run when the user pastes some content in an element

onpause

<audio>, <video>

Script to be run when the media is paused either by the user or programmatically

onplay

<audio>, <video>

Script to be run when the media has started playing

onplaying

<audio>, <video>

Script to be run when the media has started playing

onpopstate

<body>

Script to be run when the window's history changes.

onprogress

<audio>, <video>

Script to be run when the browser is in the process of getting the media data

onratechange

<audio>, <video>

Script to be run each time the playback rate changes (like when a

REMOVE ADS		in a form is clicked.
<u>onresize</u>	<u><body></u>	Script to be run when the browser window is being resized.
<u>onscroll</u>	All visible elements.	Script to be run when an element's scrollbar is being scrolled
<u>onsearch</u>	<u><input></u>	Script to be run when the user writes something in a search field (for <input type="search">)
<u>onseeked</u>	<u><audio></u> , <u><video></u>	Script to be run when the seeking attribute is set to false indicating that seeking has ended
<u>onseeking</u>	<u><audio></u> , <u><video></u>	Script to be run when the seeking attribute is set to true indicating that seeking is active
<u>onselect</u>	All visible elements.	Script to be run when the element gets selected
<u>onstalled</u>	<u><audio></u> , <u><video></u>	Script to be run when the browser is unable to fetch the media data for whatever reason
<u>onstorage</u>	<u><body></u>	Script to be run when a Web Storage area is updated
<u>onsubmit</u>	<u><form></u>	Script to be run when a form is submitted
<u>onsuspend</u>	<u><audio></u> , <u><video></u>	Script to be run when fetching the media data is stopped before it is completely loaded for whatever reason
<u>ontimeupdate</u>	<u><audio></u> , <u><video></u>	Script to be run when the playing position has changed (like when the user fast forwards to a different point in the media)

[onunload](#)
[REMOVE ADS](#)
<body>

Script to be run when a page has unloaded (or the browser window has been closed)

onvolumechange<audio>, <video>

Script to be run each time the volume of a video/audio has been changed

onwaiting<audio>, <video>

Script to be run when the media has paused but is expected to resume (like when the media pauses to buffer more data)

onwheel

All visible elements.

Script to be run when the mouse wheel rolls up or down over an element

open<details>

Specifies that the details should be visible (open) to the user

optimum<meter>

Specifies what value is the optimal value for the gauge

pattern<input>

Specifies a regular expression that an <input> element's value is checked against

placeholder<input>, <textarea>

Specifies a short hint that describes the expected value of the element

popoverGlobal Attributes

Specifies a popover element

popovertarget<button>, <input>

Specifies which popover element to invoke

popovertargetaction<button>, <input>

Specifies what happens to the popover element when the button is clicked

poster<video>

Specifies an image to be shown while the video is downloading, or until the user hits the play button



<u>readonly</u>	<u><input></u> , <u><textarea></u>	Specifies that the element is read-only
<u>rel</u>	<u><a></u> , <u><area></u> , <u><form></u> , <u><link></u>	Specifies the relationship between the current document and the linked document
<u>required</u>	<u><input></u> , <u><select></u> , <u><textarea></u>	Specifies that the element must be filled out before submitting the form
<u>reversed</u>	<u></u>	Specifies that the list order should be descending (9,8,7...)
<u>rows</u>	<u><textarea></u>	Specifies the visible number of lines in a text area
<u>rowspan</u>	<u><td></u> , <u><th></u>	Specifies the number of rows a table cell should span
<u>sandbox</u>	<u><iframe></u>	Enables an extra set of restrictions for the content in an <iframe>
<u>scope</u>	<u><th></u>	Specifies whether a header cell is a header for a column, row, or group of columns or rows
<u>selected</u>	<u><option></u>	Specifies that an option should be pre-selected when the page loads
<u>shape</u>	<u><area></u>	Specifies the shape of the area
<u>size</u>	<u><input></u> , <u><select></u>	Specifies the width, in characters (for <input>) or specifies the number of visible options (for <select>)
<u>sizes</u>	<u></u> , <u><link></u> , <u><source></u>	Specifies the size of the linked resource
<u>span</u>	<u><col></u> , <u><colgroup></u>	Specifies the number of columns to span



<u>src</u>	<u><audio></u> , <u><embed></u> , <u><iframe></u> , <u></u> , <u><input></u> , <u><script></u> , <u><source></u> , <u><track></u> , <u><video></u>	Specifies the URL of the media file
<u>srcdoc</u>	<u><iframe></u>	Specifies the HTML content of the page to show in the <iframe>
<u>srclang</u>	<u><track></u>	Specifies the language of the track text data (required if kind="subtitles")
<u>srcset</u>	<u></u> , <u><source></u>	Specifies the URL of the image to use in different situations
<u>start</u>	<u></u>	Specifies the start value of an ordered list
<u>step</u>	<u><input></u>	Specifies the legal number intervals for an input field
<u>style</u>	<u>Global Attributes</u>	Specifies an inline CSS style for an element
<u>tabindex</u>	<u>Global Attributes</u>	Specifies the tabbing order of an element
<u>target</u>	<u><a></u> , <u><area></u> , <u><base></u> , <u><form></u>	Specifies the target for where to open the linked document or where to submit the form
<u>title</u>	<u>Global Attributes</u>	Specifies extra information about an element
<u>translate</u>	<u>Global Attributes</u>	Specifies whether the content of an element should be translated or not
<u>type</u>	<u><a></u> , <u><button></u> , <u><embed></u> , <u><input></u> , <u><link></u> , <u><menu></u> , <u><object></u> , <u><script></u> , <u><source></u> , <u><style></u>	Specifies the type of element

[Tutorials](#) ▼[References](#) ▼[Exercises](#) ▼[Sign In](#)[HTML](#) [CSS](#) [JAVASCRIPT](#) [SQL](#) [PYTHON](#) [JAVA](#) [PHP](#) [W3.CSS](#) [C](#) [C++](#)[value](#)[REMOVE ADS](#)[<button>](#), [<input>](#), [](#), [<input type="checkbox">](#)[<option>](#), [<meter>](#),[<progress>](#), [<param>](#)

Specifies the value of the element

[width](#)[<canvas>](#), [<embed>](#),[<iframe>](#), [](#), [<input>](#),[<object>](#), [<video>](#)

Specifies the width of the element

[wrap](#)[<textarea>](#)

Specifies how the text in a text area is to be wrapped when submitted in a form

GoDaddy

FOR THOSE CREATING
THE FUTURE.

START T

[REMOVE ADS](#)[◀ Previous](#)[Sign in to track progress](#)[Next ▶](#)

Developer Tools

[Tutorials ▼](#)[References ▼](#)[Exercises ▼](#)[Sign In](#)[CSS](#)[JAVASCRIPT](#)[SQL](#)[PYTHON](#)[JAVA](#)[PHP](#)[W3.CSS](#)[C](#)[C++](#)[REMOVE ADS](#)[Browse tools »](#)[PLUS](#)[SPACES](#)[GET CERTIFIED](#)[FOR TEACHERS](#)[BOOTCAMPS](#)[CONTACT US](#)

Top Tutorials

- [HTML Tutorial](#)
- [CSS Tutorial](#)
- [JavaScript Tutorial](#)
- [How To Tutorial](#)
- [SQL Tutorial](#)
- [Python Tutorial](#)
- [W3.CSS Tutorial](#)
- [Bootstrap Tutorial](#)
- [PHP Tutorial](#)
- [Java Tutorial](#)
- [C++ Tutorial](#)
- [jQuery Tutorial](#)

Top References

- [HTML Reference](#)
- [CSS Reference](#)
- [JavaScript Reference](#)
- [SQL Reference](#)
- [Python Reference](#)
- [W3.CSS Reference](#)
- [Bootstrap Reference](#)
- [PHP Reference](#)



[Tutorials ▼](#)[References ▼](#)[Exercises ▼](#)[Sign In](#)[CSS](#) [JAVASCRIPT](#) [SQL](#) [PYTHON](#) [JAVA](#) [PHP](#) [W3.CSS](#) [C](#) [C++](#)[HTML Examples](#)
[CSS Examples](#)
[JavaScript Examples](#)
[How To Examples](#)
[SQL Examples](#)
[Python Examples](#)
[W3.CSS Examples](#)
[Bootstrap Examples](#)
[PHP Examples](#)
[Java Examples](#)
[XML Examples](#)
[jQuery Examples](#)[HTML Certificate](#)
[CSS Certificate](#)
[JavaScript Certificate](#)
[Front End Certificate](#)
[SQL Certificate](#)
[Python Certificate](#)
[PHP Certificate](#)
[jQuery Certificate](#)
[Java Certificate](#)
[C++ Certificate](#)
[C# Certificate](#)
[XML Certificate](#)[FORUM](#) [ABOUT](#) [ACADEMY](#)

W3Schools is optimized for learning and training. Examples might be simplified to improve reading and learning.

Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content. While using W3Schools, you agree to have read and accepted our [terms of use](#), [cookies](#) and [privacy policy](#).

Copyright 1999-2026 by Refsnes Data. All Rights Reserved. W3Schools is Powered by W3.CSS.