



Tutorials ▼

References ▼

Exercises ▼



Sign In



CSS

JAVASCRIPT

SQL

PYTHON

JAVA


PHP

W3.CSS

C

C++

REMOVE ADS



# Event Attributes

Next &gt;

## Event Attributes

to let events trigger actions in a browser, like starting a JavaScript when a user clicks on an element.

To learn more about programming events, please visit our [JavaScript tutorial](#).

Below are the global event attributes that can be added to HTML elements to define event actions.

## Window Event Attributes

Events triggered for the window object (applies to the <body> tag):

| Attribute | Value | Description |
|-----------|-------|-------------|
|-----------|-------|-------------|





Tutorials ▼

References ▼

Exercises ▼



Sign In

[HTML](#) [CSS](#) [JAVASCRIPT](#) [SQL](#) [PYTHON](#) [JAVA](#) [PHP](#) [W3.CSS](#) [C](#) [C++](#)

|                                     |               |                                                                              |
|-------------------------------------|---------------|------------------------------------------------------------------------------|
| <a href="#"><u>onerror</u></a>      | <i>script</i> | Script to be run when an error occurs                                        |
| <a href="#"><u>onhashchange</u></a> | <i>script</i> | Script to be run when there has been changes to the anchor part of the a URL |
| <a href="#"><u>onload</u></a>       | <i>script</i> | Fires after the page is finished loading                                     |
| <a href="#"><u>onmessage</u></a>    | <i>script</i> | Script to be run when the message is triggered                               |
| <a href="#"><u>onoffline</u></a>    | <i>script</i> | Script to be run when the browser starts to work offline                     |
| <a href="#"><u>ononline</u></a>     | <i>script</i> | Script to be run when the browser starts to work online                      |
| <a href="#"><u>onpagehide</u></a>   | <i>script</i> | Script to be run when a user navigates away from a page                      |
| <a href="#"><u>onpageshow</u></a>   | <i>script</i> | Script to be run when a user navigates to a page                             |
| <a href="#"><u>onpopstate</u></a>   | <i>script</i> | Script to be run when the window's history changes                           |
| <a href="#"><u>onresize</u></a>     | <i>script</i> | Fires when the browser window is resized                                     |
| <a href="#"><u>onstorage</u></a>    | <i>script</i> | Script to be run when a Web Storage area is updated                          |
| <a href="#"><u>onunload</u></a>     | <i>script</i> | Fires once a page has unloaded (or the browser window has been closed)       |

[REMOVE ADS](#)



most used in form elements):

[REMOVE ADS](#)

| Attribute                            | Value         | Description                                                                   |
|--------------------------------------|---------------|-------------------------------------------------------------------------------|
| <u><a href="#">onblur</a></u>        | <i>script</i> | Fires the moment that the element loses focus                                 |
| <u><a href="#">onchange</a></u>      | <i>script</i> | Fires the moment when the value of the element is changed                     |
| <u><a href="#">oncontextmenu</a></u> | <i>script</i> | Script to be run when a context menu is triggered                             |
| <u><a href="#">onfocus</a></u>       | <i>script</i> | Fires the moment when the element gets focus                                  |
| <u><a href="#">oninput</a></u>       | <i>script</i> | Script to be run when an element gets user input                              |
| <u><a href="#">oninvalid</a></u>     | <i>script</i> | Script to be run when an element is invalid                                   |
| <u><a href="#">onreset</a></u>       | <i>script</i> | Fires when the Reset button in a form is clicked                              |
| <u><a href="#">onsearch</a></u>      | <i>script</i> | Fires when the user writes something in a search field (for <input="search">) |
| <u><a href="#">onselect</a></u>      | <i>script</i> | Fires after some text has been selected in an element                         |
| <u><a href="#">onsubmit</a></u>      | <i>script</i> | Fires when a form is submitted                                                |

## Keyboard Events

| Attribute                         | Value         | Description                         |
|-----------------------------------|---------------|-------------------------------------|
| <u><a href="#">onkeydown</a></u>  | <i>script</i> | Fires when a user is pressing a key |
| <u><a href="#">onkeypress</a></u> | <i>script</i> | Fires when a user presses a key     |
| <u><a href="#">onkeyup</a></u>    | <i>script</i> | Fires when a user releases a key    |

[REMOVE ADS](#)[REMOVE ADS](#)

## Mouse Events

| Attribute                           | Value         | Description                                                                 |
|-------------------------------------|---------------|-----------------------------------------------------------------------------|
| <u><a href="#">onclick</a></u>      | <i>script</i> | Fires on a mouse click on the element                                       |
| <u><a href="#">ondblclick</a></u>   | <i>script</i> | Fires on a mouse double-click on the element                                |
| <u><a href="#">onmousedown</a></u>  | <i>script</i> | Fires when a mouse button is pressed down on an element                     |
| <u><a href="#">onmousemove</a></u>  | <i>script</i> | Fires when the mouse pointer is moving while it is over an element          |
| <u><a href="#">onmouseout</a></u>   | <i>script</i> | Fires when the mouse pointer moves out of an element                        |
| <u><a href="#">onmouseover</a></u>  | <i>script</i> | Fires when the mouse pointer moves over an element                          |
| <u><a href="#">onmouseup</a></u>    | <i>script</i> | Fires when a mouse button is released over an element                       |
| <u><a href="#">onmousewheel</a></u> | <i>script</i> | <b>Deprecated.</b> Use the <u><a href="#">onwheel</a></u> attribute instead |
| <u><a href="#">onwheel</a></u>      | <i>script</i> | Fires when the mouse wheel rolls up or down over an element                 |

## Drag Events

| Attribute                     | Value         | Description                                 |
|-------------------------------|---------------|---------------------------------------------|
| <u><a href="#">ondrag</a></u> | <i>script</i> | Script to be run when an element is dragged |



|                                                  |               |                                                                            |
|--------------------------------------------------|---------------|----------------------------------------------------------------------------|
| <a href="#">REMOVE ADS</a><br><u>ondragleave</u> | <i>script</i> | Script to be run when an element leaves a valid drop target                |
| <u>ondragover</u>                                | <i>script</i> | Script to be run when an element is being dragged over a valid drop target |
| <u>ondragstart</u>                               | <i>script</i> | Script to be run at the start of a drag operation                          |
| <u>ondrop</u>                                    | <i>script</i> | Script to be run when dragged element is being dropped                     |
| <u>onscroll</u>                                  | <i>script</i> | Script to be run when an element's scrollbar is being scrolled             |

## Clipboard Events

| Attribute      | Value         | Description                                           |
|----------------|---------------|-------------------------------------------------------|
| <u>oncopy</u>  | <i>script</i> | Fires when the user copies the content of an element  |
| <u>oncut</u>   | <i>script</i> | Fires when the user cuts the content of an element    |
| <u>onpaste</u> | <i>script</i> | Fires when the user pastes some content in an element |

## Media Events

Events triggered by medias like videos, images and audio (applies to all HTML elements, but is most common in media elements, like `<audio>`, `<embed>`, `<img>`, `<object>`, and `<video>`).

**Tip:** Look at our [HTML Audio and Video DOM Reference](#) for more information.

| Attribute      | Value         | Description               |
|----------------|---------------|---------------------------|
| <u>onabort</u> | <i>script</i> | Script to be run on abort |



Tutorials ▼

References ▼

Exercises ▼



Sign In

[HTML](#)
[CSS](#)
[JAVASCRIPT](#)
[SQL](#)
[PYTHON](#)
[JAVA](#)
[PHP](#)
[W3.CSS](#)
[C](#)
[C++](#)

oncueplaythrough

script

Script to be run when a file can be played all the way to the end without pausing for buffering

[REMOVE ADS](#)

oncuechange

script

Script to be run when the cue changes in a <track> element

ondurationchange

script

Script to be run when the length of the media changes

onemptied

script

Script to be run when something bad happens and the file is suddenly unavailable (like unexpectedly disconnects)

onended

script

Script to be run when the media has reach the end (a useful event for messages like "thanks for listening")

onerror

script

Script to be run when an error occurs when the file is being loaded

onloadeddata

script

Script to be run when media data is loaded

onloadedmetadata

script

Script to be run when meta data (like dimensions and duration) are loaded

onloadstart

script

Script to be run just as the file begins to load before anything is actually loaded

onpause

script

Script to be run when the media is paused either by the user or programmatically

onplay

script

Script to be run when the media is ready to start playing

onplaying

script

Script to be run when the media actually has started playing

onprogress

script

Script to be run when the browser is in the process of getting the media data

onratechange

script

Script to be run each time the playback rate changes (like when a user switches to a slow motion or fast forward mode)

onseeked

script

Script to be run when the seeking attribute is set to false indicating that seeking has ended

onsuspend *script* Script to be run when the browser is unable to fetch the media data for whatever reason

[REMOVE ADS](#)

onsuspend *script* Script to be run when fetching the media data is stopped before it is completely loaded for whatever reason


ontimeupdate *script* Script to be run when the playing position has changed (like when the user fast forwards to a different point in the media)

onvolumechange *script* Script to be run each time the volume is changed which (includes setting the volume to "mute")

onwaiting *script* Script to be run when the media has paused but is expected to resume (like when the media pauses to buffer more data)

## Misc Events

| Attribute       | Value         | Description                                               |
|-----------------|---------------|-----------------------------------------------------------|
| <u>ontoggle</u> | <i>script</i> | Fires when the user opens or closes the <details> element |

[< Previous](#)
[Sign in to track progress](#)
[Next >](#)


[Tutorials ▼](#)[References ▼](#)[Exercises ▼](#)[Sign In](#)[CSS](#)[JAVASCRIPT](#)[SQL](#)[PYTHON](#)[JAVA](#)[PHP](#)[W3.CSS](#)[C](#)[C++](#)[REMOVE ADS](#) [Browse tools »](#)[PLUS](#)[SPACES](#)[GET CERTIFIED](#)[FOR TEACHERS](#)[BOOTCAMPS](#)[CONTACT US](#)

## Top Tutorials

- [HTML Tutorial](#)
- [CSS Tutorial](#)
- [JavaScript Tutorial](#)
- [How To Tutorial](#)
- [SQL Tutorial](#)
- [Python Tutorial](#)
- [W3.CSS Tutorial](#)
- [Bootstrap Tutorial](#)
- [PHP Tutorial](#)
- [Java Tutorial](#)
- [C++ Tutorial](#)
- [jQuery Tutorial](#)

## Top References

- [HTML Reference](#)
- [CSS Reference](#)
- [JavaScript Reference](#)
- [SQL Reference](#)
- [Python Reference](#)
- [W3.CSS Reference](#)
- [Bootstrap Reference](#)
- [PHP Reference](#)
- [HTML Colors](#)
- [Java Reference](#)
- [AngularJS Reference](#)
- [jQuery Reference](#)



[Tutorials ▼](#)[References ▼](#)[Exercises ▼](#)[Sign In](#)[CSS](#) [JAVASCRIPT](#) [SQL](#) [PYTHON](#) [JAVA](#) [PHP](#) [W3.CSS](#) [C](#) [C++](#)

[How To Examples](#)  
[SQL Examples](#)  
[Python Examples](#)  
[W3.CSS Examples](#)  
[Bootstrap Examples](#)  
[PHP Examples](#)  
[Java Examples](#)  
[XML Examples](#)  
[jQuery Examples](#)

[Front End Certificate](#)  
[SQL Certificate](#)  
[Python Certificate](#)  
[PHP Certificate](#)  
[jQuery Certificate](#)  
[Java Certificate](#)  
[C++ Certificate](#)  
[C# Certificate](#)  
[XML Certificate](#)

[FORUM](#) [ABOUT](#) [ACADEMY](#)

W3Schools is optimized for learning and training. Examples might be simplified to improve reading and learning.

Tutorials, references, and examples are constantly reviewed to avoid errors, but we cannot warrant full correctness of all content. While using W3Schools, you agree to have read and accepted our [terms of use](#), [cookies](#) and [privacy policy](#).

Copyright 1999-2026 by Refsnes Data. All Rights Reserved. [W3Schools](#) is Powered by [W3.CSS](#).