

ScPy: A SuperCollider Extension for Performing Numerical Computation via Embedded Python

Noah Weninger Abram Hindle

August 24, 2016

Abstract

SuperCollider, a language for sound synthesis and algorithmic composition of audio, supports a wide range of synthesis, effect and analysis algorithms. However, available operations are limited to those implemented explicitly as Unit Generators (UGens). Since UGens are written in C/C++ and loaded as plugins during the SuperCollider server boot process, it is impossible to live code UGens, which limits the user to creating sound as a composition of existing UGens during a performance. Many of the vector operations required for efficiently creating complex audio effects are notably missing or tedious to use. To overcome this, we present ScPy, a UGen which embeds Python within SuperCollider to enable the use of the optimized vector operations provided by the NumPy library.

1 Introduction

Although a number of open-source projects which interface other languages with SuperCollider exist, they are primarily SuperCollider clients, which have features to control synths and send other automation messages. One notable exception is OctaveSC, which embeds GNU Octave within SuperCollider. However, it is designed primarily for performing operations on control rate data arrays and its author notes performance issues which prevent it from being used on audio rate data.

One of the goals of this project is to enable more flexible experimentation with FFT and phase vocoder based operations. SuperCollider contains a total of 32 built in phase vocoder operations, which provide the ability to produce many common effects. There are additionally some extra operations available as user created extensions. However, many conceivable effects are impossible.

ScPy enables users to overcome these limitations. By embedding the Python programming language within SuperCollider, it is possible to do numerical processing operations which would be too slow to perform in real time with SuperCollider alone. Through access to the NumPy library, previously difficult or impossible phase vocoder operations become trivial. Although our usage of

this library for testing purposes has mostly focused on FFT based operations, support exists for passing arbitrary data buffers to Python, which can be used to process numerical data for many other purposes as well.

2 Methodology

During the initial planning stage of the project, we wanted to essentially provide a set of fundamental operations on spectral data which could be composed together to perform any conceivable effect. It was also a requirement that these operations would be syntactically concise in order to enable easy and fast experimentation. Ideally, the system would be able to handle complex effects in real-time.

Although designing a domain-specific language (DSL) for this task was briefly considered, we eventually decided to use Python for a number of reasons. First, Python includes an excellent C API which makes embedding it within other languages trivial in comparison to many other options. Second, Python's syntax is easily readable and concise – it clearly adheres to our goals. Finally, Python has a massive number of community built libraries for performant scientific and numerical computing. With a few small exceptions, these libraries contained every one of the fundamental spectral operations we could think of.

It may seem as though embedding an interpreted language within an interpreted language could offer no performance advantage. There is certainly some performance hit when switching languages and transferring data. However, the biggest advantage comes not strictly from performance but from the diversity of operations which become available with highly optimized implementations. NumPy is used internally by ScPy for handling data arrays, so the entire NumPy library of mathematical functions comes at no cost. Any other Python library can easily be imported as well. Limited experiments have been done with the SciPy library. It would also be possible to use Theano to do processing on the GPU for extra performance. Implementing an equivalent to these popular Python libraries in pure SuperCollider is certainly possible, but it would require a very large amount of work and would see little widespread adoption since SuperCollider is ultimately a niche language.

3 Usage

Use of ScPy is through two UGens: `Py` and `PyOnce`. Both have one required argument, a block of Python code. A map of variable names may optionally be provided to bind SuperCollider variables to Python variables. Additionally, there is an optional `DoneAction` argument which specifies an action to occur in SuperCollider after the Python code has finished executing.

```
1 (s.waitForBoot {
2   var buf = { Buffer.alloc(s, 512) }.dup;
3   var hop = 1/4;
4
5   s.freeAll; // stop previous versions
6
7   PyOnce("
8     def fn(x):
9       return x
10    ", (hop:hop));
11
12   {
13     var in = AudioIn.ar([1, 2]);
14     var x = FFT(buf.collect(_.bufnum), in, hop);
15     Py("
16       out(x, fn(array(x)))
17       ", (x:x, time:Sweep.kr));
18     Out.ar(0, IFFT(x));
19   }.play(s);
20 })
```

Listing 1: SuperCollider boilerplate for no-op FFT effect with ScPy.

When Listing 1 is run, an anonymous synth is created which will take in audio from an external source, perform a STFT, process the spectral data with ScPy, perform an inverse STFT, then finally output the resulting audio. Lines 8-9 contain Python code defining the processing function where operations are to be inserted. Further examples will replace only those lines. Line 16 contains the Python code to convert the spectrum into a NumPy array, process it, then write back the processed version.

4 Implementation

ScPy is written mostly in C++, but with a small SuperCollider class library to connect the C++ back-end, and a small Python library that provides some useful operations. Due to differences between these languages, connecting them was somewhat awkward in some cases.

Since UGens may only be used as part of a synth, `PyOnce` is provided as a wrapper which hides this detail from the user and allows the execution of Python code outside of a synth. It is useful for doing initialization work. Since the current implementation executes Python code in a single global namespace, a typical usage pattern is for state to be defined in a `PyOnce` block which is later accessed and modified in a `Py` block.

One issue involves the process of passing data between SuperCollider and C++. Since UGens are designed to work primarily with data streams, adding

support for passing in many types of data came with a number of challenges. Essentially, all data must be serialized into an array of floats. Strings must be converted to an array of ASCII character codes, and prepended with their length. Arguments passed through to the Python code can have one of many types, and therefore type information must be encoded as well. However, just passing the type of a variable is not enough to know what we can do with it, since we also want to know if it inherits from a class we can use.

Since **FFT** objects in SuperCollider operate on a single channel only, they must be placed in **Array** objects to support multichannel audio. **Arrays** can hold objects of any type, so it is natural to convert them to Python **list** objects, which have similar properties. However, this presents an interesting problem: multichannel **FFT** objects are then converted to **lists** of **ndarray** objects in Python. These are a bit more awkward to work with than basic **ndarray** objects, but can easily be converted using a call to the **array** function in Python. This can be seen in practice on line 16 of Listing 1. Although it would be possible to do this conversion automatically, it is left out for the purpose of not introducing a feature simply to work around an incomplete implementation of **FFT** objects in SuperCollider. The current conversions will continue to function as intended if **FFT** objects are given multichannel support in the future.

Table 1: Type correspondence between SuperCollider and Python

SuperCollider data type	Python data type
Float	float
UGen (subclass of)	ndarray of float
Buffer	ndarray of float
FFT	ndarray of complex
Array	list

5 Future Work

At the time of writing, ScPy only supports handling audio rate data via SuperCollider’s **Buffer** objects. In order to make some use cases more ergonomic, ScPy could certainly be extended to support raw audio rate input. For example, this would make time domain audio data even simpler to work with than frequency domain data is currently. It would also enable SuperCollider’s **FFT UGen** to be easily re-implemented in Python for greater flexibility.

6 Conclusion