

Inter-rater Reliability

Abram Hindle

2012-04-27 Tue

Outline

1 Introduction

2 Inter-rater reliability

Imagine

- We're tagging or rating items
 - commits
 - topics
 - bug reports
- We're using multiple people to tag or rate these items
- How do we ensure that we have agreement

Example

- “I made a change to the install documentation.”
 - Is this a portability relevant commit message?
- “I made a change to the install documentation regarding OSX.”
 - Is this a portability relevant commit message?
- “I made a change to the install documentation regarding OSX, Windows and Linux.”
 - Is this a portability relevant commit message?

We can disagree

- With ratings this is a problem
- Especially if we want to model or predict ratings
- How random are the ratings?
- Is there a bias?

Reliability

- So how reliability are ratings.
- Is there agreement?
- What does lack of agreement mean?

- We can measure correlation
 - Not really meant for it, but a good start
 - Pearson
 - Spearman
- Cohen's Kappa Statistic
 - Good for 2 raters
- Fleiss's Kappa
 - Good for more

- `Perason cor(x,y,method="pearson")`
- `Spearman cor(x,y,method="spearman")`
- `library(irr)`
- columns of a matrix
- `kappa2(yourMatrix)`
- `kappm.fleiss(yourMatrix)`

- Go and look at the code

What's a good Kappa or Correlation?

- 1 is good
- 0 or worse is bad
- 0.1 will get reviewers annoyed

Pay attention to

- num raters
- num subjects
- Kappa
- p-value

Threats to IRR

- Kappa of all same rank is NaN
- Lack of range in ratings 0,1 versus 1-5
- Class imbalance, if 10% is rated one way this can cause a problem