



Introduction

- Each year, one billion people are affected by influenza worldwide, causing between 290,000 and 650,000 deaths.
- In France, traditional flu surveillance relies on the Sentinelles system, which provides valuable but delayed indicators (1-3 weeks).
- Clinical Data Warehouses (CDWs) can reduce this lag by using structured and unstructured hospital data to deliver timely, validated case counts enriched with clinical details.
- The objective is to improve responsiveness to outbreaks by exploiting CDWs combined with heterogeneous sources, in order to predict the epidemic status of the following week, with a particular emphasis on early detection of the outbreak.


Combining data extraction and predicted models




Data extraction




➤ Data used to predict the status of week t+1



Results



Model	TP	FP	TN	FN	Recall	Precision	F1	DeltaStart	DurationDiff
rl_ehop	8	2	25	2	0.8	0.800	0.800	2	0
rl_ehop_weather_red	8	2	25	2	0.8	0.800	0.800	2	0
rf_ehop	8	1	26	2	0.8	0.889	0.842	2	-1
svm_ehop	8	1	26	2	0.8	0.889	0.842	2	-1
svm_ehop_weather_com	10	4	23	0	1.0	0.714	0.833	0	3
svm_ehop_weather_red	10	4	23	0	1.0	0.714	0.833	0	3
svm_ehop_weather_com_RS	10	3	24	0	1.0	0.769	0.870	0	3
svm_ehop_weather_red_RS	10	4	23	0	1.0	0.714	0.833	0	3



Conclusion

- We propose combining heterogeneous data sources through machine learning models to consistently improve forecasting accuracy and responsiveness of epidemiological indicators.
- It is possible to get closer to real time thanks to the CDW, whose data are updated with a delay of day+1. It is even possible to go further by trying to predict the beginning of an epidemic the following week.
- Future work could explore deep learning approaches such as MLPs and perform weight tuning to optimize the contribution of each variable and improve prediction performance.

References

- [1] Sylvestre E, Cécilia-Joseph E, Bouzillé G, Najjoulah F, Etienne M, Malouines F, et al. The Role of Heterogenous Real-world Data for Dengue Surveillance in Martinique: Observational Retrospective Study. JMIR Public Health and Surveillance. 2022 Dec 22;8(12):e37122. doi: 10.2196/37122.
- [2] Poirier C, Hsuen Y, Bouzillé G, Cuggia M, Lavenu A, Brownstein JS, et al. Influenza forecasting for French regions combining EHR, web and climatic data sources with a machine learning ensemble approach. PLOS ONE. 2021 May 19;16(5):e0250890. doi: 10.1371/journal.pone.0250890.
- [3] Petit-Jean T, Gérardin C, Berthelot E, Chatellier G, Frank M, Tannier X, et al. Collaborative and privacy-enhancing workflows on a clinical data warehouse: an example developing natural language processing pipelines to detect medical conditions. J Am Med Inform Assoc. 2024 May 20;31(6):1280–90. doi: 10.1093/jamia/ocae069.
- [4] Poirier C, Bouzillé G, Bertaud V, Cuggia M, Santillana M, Lavenu A. Gastroenteritis Forecasting Assessing the Use of Web and Electronic Health Record Data With a Linear and a Nonlinear Approach: Comparison Study. JMIR Public Health and Surveillance. 2023 Jan 31;9:e34982. doi: 10.2196/34982.



GitHub repository with the poster and the authors' contacts