

Name : Abrham Abebe

Section: CS2

Email : abrehamabebe1921@gmail.com

From this assignment, I understood how to configure and apply a named standard Access Control List (ACL) on a Cisco router. I learned that a standard ACL controls traffic based mainly on the source IP address. I also learned how to create a named ACL using the `ip access-list standard` command and add permit and deny statements. In this activity, I allowed PC1 with the IP address 192.168.20.4 to access the File Server while preventing the other workstations from accessing it. I learned how to apply the ACL to an interface using the `ip access-group` command and specify the traffic direction. Finally, I learned how to verify an ACL using `show access-lists` and `show ip interface` commands and test whether the restrictions are working correctly.

The image shows a network diagram and a list of configuration steps for a named standard ACL.

Network Diagram: A central router R1 is connected to four switches: Switch0, Switch1, Switch2, and Switch3. Switch0 is connected to PC2. Switch1 is connected to PC0 and PC1. Switch2 is connected to a Web Server (IP: 192.168.100.100/24). Switch3 is connected to a File Server (IP: 192.168.200.100/24).

Configuration Steps:

Step 2: Configure a named standard ACL.
Configure the following named ACL on R1.

```
R1(config)# ip access-list standard File_Server_Restrictions
R1(config-std-nacl)# permit host 192.168.20.4
R1(config-std-nacl)# deny any
```

Note: For scoring purposes, the ACL name is case-sensitive.

Step 3: Apply the named ACL.
a. Apply the ACL outbound on the interface Fast Ethernet 0/1.
R1(config-if)# ip access-group File_Server_Restrictions out
b. Save the configuration.

Part 2: Verify the ACL Implementation

Step 1: Verify the ACL configuration and application to the interface.
Use the `show access-lists` command to verify the ACL configuration. Use the `show run` or `show ip interface fastethernet 0/1` command to verify that the ACL is applied correctly to the interface.

Step 2: Verify that the ACL is working properly.
All three workstations should be able to ping the Web Server, but only PC1 should be able to ping the File Server.

Interface Configuration:

```
R1(config-if)# ip access-group File_Server_Restrictions out
```

Verification:

```
R1# show access-lists
R1# show run
R1# show ip interface fastethernet 0/1
```

Completion: 100/100

Buttons: Back, 1/1, Next

Time Elapsed: 00:12:11

Check Results

Scenario 0

Fire	Last Status	Source	Destination	Type	Color	Time(sec)	Periodic Num
------	-------------	--------	-------------	------	-------	-----------	--------------