



Class: End Dumps		Model: End Dump 4X	End Dump 4X
Standard Specifications - All dimensions are nominal.			
TRAILER			
	Overall Length	28 ft.	
	Overall Width	102 in.	
	King Pin to Rear Axle	295 in.	
	Rear Over Hang	9 in.	
	Rear Axle Setting	19 in.	
	Weight lbs +/- 3%		
	Cubic Capacity - No Planks		
	Cubic Capacity with Planks		
CHASSIS			
	Coupler Plate	1/2 in. Hi-Tensile, 49 in. Height	
	Coupler Location	16 in.	
	Beams	Fabricated T1 I-Beams, run full length	
	Landing Gear	Jost 10 year no Lube (A450.T2.17)	
BODY			
	Box Length	28 ft.	
	Box Height	60 in.	
	Box width	102 in.	
	Bulkhead	Slope Nose 1/4 in. AR450	
	Side Boards	No	
	Crossmembers	Steel Sills	
	Top Rail	1/4 in. c 4 in. x 6 in. Steel Box	
	Rear Posts	3/16 in. 50W	
	Side Skirts	Diamond plate Aluminum, 96 in. at front and 102 in. wide at rear over wheel	
	Bottom Rail	Steel Box	
	Sides	60 in. High 1/4 in. AR450	
	Tailgate	60 in. Straight Hi Lift Gate - Dual Acting, 1/4 in. Hardox, Access plates on rear posts and 40 in. spreader chains	
	Tailgate Seal	1/2 in. round sides and bottom	
	Spreader Chains	40 in.	
	Tailgate Locks	Air Operated	
	Compression Locks	1 per side	
	Wear Pad	6 in. x 3/8 in. pad on top of each Beam	
	Floor	1/4 in. AR450	
	Tarp	No	
	Dump Hoist	Custom Hoist 8-5-235	
	Ladder	1 on front drivers side, inside and outside	
	Remote Grease Block	Located at rear	
	Hydraulic Hose	9 Ft. with Wing Fittings	
SUSPENSION/AXLES			
	Axles	25,000 lbs Capacity 77.5 in. Track Synethetic Semi Fluid Grease	
	Spread	44 in. - 44 in. - 46 in.	
	Suspension	1 of Reyco 21B Triaxle Single Leaf Springs, 1 of AAL25K Lifiable Axle with Electric switch in box, 17 in. Ride Height	
	Control Box	Stainless Steel	
	Air Tanks	Steel	
	Air Gauge	Located at front	
	Brakes	16 1/2 in. x 7 in., Includes Dust Shields	
	Air Brake System	4S/2M Wabco	
	Hubs & Drums	10 Stud Cast Drums, Grease hubs	
	Tires	16 of 11R22.5 Continental HSR	
	Wheels	16 of 8.25 x 22.5 Steel Disc	



Class: End Dumps	Model: End Dump 4X	End Dump 4X
Standard Specifications - All dimensions are nominal.		
GENERAL SPECIFICATIONS		
Electrical System	Modular, Vapor Proof LED GROTE as per DOT Requirements	
Front Connector	SAE J560 7 Pin and ISO Connector	
Lights	2 of 4 in. per side at rear and 3 of 2 1/2 in. in center, 1 pair of flashers located below rail.	
Back up Lights	1 set	
Side Lights	3 per Side	
Air/Electrical Connections	setup for cab controls and plumbed for Hi Lift and air locks on gate	
Finishing	Sandblasted	
Color	Primed and Painted Black, consist of the Box , Beams, Axles	
Mudflaps	Full Flaps across rear	

In conjunction with continuous product improvements, BWS Manufacturing Ltd. reserves the right to make changes to products described and/or illustrated herein without notice or liability.

Prices subject to change without notice.

Date Printed:

February 15, 2022