



Class: End Dumps	Model: End Dump 4X	End Dump 4X
Standard Specifications - All dimensions are nominal.		
TRAILER		
Overall Length	30 ft. 2 in.	
Overall Width	102 in.	
King Pin to Rear Axle	295 in.	
Rear Over Hang	9 in.	
Rear Axle Setting	19 in.	
Weight lbs +/- 3%		
Cubic Capacity - No Planks		
Cubic Capacity with Planks		
CHASSIS		
Frame Length	28 ft.	
Coupler Plate	1/2 in. Hi-Tensile, 49 in. Height	
Coupler Location	16 in.	
Beams	Fabricated T1 I-Beams, run full length	
Crossmembers	Steel Sills	
Side Skirts	Diamond plate Aluminum, 96 in. at front and 102 in. wide at rear over wheel	
Landing Gear	Jost 10 year no Lube (A450.T2.17)	
BODY		
Box Length	27 ft. 6 in.	
Box Height	60 in.	
Box width	102 in.	
Bulkhead	Slope Nose 1/4 in. AR450	
Side Boards	No	
Rear Posts	3/16 in. 50W	
Top Rail	1/4 in. c 4 in. x 6 in. Steel Box	
Bottom Rail	Steel Box	
Sides	60 in. High 1/4 in. AR450	
Tailgate	60 in. Straight Hi Lift Gate - Dual Acting, 1/4 in. Hardox (or Equivalent), Access plates on rear posts and 40 in. spreader chains	
Tailgate Seal	1/2 in. round sides and bottom	
Spreader Chains	40 in.	
Tailgate Locks	Air Operated	
Compression Locks	1 per side	
Wear Pad	6 in. x 3/8 in. pad on top of each Beam	
Floor	1/4 in. AR450	
Tarp	No	
Dump Hoist	Custom Hoist 8-5-235	
Ladder	1 on front drivers side, inside and outside	
Remote Grease Block	Located at rear	
Hydraulic Hose	9 Ft. with Wing Fittings	
SUSPENSION/AXLES		
Axles	25,000 lbs Capacity 77.5 in. Track Synethetic Semi Fluid Grease	
Spread	44 in. - 44 in. - 46 in.	
Suspension	1 of Reyco 21B Triaxle Single Leaf Springs, 1 of AAL25K Lifiable Axle with Electric switch in box, 17 in. Ride Height	
Control Box	Stainless Steel	

29 HAWKINS ROAD, CENTREVILLE, NB E7K 1A4 CANADA 888 896.5777

www.TRAILERMADESTRONG.com



Class: End Dumps	Model: End Dump 4X	End Dump 4X
Standard Specifications - All dimensions are nominal.		
Air Tanks	Steel	
Air Gauge	Located at front	
Brakes	16 1/2 in. x 7 in., Includes Dust Shields	
Air Brake System	4S/2M Wabco	
Hubs & Drums	10 Stud Cast Drums	
Tires	16 of 11R22.5 Continental HSR	
Wheels	16 of 8.25 x 22.5 Steel Disc	
GENERAL SPECIFICATIONS		
Electrical System	Modular, Vapor Proof LED GROTE as pe rDOT Requirements	
Front Connector	SAE J560 7 Pin and ISO Connector	
Lights	2 of 4 in. per side at rear and 3 of 2 1/2 in. in center, 1 pair of flashers located below rail.	
Back up Lights	1 set	
Side Lights	3 per Side	
Air/Electrical Connections	setup for cab controls and plumbed for Hi Lift and air locks on gate	
Finshing	Steel Shot Blast	
Color	Primed and Painted Black, consist of the Box, beams, Axles	
Mudflaps	Full Flaps across rear	

In conjunction with continuous product improvements, BWS Manufacturing Ltd. reserves the right to make changes to products described and/or illustrated herein without notice or liability.

Prices subject to change without notice.

Date Printed: 15-Feb-22