



Rev 0

Class: End Dumps

Model: End Dump 4X ✓

End Dump 4X

Standard Specifications - All dimensions are nominal.

TRAILER

Overall Frame Length ~~45 ft. 6 in.~~ 28 ft
Overall Box Length ~~44 ft. 6 in.~~ 28 ft
Width ~~102 in.~~ 96 in w/ 102 in frame
Board Size None Required
Wall Height ~~54 in.~~ 60 in
Weight lbs +/- 3% 21,000
Cubic Yard Capacity 80

CHASSIS

Frame Construction 18 in. Extruded Aluminum Beam Construction, Milled Finish + Bumper - HD Michiga
King Pin Height 49 in.
King Pin Location 18 in.
Fifth Wheel Plate ~~5/16 in~~ 3/8 in
Wear Pad 6 in Braided rubber on top of frame to act as buffer between box and frame
Ride Axle Configuration 4 of 25,000 lbs Capacity
Extra Lift Kit None Required URL-002 on lead
Lift Axle Control Valve RA220-IN
Steer Axle Configuration Ingersol with IMT (Dexter) Steer None
Axle Spread 72 in. - 72 in. - 100 in
Ride Suspension 4 of Hendrickson Intraax - Webb Slacks, TSE Long Stroke Booster, fixed
Ride Suspension Control Electric
Steer Suspension Ingersol with IMT (Dexter) Steer None
Steer Suspension Control Electric None
Wheel Monitor None Required
Bearing Proper Equal Inner and Outer
Hubs & Drums Duralight Hubs and Drums
Brakes 16 1/2 x 7 Drum
Dust Shields Included
Ride Rims 8.25 x 22.5 Aluminum Alcoa, High Polish outside, steel inside
Steer Rims ~~12.25 x 22.5 Aluminum Alcoa, High Polish~~ None
Ride Tires 11R22.5 Continental HSR-2
Steer Tires ~~385/65/22.5 Continental HTR-2~~ None
Hubmeter None Required
Spare Tire Carrier None Required
ABS Wabco 2S/1M
Weight Gauge Located on front at 45 degree
Frame Finish Milled, Non Polished
Paint Color for Steel Compo Black, galv hangers
Board Color None Required
Mudflaps 3 Flaps Across the Rear of the Trailer, short flaps in front of front axle
Fenders on Front None Required
Fenders Over Axles None Required
Calcium Tank None Required
Air Tanks Aluminum
Landing Gear ~~Just 10 year, No Lube w/ Painted, Landing Gear and Braces~~ Alum
Toolbox None Required

BOX CONSTRUCTION

Wall Panels AR450F Hardox, single piece
Wall Thickness 2 in. Hollow Core Double Wall 6061 Aluminum Extrusion. Fully Welded Interior Wall
Wall Finish ~~Outside Wall 0.094 (3/32) in. and Inside Wall 0.125 (1/8) in.~~ 3/16"
Last 5 Rear Wall Panels ~~Polished~~ > remove



Class: End Dumps

Model: End Dump 4X

End Dump 4X

Standard Specifications - All dimensions are nominal.

BOX CONSTRUCTION

Floor Construction	250 (1/4 in.) 6061 Aluminum Sheets welded together, supported by Reinforced Extruded Aluminum, C-Channel crossmembers on 12 in. centers 1/4" AR450F Hardox single sheet 3 1/2" AR450 box
Floor Liner	None Required 16 + Bottom radius - 22"
Bulkhead Construction	3/16 in. 5083 Aluminum Sheets with Corners Formed into a Radius Flat slope nose
Tailgate	Heavy Duty 2 in. Hollow Core Double Wall 6061 Aluminum Extrusion. Fully Welded inside extruded frame 1/4" Hardox AR450F
Tailgate Slope	Straight + Top Rail - 3/16" x 4" x 6
Tailgate Type	Overslung (Hinged at top), air assist hi-lift w/ 3" x 3" x 3/8" angle option
Tailgate Locks (Stainless)	Manual Air cylinder
Tailgate Hinges	Stainless remove
Compression Locks	None Required 1 per side of tailgate
Rear Tailgate Seal	Rubber Seal + Remote Grease - single point rear w hoist
Grain Chute	None Required + Side Skirts - none @ front, alum diamond plate full length @ rear
Sock Adapter	None Required + Front Cab Shield - 12" cab shield
Header Type	None Required + Rear End Style - squared off
Tarp	None Required + Spreader Chains - yes w/ cover
Tarp Drive	None Required
Front Tarp Shield	None Required
Rear Tarp Shield	None Required
Tarp Color	None Required
Tarp Supplies	None Required
Cross Pipes	None Required
Man Door	None Required 8-5-235
Hoist Size	CUSTOM 95-4500-340 (Minimum of 59.4 Gallons required to Fully Extend Cylinders)
Square Offs	Installed on Top Front Outside Corners of Box remove
Catwalk	None Required
Shovel Holder	Located on dog house curbside
Broom Holder	Located on dog house None
Asphalt Lip	None Provided (If required It is 8 in. with no compression locks and 6 in. with bottom compression locks)
Steps - Front, Driver Side	None Required Fixed steel ladder on outside
Steps - Rear, Driver Side	None Required Steel ladder outside
Steps - Front Passenger Side	None Required
Steps - Rear, Passenger Side	None Required
Jug Holder	None Required
Fork Lift Package	None Required
Hydraulic Hose	None Required 1" x 108" hose w female quick-connect
Document Holder	Standard Round

LIGHTING/ELECTRICAL

Electrical System	Grote
Lights	LED CMVSS 108 / FMVSS 108
LED Type	Colored
Rear Lighting	3 of 4 in. per side at rear 9 of 4" at rear, grouped in 3 (ooo ooo,
Rear Center Plate Lights	None Required 1 pair of small
Lights Located in Bottom Rail	5 of 2 1/2 in. Amber evenly spaced per side
Lights Located in Top Wall	None Required
Tarp Shield Lights	None Required. They can only be mounted in tarp shield for Slide N Go Tarp Only
Tailgate Lights	None Required
Tailgate Post Lights	None Required
Signal Lights on Sides	Located in the Siderail



Class: End Dumps

Model: End Dump 4X

End Dump 4X

Standard Specifications - All dimensions are nominal.

LIGHTING/ELECTRICAL

Reverse Lights below the rail

None Required

Light Shield

~~1/4 in. x 2 in.~~

3/8" x 4" full apron light shield

In conjunction with continuous product improvements, BWS Manufacturing Ltd. reserves the right to make changes to products described and/or illustrated herein without notice or liability.

Prices subject to change without notice.

Date Printed:

March 16, 2023

