



Class: B-Trains		Model: BTL3X+2X	BTL3X+2X
Standard Specifications - All dimensions are nominal.			
1 - TRAILER			
	10 - Overall Frame Length	35 ft.	
	20 - Overall Box Length	34 ft.	
	25 - Width	102 in	
	30 - Board Size	None Required	
	40 - Wall Height	60 in.	
	60 - Weight lbs +/- 3%	16,500	
	70 - Cubic Yard Capacity	61	
28 - CHASSIS			
	10 - Frame Construction	18 in. Extruded Aluminum Beam Construction, Milled Finish	
	40 - Wear Pad	6 in. Braided rubber on top of frame to act as buffer between box and frame	
	50 - Ride Axle Configuration	3 of 25,000 lbs Capacity	
	60 - Extra Lift Kit	None Required	
	70 - Lift Axle Control Valve	None Required, for use with Lift Axle only	
	80 - Steer Axle Configuratio	None Required	
	90 - Axle Spread	72 in.	
	100 - Ride Suspension	3 of Hendrickson Intraax - Webb Slacks, TSE Long Stroke Booster, fixed	
	101 - Ride Suspension Contr	Electric	
	110 - Steer Suspension	None Required	
	111 - Steer Suspension Cont	None Required	
	120 - Wheel Monitor	None Required	
	130 - Bearing	Propar Equal Inner and Outer	
	140 - Hubs & Drums	Duralight Hubs and Drums	
	145 - Dust Shields	Included	
	150 - Ride Rims	8.25 x 22.5 Aluminum Alcoa, High Polish	
	160 - Steer Rims	None Required	
	170 - Ride Tires	11R22.5 Continental HSR-2	
	180 - Steer Tires	None Required	
	190 - Hubmeter	None Required	
	200 - Spare Tire Carrier	None Required	
	210 - ABS	Wabco 2S/1M	
	220 - Weight Gauge	Located on front at 45 degree	
	230 - Frame Finish	Milled, Non Polished	
	250 - Paint Color for Steel C	Black	
	260 - Board Color	None Required	
	270 - Mudflaps	3 Flaps Across the Rear of the Trailer	
	280 - Fenders on Front	None Required	
	290 - Fenders Over Axles	None Required	
	300 - Calcium Tank	None Required	
	310 - Air Tanks	Aluminum	
	330 - Toolbox	None Required	



Class: B-Trains	Model: BTL3X+2X	BTL3X+2X
Standard Specifications - All dimensions are nominal.		
34 - BOX CONSTRUCTION		
10 - Wall Panels	2 in. Hollow Core Double Wall 6061 Aluminum Extrusion. Fully Welded Interior Wall	
30 - Wall Thickness	Outside Wall 0.094 (3/32)in. and Inside Wall 0.125 (1/8) in.	
40 - Wall Finish	Polished	
50 - Last 5 Rear Wall Panels	Outside Wall 0.094 (3/32)in. and Inside Wall 0.125 (1/8) in.	
70 - Floor Construction	.250 (1/4 in.) 6061 Aluminum Sheets welded together, supported by Reinforced Extruded Aluminum, C-Channel crossmembers on 12 in. centers	
80 - Floor Liner	None Required	
90 - Bulkhead Construction	3/16 in. 5083 Aluminum Sheets with Corners Formed into a Radius	
100 - Tailgate	Heavy Duty 2 in. Hollow Core Double Wall 6061 Aluminum Extrusion. Fully Welded inside extruded frame	
110 - Tailgate Slope	Straight	
120 - Tailgate Type	Overslung (Hinged at top)	
130 - Tailgate Locks (Stainles	Manual	
135 - Tailgate Hinges	Stainless	
140 - Compression Locks	None Required	
150 - Rear Tailgate Seal	Rubber Seal	
160 - Grain Chute	None Required	
170 - Sock Adapter	None Required	
180 - Header Type	None Required	
190 - Tarp	None Required	
200 - Tarp Drive	None Required	
210 - Front Tarp Shield	None Required	
220 - Rear Tarp Shield	None Required	
230 - Tarp Color	None Required	
240 - Tarp Supplies	None Required	
250 - Cross Pipes	None Required	
260 - Man Door	None Required	
270 - Hoist Size	CUSTOM 95-4500-280 (Minimum of 48.9 Gallons required to Fully Extend Cylinders)	
280 - Square Offs	Installed on Top Front Outside Corners of Box	
290 - Catwalk	None Required	
300 - Shovel Holder	Located on Dog House	
310 - Broom Holder	Located on Dog House	
320 - Asphalt Lip	None Provided (If required It is 8 in. with no compression locks and 6 in. with bottom compression locks)	
330 - Steps - Front, Driver Si	None Required	
331 - Steps - Rear, Driver Sid	None Required	
340 - Steps - Front Passenge	None Required	
341 - Steps - Rear, Passenge	None Required	
350 - Jug Holder	None Required	
360 - Fork Lift Package	None Required	
370 - Hydraulic Hoses	None Required	
380 - Document Holder	Standard Round	



Class: B-Trains		Model: BTL3X+2X	BTL3X+2X
Standard Specifications - All dimensions are nominal.			
44 - DOLLY			
10 - No of Dolly Axles		2	
20 - Drawbar		66 in.	
30 - Turntable		SAF Holland	
40 - Lock Pin		Double Lock Pin	
50 - Axles		71.5 in. AXN, Oil Lubricated	
60 - Axle Spacing		44 in.	
70 - Suspension Control		AAT Hendrickson Intraax, Air Ride, 13 1/2 in. Ride Height	
80 - Brake Shoes		7 in. XL, 2/30/30 Chambers	
90 - Hub and Drum		Cast with SteelHub 10 Stud TP, LS, 7 in.	
100 - Tires		11R22.5 Continental HSR-2	
110 - Wheels		8.25 x 22.5 in. 10 Hole; Steel inside and Aloca LVL outside	
120 - Fenders		Plastic Quarter Fenders	
73 - LIGHTING/ELECTRICAL			
10 - Electrical System		Grote	
20 - Lights		LED CMVSS 108 / FMVSS 108	
30 - LED Type		Colored	
40 - Rear Lighting		3 of 4 in. per side at rear	
50 - Rear Center Plate Lights		None Required	
60 - Lights Located in Botto		3 of 2 1/2 in. Amber evenly spaced per side	
70 - Lights Located in Top W		None Required	
80 - Tarp Shield Lights		None Required. They can only be mounted in tarp shield for Slide N Go Tarp Only	
90 - Tailgate Lights		None Required	
100 - Tailgate Post Lights		None Required	
110 - Signal Lights on Sides		Located in the Siderail	
120 - Reverse Lights below t		None Required	
130 - Light Shield		1/4 in. x 2 in.	

In conjunction with continuous product improvements, BWS Manufacturing Ltd. reserves the right to make changes to products described and/or illustrated herein without notice or liability.

Prices subject to change without notice.

Date Printed: 20-Mar-23