



Class: B-Trains	Model: BTL3X	BTL3X
-----------------	--------------	-------

Standard Specifications - All dimensions are nominal.

1 - TRAILER

10 - Overall Frame Length	35 ft.
20 - Overall Box Length	34 ft.
25 - Width	102 in
30 - Board Size	None Required
40 - Wall Height	60 in.
60 - Weight lbs +/- 3%	16,500
70 - Cubic Yard Capacity	61

28 - CHASSIS

10 - Frame Construction	18 in. Extruded Aluminum Beam Construction, Milled Finish
20 - King Pin Height	49 in.
30 - King Pin Location	15 in.
35 - Fifth Wheel Plate	5/16 in
40 - Wear Pad	6 in. Braided rubber on top of frame to act as buffer between box and frame
50 - Ride Axle Configuration	3 of 25,000 lbs Capacity
60 - Extra Lift Kit	None Required
70 - Lift Axle Control Valve	None Required, for use with Lift Axle only
80 - Steer Axle Configuratio	None Required
90 - Axle Spread	72 in.
100 - Ride Suspension	3 of Hendrickson Intraax - Webb Slacks, TSE Long Stroke Booster, fixed
101 - Ride Suspension Contr	Electric
110 - Steer Suspension	None Required
111 - Steer Suspension Cont	None Required
120 - Wheel Monitor	None Required
130 - Bearing	Propar Equal Inner and Outer
140 - Hubs & Drums	Duralight Hubs and Drums
145 - Dust Shields	Included
150 - Ride Rims	8.25 x 22.5 Aluminum Alcoa, High Polish
160 - Steer Rims	None Required
170 - Ride Tires	11R22.5 Continental HSR-2
180 - Steer Tires	None Required
190 - Hubmeter	None Required
200 - Spare Tire Carrier	None Required
210 - ABS	Wabco 2S/1M
220 - Weight Gauge	Located on front at 45 degree
230 - Frame Finish	Milled, Non Polished
250 - Paint Color for Steel C	Black
260 - Board Color	None Required
270 - Mudflaps	3 Flaps Across the Rear of the Trailer
280 - Fenders on Front	None Required
290 - Fenders Over Axles	None Required
300 - Calcium Tank	None Required
310 - Air Tanks	Aluminum
320 - Landing Gear	Jost 10 year, No Lube w/Painted, Landing Gear and Braces
330 - Toolbox	None Required
340 - Pintle Hook	T-990

29 HAWKINS ROAD, CENTREVILLE, NB E7K 1A4 CANADA 888 896.5777

www.TRAILERMADESTRONG.com



Class: B-Trains	Model: BTL3X	BTL3X
Standard Specifications - All dimensions are nominal.		
34 - BOX CONSTRUCTION		
10 - Wall Panels	2 in. Hollow Core Double Wall 6061 Aluminum Extrusion. Fully Welded Interior Wall	
30 - Wall Thickness	Outside Wall 0.094 (3/32)in. and Inside Wall 0.125 (1/8) in.	
40 - Wall Finish	Polished	
50 - Last 5 Rear Wall Panels	Outside Wall 0.094 (3/32)in. and Inside Wall 0.125 (1/8) in.	
70 - Floor Construction	.250 (1/4 in.) 6061 Aluminum Sheets welded together, supported by Reinforced Extruded Aluminum, C-Channel crossmembers on 12 in. centers	
80 - Floor Liner	None Required	
90 - Bulkhead Construction	3/16 in. 5083 Aluminum Sheets with Corners Formed into a Radius	
100 - Tailgate	Heavy Duty 2 in. Hollow Core Double Wall 6061 Aluminum Extrusion. Fully Welded inside extruded frame	
110 - Tailgate Slope	Straight	
120 - Tailgate Type	Overslung (Hinged at top)	
130 - Tailgate Locks (Stainles	Manual	
135 - Tailgate Hinges	Stainless	
140 - Compression Locks	None Required	
150 - Rear Tailgate Seal	Rubber Seal	
160 - Grain Chute	None Required	
170 - Sock Adapter	None Required	
180 - Header Type	None Required	
190 - Tarp	None Required	
200 - Tarp Drive	None Required	
210 - Front Tarp Shield	None Required	
220 - Rear Tarp Shield	None Required	
230 - Tarp Color	None Required	
240 - Tarp Supplies	None Required	
250 - Cross Pipes	None Required	
260 - Man Door	None Required	
270 - Hoist Size	CUSTOM 95-4500-280 (Minimum of 48.9 Gallons required to Fully Extend Cylinders)	
280 - Square Offs	Installed on Top Front Outside Corners of Box	
290 - Catwalk	None Required	
300 - Shovel Holder	Located on Dog House	
310 - Broom Holder	Located on Dog House	
320 - Asphalt Lip	None Provided (If required It is 8 in. with no compression locks and 6 in. with bottom compression locks)	
330 - Steps - Front, Driver Si	None Required	
331 - Steps - Rear, Driver Sid	None Required	
340 - Steps - Front Passenge	None Required	
341 - Steps - Rear, Passenge	None Required	
350 - Jug Holder	None Required	
360 - Fork Lift Package	None Required	
370 - Hydraulic Hoses	None Required	
380 - Document Holder	Standard Round	



Class: B-Trains	Model: BTL3X	BTL3X
Standard Specifications - All dimensions are nominal.		
73 - LIGHTING/ELECTRICAL		
10 - Electrical System	Grote	
20 - Lights	LED CMVSS 108 / FMVSS 108	
30 - LED Type	Colored	
40 - Rear Lighting	3 of 4 in. per side at rear	
50 - Rear Center Plate Lights	None Required	
60 - Lights Located in Botto	3 of 2 1/2 in. Amber evenly spaced per side	
70 - Lights Located in Top W	None Required	
80 - Tarp Shield Lights	None Required. They can only be mounted in tarp shield for Slide N Go Tarp Only	
90 - Tailgate Lights	None Required	
100 - Tailgate Post Lights	None Required	
110 - Signal Lights on Sides	Located in the Siderail	
120 - Reverse Lights below t	None Required	
130 - Light Shield	1/4 in. x 2 in.	

In conjunction with continuous product improvements, BWS Manufacturing Ltd. reserves the right to make changes to products described and/or illustrated herein without notice or liability.

Prices subject to change without notice.

Date Printed: 20-Mar-23