



Class: B-Trains	Model: ED4X Detroit T	ED4X Detroit T
-----------------	-----------------------	----------------

Standard Specifications - All dimensions are nominal.

1 - TRAILER

10 - Overall Frame Length	45 ft. 6 in.
20 - Overall Box Length	44 ft. 6 in.
25 - Width	102 in.
30 - Board Size	None Required
40 - Wall Height	54 in.
60 - Weight lbs +/- 3%	21,000
70 - Cubic Yard Capacity	80

28 - CHASSIS

10 - Frame Construction	18 in. Extruded Aluminum Beam Construction, Milled Finish
20 - King Pin Height	49 in.
30 - King Pin Location	18 in.
35 - Fifth Wheel Plate	5/16 in
40 - Wear Pad	6 in. Braided rubber on top of frame to act as buffer between box and frame
50 - Ride Axle Configuration	3 of 25,000 lbs Capacity
60 - Extra Lift Kit	None Required
70 - Lift Axle Control Valve	RA220-IN
80 - Steer Axle Configuratio	Ingersol with IMT (Dexter) Steer
90 - Axle Spread	72 in. - 72 in. - 100 in
100 - Ride Suspension	3 of Hendrickson Intraax - Webb Slacks, TSE Long Stroke Booster, fixed
101 - Ride Suspension Contr	Electric
110 - Steer Suspension	Ingersol with IMT (Dexter) Steer
111 - Steer Suspension Cont	Electric
120 - Wheel Monitor	None Required
130 - Bearing	Propar Equal Inner and Outer
140 - Hubs & Drums	Duralight Hubs and Drums
145 - Brakes	16 1/2 x 7 Drum
145 - Dust Shields	Included
150 - Ride Rims	8.25 x 22.5 Aluminum Alcoa, High Polish
160 - Steer Rims	12.25 x 22.5 Aluminum Alcoa, High Polish
170 - Ride Tires	11R22.5 Continental HSR-2
180 - Steer Tires	385/65/22.5 Continental HTR-2
190 - Hubmeter	None Required
200 - Spare Tire Carrier	None Required
210 - ABS	Wabco 2S/1M
220 - Weight Gauge	Located on front at 45 degree
230 - Frame Finish	Milled, Non Polished
250 - Paint Color for Steel C	Black
260 - Board Color	None Required
270 - Mudflaps	3 Flaps Across the Rear of the Trailer
280 - Fenders on Front	None Required
290 - Fenders Over Axles	None Required
300 - Calcium Tank	None Required
310 - Air Tanks	Aluminum
320 - Landing Gear	Jost 10 year, No Lube w/Painted, Landing Gear and Braces
330 - Toolbox	None Required



Class: B-Trains	Model: ED4X Detroit T	ED4X Detroit T
-----------------	-----------------------	----------------

Standard Specifications - All dimensions are nominal.

34 - BOX CONSTRUCTION

10 - Wall Panels	2 in. Hollow Core Double Wall 6061 Aluminum Extrusion. Fully Welded Interior Wall
30 - Wall Thickness	Outside Wall 0.094 (3/32)in. and Inside Wall 0.125 (1/8) in.
40 - Wall Finish	Polished
50 - Last 5 Rear Wall Panels	Outside Wall 0.094 (3/32)in. and Inside Wall 0.125 (1/8) in.
70 - Floor Construction	.250 (1/4 in.) 6061 Aluminum Sheets welded together, supported by Reinforced Extruded Aluminum, C-Channel crossmembers on 12 in. centers
80 - Floor Liner	None Required
90 - Bulkhead Construction	3/16 in. 5083 Aluminum Sheets with Corners Formed into a Radius
100 - Tailgate	Heavy Duty 2 in. Hollow Core Double Wall 6061 Aluminum Extrusion. Fully Welded inside extruded frame
110 - Tailgate Slope	Straight
120 - Tailgate Type	Overslung (Hinged at top)
130 - Tailgate Locks (Stainles	Manual
135 - Tailgate Hinges	Stainless
140 - Compression Locks	None Required
150 - Rear Tailgate Seal	Rubber Seal
160 - Grain Chute	None Required
170 - Sock Adapter	None Required
180 - Header Type	None Required
190 - Tarp	None Required
200 - Tarp Drive	None Required
210 - Front Tarp Shield	None Required
220 - Rear Tarp Shield	None Required
230 - Tarp Color	None Required
240 - Tarp Supplies	None Required
250 - Cross Pipes	None Required
260 - Man Door	None Required
270 - Hoist Size	CUSTOM 95-4500-340 (Minimum of 59.4 Gallons required to Fully Extend Cylinders)
280 - Square Offs	Installed on Top Front Outside Corners of Box
290 - Catwalk	None Required
300 - Shovel Holder	Located on Dog House
310 - Broom Holder	Located on Dog House
320 - Asphalt Lip	None Provided (If required It is 8 in. with no compression locks and 6 in. with bottom compression locks)
330 - Steps - Front, Driver Si	None Required
331 - Steps - Rear, Driver Sid	None Required
340 - Steps - Front Passenge	None Required
341 - Steps - Rear, Passenge	None Required
350 - Jug Holder	None Required
360 - Fork Lift Package	None Required
370 - Hydraulic Hose	None Required
380 - Document Holder	Standard Round



Class: B-Trains	Model: ED4X Detroit T	ED4X Detroit T
------------------------	------------------------------	-----------------------

Standard Specifications - All dimensions are nominal.

73 - LIGHTING/ELECTRICAL

10 - Electrical System	Grote
20 - Lights	LED CMVSS 108 / FMVSS 108
30 - LED Type	Colored
40 - Rear Lighting	3 of 4 in. per side at rear
50 - Rear Center Plate Lights	None Required
60 - Lights Located in Botto	3 of 2 1/2 in. Amber evenly spaced per side
70 - Lights Located in Top W	None Required
80 - Tarp Shield Lights	None Required. They can only be mounted in tarp shield for Slide N Go Tarp Only
90 - Tailgate Lights	None Required
100 - Tailgate Post Lights	None Required
110 - Signal Lights on Sides	Located in the Siderail
120 - Reverse Lights below t	None Required
130 - Light Shield	1/4 in. x 2 in.

In conjunction with continuous product improvements, BWS Manufacturing Ltd. reserves the right to make changes to products described and/or illustrated herein without notice or liability.

Prices subject to change without notice.

Date Printed: 20-Mar-23