



Class: Sanimax		Model: ED2X Sanimax	End Dump 2X - US Spread
Standard Specifications - All dimensions are nominal.			
TRAILER			
	Length	40 ft. Frame, 39 ft. 6 in. Box	
	Width	96 in. Inboard	
CHASSIS			
	Frame	T-1 Steel	
	Frame Length	40 Ft.	
	King Pin Position	16 in. Bolt in Pin (Holland with wire), Galvanized Square	
BOX CONSTRUCTION			
	Length	39 ft.	
	Wall Heights	70 in. Durawall	
	Wall Finish	Polished	
	Board Size	No Boards	
	Panels	Wall inside 1/8 in.	
	Floor	1/4 in. full aluminum in 5083	
	Crossmembers	Spaced at 12 in. center	
	Splash Guards	Located in front and rear part of trailer, 40 in. long, full width of trailer	
	Mud Flap	At rear follow the law in USA (bottom of mudflap to the ground)	
	Mud Flap Positioning	0 Ol, (Located at rear) All Stargate, needs 6 in. wear pad on flaps and needs to be flush at rear	
	Shovel Holders	Front bulkhead helper outside	
	Steps Front	6 in. x 12 in. serrated, Inside steps mounted on rear face of divider	
	Steps Rear	No steps at rear	
	Divider	Not Provided	
	Z-Rail with holes	Long Z-Rail with holes (shredder plate 10 in. maximum) install customers hinges	
	Hinges on Z-Rail	Install hinges, supplied by customer, at the top of the Z-Rail so that thy can open it for cleaning	
	Shredder Plate	Shredder Plate to have 3/8 in. holes draining @ 1 1/2 in. c/c (6 lines of holes) from back of the divider all the way to the rear	
	Top Rail & Wall	IMPORTANT: Picture 31 (ref 8907) "A" needs to be flush with "B" no gap or notch between the top rail and the wall, need to be smooth all way long	
	Cross Tubes	2 of 4 in. Risetop Cross tubes	
	Shutters	Don't install durt shutters each side of hoist door because blood tank goes there	
	Drain Valves	Add 4 x 3 drain valves - 3 per side, first to be 3 ft. rearward at landing gear, 2nd forward first axle, 3rd forward rear axle	
	Tailgate	72 in. No Slope (Straight), Manual	
	Tailgate Seals	ZZD-303152 High Thickness Door Seal	
	Grain Door	None Provided	
	Compression Locks	3 Compression Locks at the bottom + 6 Compression Locks on the sides (3 on each side)	
	Hoist	None Required but with Dog House and setup for future hoist	
	Hydraulic Connection	None Required	
	Hoist Door	None Required	
	Top Hoist Pin	Top Hoist Pin to be removable from outside	
	Tarp	No Tarp with NO corner at front	
	Body Hold Down	Secure body to frame, front and middle body guides	
	Waterproof	100% waterproof all welding	
SUSPENSION/AXLES			
	Suspension	Hendrickson Intraax (30,000 lbs) with Galvanized Hangers	
	Axle Configuartion	121 in.	
	ABS Braking System and val	Bendix 2S/1M with all vlave to be Bendix	
	Hub and Drums	Duralite Hub, standard drums	
	Bearing	Big Bearing, P Spindle with Grease Bearing	
	Air Tank	Aluminum, Install in frame highest position possible within the frame	
	Air Gauge	Located inside control box	



Class: Sanimax	Model: ED2X Sanimax	End Dump 2X - US Spread
Standard Specifications - All dimensions are nominal.		
SUSPENSION/AXLES		
Booster	TSE, Long Life	
Ride Rims	22.5, White Steel	
Ride Tires	11R22.5, Continental HSR-2	
Slack Adjusters	WEBB	
Hubdometer	Located on Driver Side front axle, in Miles	
Control Box	Stainless Steel, must be 18 in. to the rear of the dolly leg	
Tire Carrier	None Provided	
Landing Gear	Holland Mark V	
Landing Gear and Hanger	Space between land gear and hanger suspension will be 133 in.	
Fender	Aluminum	
GENERAL SPECIFICATIONS		
Lights in Siderail	3 of LED Amber including turn signal, per side	
Center Rear Plate	4 of 4 in. and 3 of 2 1/2 in.	
Flasher	Inside rail	
Color	Aluminum Frame with Landing Gear painted PPG Blue, 114027	
Document Holder	Installed on Stainless Control Box	

In conjunction with continuous product improvements, BWS Manufacturing Ltd. reserves the right to make changes to products described and/or illustrated herein without notice or liability.

Prices subject to change without notice.

Date Printed:

June 30, 2022