



Class: Sanimax		Model: ED4X Sanimax	End Dump 4X Quebec SAN Pork
Standard Specifications - All dimensions are nominal.			
TRAILER			
	Length	45 ft. Frame, 44 ft. Box	
	Width	102 in. Inboard	
	King Pin to rear Axle	495 in. to rear axle, 21 in. setting at rear	
CHASSIS			
	Frame	T-1 Steel	
	Frame Length	44 Ft. 6 in.	
	King Pin Position	18 in. Bolt in Pin (Holland with wire) with Galvanized Square	
BOX CONSTRUCTION			
	Length	44 ft.	
	Wall Heights	72 in. Durawall	
	Wall Finish	Polished	
	Body Hold Downs	Secure Body to frame front and midlle body guides	
	Board Size	No Boards	
	Panels	Wall inside 1/8 in.	
	Floor	1/4 in. full aluminum in 5083	
	Crossmembers	Spaced at 12 in. center to center	
	Splash Guards	None Provided	
	Mud Flap	At rear follow the law in Ontario (bottom of mudflap to the ground)	
	Mud Flap Positioning	O1O1O1O1, short flaps at front and flaps Located behind each axle grouping and 3 across the rear at 42 in.) All Stargate, needs 6 in. wear pad on flaps and needs to be flush at rear	
	Shovel Holders	Front bulkhead helper outside	
	Steps Front	6 in. x 12 in. Serrated, Inside steps mounted on rear face of divider	
	Steps Rear	No steps at rear	
	Divider	None Provided	
	Z-Rail with holes	Long Z-Rail with holes (shredder plate 10 in. maximum), must be removable	
	Tailgate Hinges	Double Hinge to hold 5000 kg, mounted as high as possible	
	Hinges on Z-Rail	Install hinges, supplied by customer, at the top of the Z-Rail so that thy can open it for cleaning	
	Shredder Plate	Shredder Plate to have 3/8 in. holes draining @ 1 1/2 in. c/c (6 lines of holes) from back of the divider all the way to the rear	
	Top Rail & Wall	IMPORTANT: Needs to be flush with no gap or notch between the top rail and the wall, need to be smooth all way long	
	Cross Tubes	2 of 4 in. rise top Cross tubes, 1st at 1/3 and 2nd at 2/3 of the box	
	Shutters	Don't install durt shutters each side of hoist door because blood tank goes there	
	Drain Valves	Add 6 x 3 drain valves - 3 per side at center of the 2 last axles, at center of the steering axle and tridem and 375 1/2 from rear of floor (Tailgate)	
	Tailgate	72 in. No Slope (Straight), Manual	
	Tailgate Seals	ZZD-303152 High Thickness Door Seal	
	Grain Door	None Provided	
	Compression Locks	3 Compression Locks at the bottom + 6 Welded Compression Locks on the sides (3 on each side)	
	Hoist	Customer will supply their own, Stargate will install. Need grease zerk at top and bottom of hoist	
	Hydraulic Connection	Quick Coupler plug 1 in.	
	Hoist Door	Hoist Door at front box: made small door to be able to put in and out the top pin of hoist by the hoist door, cut out on Nose to be 18 in. L x 13 in. IPO 12 in. L x 13 in. W	
	Top Hoist Pin	Top Hoist Pin to be removable from outside	
	Tarp	No Tarp with NO corner at front	
	Ontario Inspection	To be completed	
	Waterproof	Trailer must be tested and be 100% waterproof on all welding	
SUSPENSION/AXLES			
	Suspension	Tridem Hendrickson Intraax (30,000 lbs) with Galvanized Hangers	
	Steering Axle	Hendrickson Suspension and axle with Air Bag inside frame (Single Tire Application)	
	Axle Configuartion	72 in - 72 in. - 100 in.	



Class: Sanimax	Model: ED4X Sanimax	End Dump 4X Quebec SAN Pork
Standard Specifications - All dimensions are nominal.		
SUSPENSION/AXLES		
ABS Braking System and val	Wabco 2S/1M ECU with all Bendix Valves	
Hub and Drums	Duralite Hub, standard drums	
Bearing	Big Bearing, P Spindle with Grease Bearing	
Air Tank	Aluminum, Install in frame highest position possible within the frame	
Air Gauge	Located inside control box	
Booster	TSE, Long Life	
Ride Rims	8.25 x 22.5, Steel, White	
Steering Rims	Aluminum Alcoa LVL, 22.5	
Ride Tires	11R22.5, Continental HSR-2	
Steering Tires	385/65R22.5, Continental HTR-2	
Slack Adjusters	WEBB	
Hubdometer	Located on center Axle, Driver Side front axle, in KM's	
Wheel Monitor	RM 50	
Control Box	Stainless Steel, must be 18 in. to the rear of the dolly leg	
Tire Carrier	Installed between steering and tridem, curb side	
Landing Gear	Holland Mark V, 30 in.	
Landing Gear and Hanger	Space between land gear and hanger suspension will be 133 in. plus tank height is 28 in. TO BE CHECK IF POSSIBLE	
Fender	17 in. Polished Aluminum Checkerplate	
GENERAL SPECIFICATIONS		
Lights in Siderail	3 of LED Amber including turn signal, per side	
Center Rear Plate	4 of 4 in. and 3 of 2 1/2 in.	
Additional Lighting	Extra Cable run at rear for future customer gate hopper install	
Harness	Run 7 way to top of pocket with 20 ft. extra wire for future lights on tank installed on tailgate (Harness to run form rear light plate to front post)	
Color	Galvanized Frame with Landing Gear Painted PPG Blue, 114027	
Document Holder	Installed on Stainless Control Box	

In conjunction with continuous product improvements, BWS Manufacturing Ltd. reserves the right to make changes to products described and/or illustrated herein without notice or liability.

Prices subject to change without notice.

Date Printed:

June 30, 2022