



Class: Walking Floor		Model: Walking Floor 3X	Walking Floor 3X
Standard Specifications - All dimensions are nominal.			
TRAILER			
	Overall Length	48 ft.	
	Overall Width	102 in.	
	Overall Height	156 1/2 in.	
	Inside Wall Height	100 in.	
	Weight lbs +/- 3%	21,500	
	Cubic Yard Capacity	120	
CHASSIS			
	Subframe	10 in. Extruded I-Beam	
	Crossmembers	5 1/4 in. Extruded Aluminum I-Beam	
	Coupler Plate	5/16 in. 100,000 PSI	
	Coupler Height	48 in.	
	Coupler Location	36 in.	
	Tractor Drive Model	Tandem Drive	
	Axle Spacing	49 in.	
	Ride Axle Suspension	Hendrickson Intraax AAT 30K-15 AL-Drum	
	Suspension Hangers	Standard Steel	
	Lift Kits	None Required	
	Lift/Steer Axle	None Required	
	Lift/Steer Suspension	None Required	
	Steer Lift Kit	None Required	
	Steer Lift Controls	None Required	
	Lift/Steer Suspension Contr	None Required	
	Brakes	Drum	
	ABS	Wabco 2S/1M	
	Air Tanks	Aluminum	
	Ride Rims	8.25 x 22.5 - 10 Whole Steel, Powder Coated White	
	Steer Tires	None Required	
	Ride Tires	11R22.5 Continental HSR-2, 16 ply	
	Steer Rims	None Required	
	Tire Carrier	None Required	
	Tire Inflation System	None Required	
	Chrome Top Hats	None Required	
	Hubmeter	None Required	
	Enclosure for switches	Stainless Steel	
	Landing Gear	Jost A450, 10 year no lube, Gear on Driver side	
	Bumper	Steel Heavy Duty Push Bumper with Tow Hook	
BOX CONSTRUCTION			
	Panel Type - Front	Standard 1/8 in.	
	Panel Type - Center	Standard 1/8 in.	
	Panel Type - Rear	Standard 1/8 in.	
	Tapered Sides	100 in. No Taper Required	
	Tapered Fender Wells	None Required	
	Top Rail	6061 Extruded Aluminum	
	Floor	2190 7/32 in.	
	Drive unit	3 1/2 in. Keith Cylinder	
	PTO Capacity	30 GPM @ 3000 psi	
	Hydraulic Valves	set for Keith Mobile Floor	
	Retractable Sweep System	None Required	
	Hydraulic Pipe	Stainless Steel	
	Compactor Compatible	No	



Class: Walking Floor	Model: Walking Floor 3X	Walking Floor 3X
Standard Specifications - All dimensions are nominal.		
BOX CONSTRUCTION		
Roof	None Required	
Upper Cross Tubes/Caps	2 Steel Tubes (1 at Mid and 1 at Rear)	
Wear Plate Rear 6 Ft.	None Required	
Bulkhead	2 in. Durawall Panel	
Bulkhead Steps	None Required	
Catwalk	None Required	
Hose Bracket on Catwalk	None Required	
Mandoor	None Required	
Hydraulic Pipe	9 ft. with winged style fitting	
Tailgate Panels	Durawall Hollow Core	
Tailgate Hinge Type	Swing style, Curbside	
Tailgate Operation	Mechanical Paddle Latch	
Safety Chains	Included	
Compression Locks/Winder	None Required	
Tailgate Steps	None Required	
Tarp Model	None Required	
Tarp Control	None Required	
Bow Holders	None Required	
Bows	None Required	
Tarp Color	None Required	
Tarp Hooks	None Required	
Tarp Bar	None Required	
Straps and Ratchet	None Required	
Tarp Supplies	None Required	
GENERAL SPECIFICATIONS		
Light Type	Grote LED with Grommet	
Rear Lights	3 of 4 in. per side and 3 of 2 1/2 in. in center	
Marker Lights in Bottom Rail	3 of 2 1/2 in.	
Marker Lights in Top Wall	None Required	
Light Shield	None Required	
Back up Lights	None Required	
Midway Turns	1 pair located in the siderail	
Paint Color	Metallic Silver	
Rear Mudflaps	Rubber Flaps full width	
Additional Mudflaps	None Required	
Document Holder	Round Holder Included	

In conjunction with continuous product improvements, BWS Manufacturing Ltd. reserves the right to make changes to products described and/or illustrated herein without notice or liability.

Prices subject to change without notice.

Date Printed:

November 21, 2022