



Class: End Dumps		Model: End Dump 4X	End Dump 4X
Standard Specifications - All dimensions are nominal.			
TRAILER			
	Overall Frame Length	35 ft.	
	Overall Box Length	34 ft.	
	Board Size	2 in. x 6 in. Spruce	
	Weight lbs +/- 2%		
	Cubic Capacity		
	Cubic Capacity w/boards		
CHASSIS			
	Frame Construction	18 in. Extruded Aluminum Beam Construction, Milled Finish	
	King Pin Height	49 in.	
	King Pin Location	15 in.	
	Wear Pad	6 in. Braided rubber on top of frame to act as buffer between box and frame	
	Ride Axle Configuration	3 of 25,000 lbs Capacity	
	Extra Lift Kit	None Required	
	Lift Axle Control Valve	None Required, for use with Lift Axle only	
	Steer Axle Configuration	None Required	
	Axle Spread	72 in.	
	Ride Suspension	3 of Hendrickson Intraax - Webb Slacks, TSE Long Stroke Booster, fixed	
	Wheel Monitor	None Required	
	Steer Suspension	None Required	
	Bearing	Propar Equal Inner and Outer	
	Hubs & Drums	Duralight Hubs and Drums	
	Ride Rims	Aluminum 22.5 Alcoa LVL	
	Steer Rims	None Required	
	Ride Tires	11R22.5 Continental HSR-2	
	Steer Tires	None Required	
	Hubmeter	None Required	
	Spare Tire Carrier	None Required	
	ABS	Haldex 2S/1M	
	Weight Gauge	Located on front at 45 degree	
	Frame Finish	Milled, Non Polished	
	Paint Color for Steel Compo	Black	
	Board Color	Black	
	Mudflaps	3 Flaps Across the Rear of the Trailer	
	Fenders on Front	None Required	
	Fenders Over Axles	None Required	
	Calcium Tank	None Required	
	Air Tanks	Aluminum	
	Landing Gear	Jost 10 year, No Lube w/Painted, Landing Gear and Braces	
	Toolbox	None Required	
BOX CONSTRUCTION			
	Wall Panels	2 in. Hollow Core Double Wall 6061 Aluminum Extrusion. Fully Welded Interior Wall	
	Wall Height	60 in.	
	Wall Thickness	Outside Wall 0.094 (3/32)in. and Inside Wall 0.125 (1/8) in.	
	Wall Finish	Polished	
	Last 5 Rear Wall Panels	Outside Wall 0.094 (3/32)in. and Inside Wall 0.125 (1/8) in.	
	Floor Construction	.250 (1/4 in.) 6061 Aluminum Sheets welded together, supported by Reinforced Extruded Aluminum, C-Channel crossmembers on 12 in. centers	
	Floor Liner	None Required	



Class: End Dumps	Model: End Dump 4X	End Dump 4X
Standard Specifications - All dimensions are nominal.		
BOX CONSTRUCTION		
Bulkhead Construction	3/16 in. 5083 Aluminum Sheets with Corners Formed into a Radius	
Tailgate	2 in. Hollow Core Double Wall 6061 Aluminum Extrusion. Fully Welded inside extruded frame	
Tailgate Slope	Straight	
Tailgate Type	Overslung (Hinged at top)	
Tailgate Locks (Stainless)	Manual	
Compression Locks	None Required	
Rear Tailgate Seal	Rubber Seal	
Grain Chute	None Required	
Sock Adapter	None Required	
Header Type	None Required	
Tarp	None Required	
Tarp Drive	None Required	
Front Tarp Shield	None Required	
Rear Tarp Shield	None Required	
Tarp Color	None Required	
Tarp Supplies	None Required	
Cross Pipes	None Required	
Man Door	None Required	
Hoist Size	CUSTOM 95-4500-280 (Minimum of 49 Gallons required to Fully Extend Cylinders)	
Square Offs	Installed on Top Front Outside Corners of Box	
Catwalk	None Required	
Shovel Holder	Located on Dog House	
Broom Holder	Located on Dog House	
Asphalt Lip	None Provided (If required It is 8 in. with no compression locks and 6 in. with bottom compression locks)	
Steps - Front, Driver Side	None Required	
Steps - Rear, Driver Side	None Required	
Steps - Front Passenger Side	None Required	
Steps - Rear, Passenger Side	None Required	
Jug Holder	None Required	
Fork Lift Package	None Required	
LIGHTING/ELECTRICAL		
Electrical System	Grote	
Lights	LED CMVSS 108 / FMVSS 108	
LED Type	Colored	
Rear Lighting	3 of 4 in. per side at rear	
Rear Center Plate Lights	None Required	
Lights Located in Bottom Rai	3 of 2 1/2 in. Amber evenly spaced per side	
Lights Located in Top Rail	None Required	
Tarp Shield Lights	None Required. They can only be mounted in tarp shield for Slide N Go Tarp Only	
Tailgate Lights	None Required	
Tailgate Post Lights	None Required	
Signal Lights on Sides	Located in the Siderail	
Reverse Lights below the rai	None Required	

In conjunction with continuous product improvements, BWS Manufacturing Ltd. reserves the right to make changes to products described and/or illustrated herein without notice or liability.

Prices subject to change without notice.

Date Printed:

February 16, 2022