



Date Printed: 17-Mar-23

BTL3X+2X**BTL3X+2X****B-Trains**

Promotional Drawing	24-Mar-23	Approved By	☐	Base Weight:	16,500	Base Price	\$111,886
----------------------------	-----------	--------------------	--------------------------	---------------------	--------	-------------------	-----------

TRAILER

Overall Frame Length	35 ft.
Overall Box Length	34 ft.
Width	102 in
Board Size	None Required
Wall Height	60 in.
Weight lbs +/- 3%	16500, including options
Cubic Yard Capacity	61

CHASSIS

Frame Construction	18 in. Extruded Aluminum Beam Construction, Milled Finish
Wear Pad	6 in. Braided rubber on top of frame to act as buffer between box and frame
Ride Axle Configuration	3 of 25,000 lbs Capacity
Extra Lift Kit	None Required
Lift Axle Control Valve	None Required, for use with Lift Axle only
Steer Axle Configuration	None Required
Axle Spread	72 in.
Ride Suspension	3 of Hendrickson Intraax - Webb Slacks, TSE Long Stroke Booster, fixed
Ride Suspension Control	Electric
Steer Suspension	None Required
Steer Suspension Control	None Required
Wheel Monitor	None Required
Bearing	Propar Equal Inner and Outer
Hubs & Drums	Duralight Hubs and Drums
Dust Shields	Included
Ride Rims	8.25 x 22.5 Aluminum Alcoa, High Polish
Steer Rims	None Required
Ride Tires	11R22.5 Continental HSR-2
Steer Tires	None Required
Hubmeter	None Required
Spare Tire Carrier	None Required
ABS	Wabco 2S/1M
Weight Gauge	Located on front at 45 degree
Frame Finish	Milled, Non Polished
Paint Color for Steel Compo	Black
Board Color	None Required
Mudflaps	3 Flaps Across the Rear of the Trailer
Fenders on Front	None Required
Fenders Over Axles	None Required
Calcium Tank	None Required
Air Tanks	Aluminum
Toolbox	None Required

BOX CONSTRUCTION

Wall Panels	2 in. Hollow Core Double Wall 6061 Aluminum Extrusion. Fully Welded Interior Wall
Wall Thickness	Outside Wall 0.094 (3/32)in. and Inside Wall 0.125 (1/8) in.
Wall Finish	Polished



Date Printed: 17-Mar-23

BTL3X+2X**BTL3X+2X****B-Trains**

Promotional Drawing	24-Mar-23	Approved By	☐	Base Weight:	16,500	Base Price	\$111,886
----------------------------	-----------	--------------------	--------------------------	---------------------	--------	-------------------	-----------

BOX CONSTRUCTION

Last 5 Rear Wall Panels	Outside Wall 0.094 (3/32)in. and Inside Wall 0.125 (1/8) in.
Floor Construction	.250 (1/4 in.) 6061 Aluminum Sheets welded together, supported by Reinforced Extruded Aluminum, C-Channel crossmembers on 12 in. centers
Floor Liner	None Required
Bulkhead Construction	3/16 in. 5083 Aluminum Sheets with Corners Formed into a Radius
Tailgate	Heavy Duty 2 in. Hollow Core Double Wall 6061 Aluminum Extrusion. Fully Welded inside extruded frame
Tailgate Slope	Straight
Tailgate Type	Overslung (Hinged at top)
Tailgate Locks (Stainless)	Manual
Tailgate Hinges	Stainless
Compression Locks	None Required
Rear Tailgate Seal	Rubber Seal
Grain Chute	None Required
Sock Adapter	None Required
Header Type	None Required
Tarp	None Required
Tarp Drive	None Required
Front Tarp Shield	None Required
Rear Tarp Shield	None Required
Tarp Color	None Required
Tarp Supplies	None Required
Cross Pipes	None Required
Man Door	None Required
Hoist Size	CUSTOM 95-4500-280 (Minimum of 48.9 Gallons required to Fully Extend Cylinders)
Square Offs	Installed on Top Front Outside Corners of Box
Catwalk	None Required
Shovel Holder	Located on Dog House
Broom Holder	Located on Dog House
Asphalt Lip	None Provided (If required It is 8 in. with no compression locks and 6 in. with bottom compression locks)
Steps - Front, Driver Side	None Required
Steps - Rear, Driver Side	None Required
Steps - Front Passenger Side	None Required
Steps - Rear, Passenger Side	None Required
Jug Holder	None Required
Fork Lift Package	None Required
Hydraulic Hoses	None Required
Document Holder	Standard Round

DOLLY

No of Dolly Axles	*NPO*: 2
Drawbar	*NPO*: 66 in.
Turntable	*NPO*: SAF Holland
Lock Pin	*NPO*: Double Lock Pin



Date Printed: 17-Mar-23

BTL3X+2X**BTL3X+2X****B-Trains**

Promotional Drawing	24-Mar-23	Approved By	☐	Base Weight:	16,500	Base Price	\$111,886
---------------------	-----------	-------------	--------------------------	--------------	--------	------------	-----------

DOLLY

Axles	*NPO*: 71.5 in. AXN, Oil Lubricated
Axle Spacing	*NPO*: 44 in.
Suspension Control	*NPO*: AAT Hendrickson Intraax, Air Ride, 13 1/2 in. Ride Height
Brake Shoes	*NPO*: 7 in. XL, 2/30/30 Chambers
Hub and Drum	*NPO*: Cast with Steel Hub 10 Stud TP, LS, 7 in.
Tires	*NPO*: 11R22.5, Continental HSR-2
Wheels	*NPO*: 8.25 x 22.5 in, 10 Hole, (Steel inside and Aloca LVL outside)
Fenders	*NPO*: Plastic Quarter Fenders

LIGHTING/ELECTRICAL

Electrical System	Grote
Lights	LED CMVSS 108 / FMVSS 108
LED Type	Colored
Rear Lighting	3 of 4 in. per side at rear
Rear Center Plate Lights	None Required
Lights Located in Bottom Rail	3 of 2 1/2 in. Amber evenly spaced per side
Lights Located in Top Wall	None Required
Tarp Shield Lights	None Required. They can only be mounted in tarp shield for Slide N Go Tarp Only
Tailgate Lights	None Required
Tailgate Post Lights	None Required
Signal Lights on Sides	Located in the Siderail
Reverse Lights below the rail	None Required
Light Shield	1/4 in. x 2 in.

Options & NPOs:	3	Weight:	0	Price:	\$0
-----------------	---	---------	---	--------	-----

Approved for:	Remorques Lewis Inc.		
Dealer Branch:	Main Branch - La Presentation		
Sales Person:	Pierre-Antony Cote		
Customer:			
Work Order #		Serial Number:	
Sales Order #		PO Number:	
PO Date:		Delivery Date:	
Order Date:		Payment Terms:	Net 10 Days
Prepared by:	Avery Briggs		
Authorized Signature:			
QUOTE IS VALID FOR 15 DAYS			

Invoicing Information Per Trailer		
Gross Price (CAD)		\$111,886
Slot Program Discount	1.0%	-\$1,119
Subtotal		\$110,767
	0.0%	\$0
Subtotal		\$110,767
	0.0%	\$0
Payable in CDN Funds:		\$110,767
FOB Milton, Ontario APPLICABLE TAXES & SHIPPING NOT INCLUDED		

Special Instructions

* Represents Major Component Changes (requires Structural Alterations and cannot be included on finished Trailer Products)