

Algorithm Design & Analysis (CS3383)¹

Unit 1: Divide and Conquer Introduction

Rasoul Shahsavarifar

January 14, 2019

¹Thanks to Dr. Patricia Evans and Dr. David Bremner at UNB, Dr. Erik Demaine at MIT for sharing the teaching stuffs

Outline²

Divide and Conquer

Intro

Merge Sort

Recursion Tree for recurrences

Integer Multiplication

²Reading:

- ▶ Main textbook (DPV), Divide and conquer algorithms, Chapter 2 mainly 2.1 to 2.5
- ▶ Algorithms, Cormen, Chapter 4 (4.2, 4.3, 4.4, 4.5)

unit prereqs

- ▶ mergesort
- ▶ geometric series (CLRS A.5)

Contents

Divide and Conquer

Intro

Merge Sort

Recursion Tree for recurrences

Integer Multiplication

Structure of divide and conquer

```
function SOLVE( $P$ )  
  if  $|P|$  is small then  
    SolveDirectly( $P$ )  
  else  
     $P_1 \dots P_k = \text{Partition}(P)$   
    for  $i = 1 \dots k$  do  
       $S_i = \text{Solve}(P_i)$   
    end for  
    Combine( $S_1 \dots S_k$ )  
  end if  
end function
```

► Where is the actual work?

Structure of divide and conquer

```
function SOLVE( $P$ )  
  if  $|P|$  is small then  
    SolveDirectly( $P$ )  
  else  
     $P_1 \dots P_k = \text{Partition}(P)$   
    for  $i = 1 \dots k$  do  
       $S_i = \text{Solve}(P_i)$   
    end for  
    Combine( $S_1 \dots S_k$ )  
  end if  
end function
```

- ▶ Where is the actual work?
- ▶ How many subproblems?

Structure of divide and conquer

```
function SOLVE( $P$ )  
  if  $|P|$  is small then  
    SolveDirectly( $P$ )  
  else  
     $P_1 \dots P_k = \text{Partition}(P)$   
    for  $i = 1 \dots k$  do  
       $S_i = \text{Solve}(P_i)$   
    end for  
    Combine( $S_1 \dots S_k$ )  
  end if  
end function
```

- ▶ Where is the actual work?
- ▶ How many subproblems?
- ▶ How big are the subproblems?

Contents

Divide and Conquer

Intro

Merge Sort


Recursion Tree for recurrences


Integer Multiplication

Merge Sort

Input:

10	2	5	3	7	13	1	6
----	---	---	---	---	----	---	---






Merge sort

MERGE-SORT $A[1 \dots n]$

1. If $n = 1$, done.
2. Recursively sort $A[1 \dots \lceil n/2 \rceil]$ and $A[\lceil n/2 \rceil + 1 \dots n]$.
3. “*Merge*” the 2 sorted lists.

Key subroutine: **MERGE**



Merging two sorted arrays


20 12

13 11

7 9

2

1



Merging two sorted arrays


20 12

13 11


7 9


2 1

1





Merging two sorted arrays







Merging two sorted arrays







Merging two sorted arrays







Merging two sorted arrays







Merging two sorted arrays







Merging two sorted arrays







Merging two sorted arrays







Merging two sorted arrays







Merging two sorted arrays






Merging two sorted arrays






Merging two sorted arrays



Time = $\Theta(n)$ to merge a total of n elements (linear time).



Analyzing merge sort

$T(n)$

$\Theta(1)$

$2T(n/2)$


$\Theta(n)$



MERGE-SORT $A[1 \dots n]$

1. If $n = 1$, done.
2. Recursively sort $A[1 \dots \lceil n/2 \rceil]$ and $A[\lceil n/2 \rceil + 1 \dots n]$.
3. ***Merge*** the 2 sorted lists


Sloppiness: Should be $T(\lceil n/2 \rceil) + T(\lfloor n/2 \rfloor)$,
but it turns out not to matter asymptotically.



Recurrence for merge sort


$$T(n) = \begin{cases} \Theta(1) & \text{if } n = 1; \\ 2T(n/2) + \Theta(n) & \text{if } n > 1. \end{cases}$$

- We shall usually omit stating the base case when $T(n) = \Theta(1)$ for sufficiently small n , but only when it has no effect on the asymptotic solution to the recurrence.
- We will see several ways starting with "Rec. Tree" to find a good upper bound on $T(n)$.



Recursion tree


Solve $T(n) = 2T(n/2) + cn$, where $c > 0$ is constant.



Recursion tree


Solve $T(n) = 2T(n/2) + cn$, where $c > 0$ is constant.


$$T(n)$$



Recursion tree


Solve $T(n) = 2T(n/2) + cn$, where $c > 0$ is constant.






Recursion tree


Solve $T(n) = 2T(n/2) + cn$, where $c > 0$ is constant.






Recursion tree


Solve $T(n) = 2T(n/2) + cn$, where $c > 0$ is constant.






Recursion tree


Solve $T(n) = 2T(n/2) + cn$, where $c > 0$ is constant.






Recursion tree


Solve $T(n) = 2T(n/2) + cn$, where $c > 0$ is constant.







Recursion tree

Solve $T(n) = 2T(n/2) + cn$, where $c > 0$ is constant.






Solve $T(n) = 2T(n/2) + cn$, where $c > 0$ is constant.




Solve $T(n) = 2T(n/2) + cn$, where $c > 0$ is constant.



Recursion tree

Solve $T(n) = 2T(n/2) + cn$, where $c > 0$ is constant.



Contents

Divide and Conquer

Intro

Merge Sort

Recursion Tree for recurrences

Integer Multiplication

Example

$$T(n) = 2T(3n/8) + n^2$$

► board

Contents

Divide and Conquer

Intro

Merge Sort

Recursion Tree for recurrences

Integer Multiplication

Integer Multiplication

Consider the problem of multiplying together two arbitrarily large numbers.

Integer Multiplication

Consider the problem of multiplying together two arbitrarily large numbers.

Input: positive integers x and y , each n bits long

Output: positive integer z where $z = x \cdot y$

Integer Multiplication

Consider the problem of multiplying together two arbitrarily large numbers.

Input: positive integers x and y , each n bits long

Output: positive integer z where $z = x \cdot y$

A straightforward approach using base-2 arithmetic, akin to how we multiply by hand, takes $\Theta(n^2)$ time.

Integer Multiplication

Consider the problem of multiplying together two arbitrarily large numbers.

Input: positive integers x and y , each n bits long

Output: positive integer z where $z = x \cdot y$

A straightforward approach using base-2 arithmetic, akin to how we multiply by hand, takes $\Theta(n^2)$ time.

Could we do better if we used results from subinstances?

Integer Multiplication

A Divide and Conquer approach can be considered to be a very large scale version of multiplication, only using base $2^{\lfloor \frac{n}{2} \rfloor}$ instead of a constant base.

Integer Multiplication

A Divide and Conquer approach can be considered to be a very large scale version of multiplication, only using base $2^{\lfloor \frac{n}{2} \rfloor}$ instead of a constant base.

For simplicity we assume that n is a power of 2, so $\frac{n}{2}$ will always be integer.

Integer Multiplication

A Divide and Conquer approach can be considered to be a very large scale version of multiplication, only using base $2^{\lfloor \frac{n}{2} \rfloor}$ instead of a constant base.

For simplicity we assume that n is a power of 2, so $\frac{n}{2}$ will always be integer.

So we split the bitstring for each of x and y in half, generating x_L, x_R, y_L, y_R such that

$$\begin{aligned}x &= 2^{\frac{n}{2}} \cdot x_L + x_R \\ y &= 2^{\frac{n}{2}} \cdot y_L + y_R.\end{aligned}$$

Using x_L, x_R, y_L, y_R we can now express our multiplication of the n -bit integers as *four* multiplications of $\frac{n}{2}$ -bit integers:

$$\begin{aligned}x \cdot y &= (2^{\frac{n}{2}} \cdot x_L + x_R) \cdot (2^{\frac{n}{2}} \cdot y_L + y_R) \\&= 2^n \cdot x_L y_L + 2^{\frac{n}{2}} \cdot (x_L y_R + x_R y_L) + x_R y_R\end{aligned}$$

Using x_L, x_R, y_L, y_R we can now express our multiplication of the n -bit integers as *four* multiplications of $\frac{n}{2}$ -bit integers:

$$\begin{aligned}x \cdot y &= (2^{\frac{n}{2}} \cdot x_L + x_R) \cdot (2^{\frac{n}{2}} \cdot y_L + y_R) \\&= 2^n \cdot x_L y_L + 2^{\frac{n}{2}} \cdot (x_L y_R + x_R y_L) + x_R y_R\end{aligned}$$

Computing this with four half-size multiplications gives us a time recurrence of

$$T(n) = 4T\left(\frac{n}{2}\right) + cn$$

Computing this with four half-size multiplications gives us a time recurrence of

$$T(n) = 4T\left(\frac{n}{2}\right) + cn$$

since the operations to split the numbers and put the multiplication results together all take time linear in the number of bits:

- ▶ the numbers are split by bitshifting

Computing this with four half-size multiplications gives us a time recurrence of

$$T(n) = 4T\left(\frac{n}{2}\right) + cn$$

since the operations to split the numbers and put the multiplication results together all take time linear in the number of bits:

- ▶ the numbers are split by bitshifting
- ▶ combining the recursion results takes three addition operations and two bitshifts, all linear

To solve $T(n) = 4T(\frac{n}{2}) + cn$, we can use recursion tree analysis. Each instantiation makes four calls, each on half the size, and takes linear time otherwise, so:

To solve $T(n) = 4T(\frac{n}{2}) + cn$, we can use recursion tree analysis. Each instantiation makes four calls, each on half the size, and takes linear time otherwise, so:

$$T(n) = \sum_{i=0}^{\log_2 n} c \cdot \frac{n}{2^i} \cdot 4^i$$

To solve $T(n) = 4T(\frac{n}{2}) + cn$, we can use recursion tree analysis. Each instantiation makes four calls, each on half the size, and takes linear time otherwise, so:

$$\begin{aligned} T(n) &= \sum_{i=0}^{\log_2 n} c \cdot \frac{n}{2^i} \cdot 4^i \\ &= cn \cdot \sum_{i=0}^{\log_2 n} \frac{4^i}{2^i} = cn \cdot \sum_{i=0}^{\log_2 n} 2^i \end{aligned}$$

To solve $T(n) = 4T(\frac{n}{2}) + cn$, we can use recursion tree analysis. Each instantiation makes four calls, each on half the size, and takes linear time otherwise, so:

$$\begin{aligned} T(n) &= \sum_{i=0}^{\log_2 n} c \cdot \frac{n}{2^i} \cdot 4^i \\ &= cn \cdot \sum_{i=0}^{\log_2 n} \frac{4^i}{2^i} = cn \cdot \sum_{i=0}^{\log_2 n} 2^i \end{aligned}$$

A geometric series

To solve $T(n) = 4T(\frac{n}{2}) + cn$, we can use recursion tree analysis. Each instantiation makes four calls, each on half the size, and takes linear time otherwise, so:

$$\begin{aligned} T(n) &= \sum_{i=0}^{\log_2 n} c \cdot \frac{n}{2^i} \cdot 4^i \\ &= cn \cdot \sum_{i=0}^{\log_2 n} \frac{4^i}{2^i} = cn \cdot \sum_{i=0}^{\log_2 n} 2^i \end{aligned}$$

A geometric series

$$= cn \cdot \frac{2^{\log_2 n + 1} - 1}{2 - 1} = 2cn \cdot 2^{\log_2 n} - cn$$

To solve $T(n) = 4T(\frac{n}{2}) + cn$, we can use recursion tree analysis. Each instantiation makes four calls, each on half the size, and takes linear time otherwise, so:

$$\begin{aligned} T(n) &= \sum_{i=0}^{\log_2 n} c \cdot \frac{n}{2^i} \cdot 4^i \\ &= cn \cdot \sum_{i=0}^{\log_2 n} \frac{4^i}{2^i} = cn \cdot \sum_{i=0}^{\log_2 n} 2^i \end{aligned}$$

A geometric series

$$= cn \cdot \frac{2^{\log_2 n + 1} - 1}{2 - 1} = 2cn \cdot 2^{\log_2 n} - cn$$

$$= 2cn \cdot n - cn = 2cn^2 - cn \in \Theta(n^2)$$

Gauss's Method

Consider a different way of computing $(x_L y_R + x_R y_L)$, the coefficient of $2^{\frac{n}{2}}$.

Gauss's Method

Consider a different way of computing $(x_L y_R + x_R y_L)$, the coefficient of $2^{\frac{n}{2}}$.

We are already computing $x_L y_L$ and $x_R y_R$

Gauss's Method

Consider a different way of computing $(x_L y_R + x_R y_L)$, the coefficient of $2^{\frac{n}{2}}$.

We are already computing $x_L y_L$ and $x_R y_R$

Considering the binomial product

$$(x_L + x_R)(y_L + y_R) = x_L y_L + x_L y_R + x_R y_L + y_R x_R$$

we get that

$$x_L y_R + x_R y_L = (x_L + x_R)(y_L + y_R) - x_L y_L - x_R y_R$$

Gauss's Method

Consider a different way of computing $(x_L y_R + x_R y_L)$, the coefficient of $2^{\frac{n}{2}}$.

We are already computing $x_L y_L$ and $x_R y_R$

Considering the binomial product

$$(x_L + x_R)(y_L + y_R) = x_L y_L + x_L y_R + x_R y_L + y_R x_R$$

we get that

$$x_L y_R + x_R y_L = (x_L + x_R)(y_L + y_R) - x_L y_L - x_R y_R$$

This might be better because we already compute $x_L y_L$ and $x_R y_R$

So the recursive algorithm is:

- ▶ first compute x_L, x_R, y_L, y_R and $x_L + x_R, y_L + y_R$ in linear time

So the recursive algorithm is:

- ▶ first compute x_L, x_R, y_L, y_R and $x_L + x_R, y_L + y_R$ in linear time
- ▶ then calculate $x_L y_L, x_R y_R$, and $(x_L + x_R)(y_L + y_R)$ recursively

So the recursive algorithm is:

- ▶ first compute x_L, x_R, y_L, y_R and $x_L + x_R, y_L + y_R$ in linear time
- ▶ then calculate $x_L y_L, x_R y_R$, and $(x_L + x_R)(y_L + y_R)$ recursively
- ▶ and assemble the results in linear time

So the recursive algorithm is:

- ▶ first compute x_L, x_R, y_L, y_R and $x_L + x_R, y_L + y_R$ in linear time
- ▶ then calculate $x_L y_L, x_R y_R$, and $(x_L + x_R)(y_L + y_R)$ recursively
- ▶ and assemble the results in linear time

Using this approach, we make *three* recursive calls, each of size $\frac{n}{2}$, yielding the time recurrence

$$T(n) = 3T\left(\frac{n}{2}\right) + cn$$

So the recursive algorithm is:

- ▶ first compute x_L, x_R, y_L, y_R and $x_L + x_R, y_L + y_R$ in linear time
- ▶ then calculate $x_L y_L, x_R y_R$, and $(x_L + x_R)(y_L + y_R)$ recursively
- ▶ and assemble the results in linear time

Using this approach, we make *three* recursive calls, each of size $\frac{n}{2}$, yielding the time recurrence

$$T(n) = 3T\left(\frac{n}{2}\right) + cn$$

Except that's not quite right. What we actually have is

$$T(n) = 2T\left(\frac{n}{2}\right) + T\left(\frac{n}{2} + 1\right) + O(n)$$

Solving the recurrence (board)

$$T(n) = 2T\left(\frac{n}{2}\right) + T\left(\frac{n}{2} + 1\right) + O(n)$$

- Does the +1 make any difference? Probably not, but how to be sure?

