CODEFORCES
Sponsored by Telegram

AmPieSamPie | Logout

HOME TOP CATALOG CONTESTS GYM PROBLEMSET GROUPS RATING EDU API CALENDAR HELP

PROBLEMS SUBMIT CODE MY SUBMISSIONS STATUS STANDINGS CUSTOM INVOCATION

E. Reverse Sorting

time limit per test: 2 seconds
memory limit per test: 256 megabytes

Forbidden Keywords for the Quiz: sort, open, file, creat(, fstream, thread, process, system(, exec(

You are given an array A of $\mathbf{N}$ integers. Your task is to sort the array in non-decreasing order using only a specific type of operation:

- In one operation, you may select any subarray of length exactly 3 and reverse it. In other words, you choose some $1 \leq i, j \leq N$ such that $j - i + 1 = 3$ and reverse `A[i...j]`.

You can apply this operation as many times as you like (or not at all). Your goal is to determine whether it is possible to sort the array using only this operation. If it is possible, you have to print the operations too. Look at the output format for a better understanding.

Input

The first line contains an integer N $(1 \leq N \leq 1000)$. The second line contains N integers A_i $(1 \leq S_i \leq 10^5)$.

Output

If it is not possible to make the array non-decreasing, print **NO**. Otherwise print **YES**. If your answer is **YES**, you have to output the number of moves you needed, let it be M. Then the next M lines will contain pairs of (i, j) representing a valid operation. Make sure your moves are valid, and those moves make the array A non-decreasing.

NOTE: If you don't understand the output format properly, look at the sample input-output and explanation.

Examples

input Copy

```
4
2 3 1 1
```

output Copy

```
YES
2
1 3
2 4
```

input Copy

```
6
2 5 5 1 5 5
```

output Copy

```
NO
```

input Copy

```
1
2
```

output Copy

CSE221 Assignment 01 Fall 2026
Contest is running
9 days
Virtual Participation

→ Submit?

Language: Java 21 64bit
Choose file: Choose File No file chosen
Submit

→ Last submissions

Submission	Time	Verdict
395725016	Oct/23/2026 18:44	Wrong answer on test 14
395724336	Oct/23/2026 18:39	Wrong answer on test 2
395724040	Oct/23/2026 18:37	Wrong answer on test 1

```
YES
0
```

input Copy

```
2
6 6
```

output Copy

```
YES
0
```

Note

For the Sample Input, one way to sort the array $[2, 3, 1, 1]$ using only the allowed operation:

1. Choose indices $(1, 3)$ and reverse the subarray $[2, 3, 1]$ which becomes $[1, 3, 2]$. So the resulting array: $[1, 3, 2, 1]$
2. Choose indices $(2, 4)$ and reverse subarray $[3, 2, 1]$ which becomes $[1, 2, 3]$. So the resulting array: $[1, 1, 2, 3]$

Codeforces (c) Copyright 2010-2026 Mike Mirzayanov
The only programming contests Web 2.0 platform
Server time: Oct/23/2026 22:33:19^{UTC+6} (f1).
Desktop version, switch to mobile version.
Privacy Policy | Terms and Conditions

Supported by

