

Dissertation  
Towards a Framework for DHT Distributed  
Computing

Andrew Rosen

Georgia State University

May 13th, 2016

# Table of Contents

- 1 Introduction
  - Objective
  - Distributed Computing and Challenges
  - What Are Distributed Hash Tables?
  - Why DHTs and Distributed Computing
- 2 Background
  - The Components and Terminology
  - Example DHT: Chord
- 3 Previous Work
  - VHash
  - ChordReduce
- 4 UrDHT
  - Introduction
- 5 Autonomous Load-Balancing
  - Introduction
  - Distribution of Keys in A DHT
  - Experimental Setup
  - Churn
  - Random Injection
  - Neighbor Injection
  - Invitation
  - Conclusion
- 6 Conclusion
  - Conclusion

# Objective

Our objective is to create a generalized framework for distributed computing using Distributed Hash Tables.

# Objective

Our objective is to create a generalized framework for distributed computing using Distributed Hash Tables.

Or

# Objective

Our objective is to create a generalized framework for distributed computing using Distributed Hash Tables.

Or

We want to build a completely decentralized distributed computing framework.

# What do I Mean by Distributed Computing?

A system where we can take a task and break it down into multiple parts, where each part is worked upon individually.

# Challenges of Distributed Computing

Distributed Computing platforms experience these challenges:

**Scalability** As the network grows, more resources are spent on maintaining and organizing the network.





# Challenges of Distributed Computing

Distributed Computing platforms experience these challenges:

**Scalability** As the network grows, more resources are spent on maintaining and organizing the network.

**Fault-Tolerance** As more machines join the network, there is an increased risk of failure.

**Load-Balancing** Tasks need to be evenly distributed among all the workers.

# Distributed Key/Value Stores

**Distributed Hash Tables** are mechanisms for storing values associated with certain keys.

- Values, such as filenames, data, or IP/port combinations are associated with keys.
- These keys are generated by taking the hash of the value.
- We can get the value for a certain key by asking any node in the network.

## How Does It Work?

# Current Applications

Applications that use or incorporate DHTs:

- P2P File Sharing applications, such as BitTorrent.
- Distributed File Storage.
- Distributed Machine Learning.
- Name resolution in a large distributed database.

# Strengths of DHTs

DHTs are designed for large P2P applications, which means they need to be (and are):

- Scalable
- Fault-Tolerant
- Load-Balancing

# DHTs Address the Specified Challenges

The big issues in distributed computing can be solved by the mechanisms provided by Distributed Hash Tables.

# Uses For DHT Distributed Computing

The generic framework we are proposing would be ideal for:

- Embarrassingly Parallel Computations
  - Any problem that can be framed using Map and Reduce.
  - Brute force cryptography.
  - Genetic algorithms.
  - Markov chain Monte Carlo methods.
- Use in either a P2P context or a more traditional deployment.

# Table of Contents

- Objective
- Distributed Computing and Challenges
- What Are Distributed Hash Tables?
- Why DHTs and Distributed Computing

## 2 Background

- The Components and Terminology
- Example DHT: Chord

- VHash
- ChordReduce

- Introduction

- Introduction
- Distribution of Keys in A DHT
- Experimental Setup
- Churn
- Random Injection
- Neighbor Injection
- Invitation
- Conclusion

- ## ● Conclusion




## Required Attributes of DHT

- A distance and midpoint function.
- A closeness or ownership definition.
- A Peer management strategy.


## Chord's Closest Metric.

**Figure:** A Voronoi diagram for a Chord network, using Chord's definition of closest.



# Chord Using A Different Closest Metric

**Figure:** A Voronoi diagram for a Chord network, where closest is defined by the node being the closest in either direction.



- Network size is  $n$  nodes.
- Keys and IDs are  $m$  bit hashes, usually SHA1.
- Peerlists are made up of:
  - **Short Peers** The neighboring nodes that define the network's topology.
  - **Long Peers** Routing shortcuts.

# Functions

- `lookup(key)` Finds the node responsible for a given key.

`put(key, value)` Stores *value* at the node responsible for *key*,  
where  $key = hash(value)$ .


`get(key)` Returns the *value* associated with *key*.

# Chord

- Ring Topology
- Short Peers: predecessor and successor in the ring.
- Responsible for keys between their predecessor and themselves.
- Long Peers:  $\log n$  nodes, where the node at index  $i$  in the peerlist is

$$\text{root}(r + 2^{i-1} \bmod m), 1 < i < m$$

# A Chord Network



**Figure:** An 8-node Chord ring where  $m = 8$ . Node 24's long peers are shown.

# Fault Tolerance in Chord

- Local maintenance thread gradually fixes the network topology.
  - Each node “notifies” its successor.
  - The successor replies with a better successor if one exists.
- The long peers are gradually updated by performing a lookup on each entry.



100

- [illegible]

# Table of Contents

- 1 Introduction
  - Objective
  - Distributed Computing and Challenges
  - What Are Distributed Hash Tables?
  - Why DHTs and Distributed Computing
- 2 Background
  - The Components and Terminology
  - Example DHT: Chord
- 3 Previous Work
  - VHash
  - ChordReduce
- 4 UrDHT
  - Introduction
- 5 Autonomous Load-Balancing
  - Introduction
  - Distribution of Keys in A DHT
  - Experimental Setup
  - Churn
  - Random Injection
  - Neighbor Injection
  - Invitation
  - Conclusion
- 6 Conclusion
  - Conclusion

# Overarching Goal

My research has been focused on:

- Abstracting out DHTs.
- Distributed computation using DHTs.

# Goals

## VHash sprung from two related ideas:

- We wanted a way be able optimize latency by embedding it into the routing overlay.

# Goals

VHash sprung from two related ideas:

- We wanted a way be able optimize latency by embedding it into the routing overlay.
- We wanted to create a DHT based off of Voronoi tessellations. Unfortunately:

# Goals

VHash sprung from two related ideas:

- We wanted a way be able optimize latency by embedding it into the routing overlay.
- We wanted to create a DHT based off of Voronoi tessellations. Unfortunately:
  - Distributed algorithms for this problem don't really exist.


# Goals

VHash sprung from two related ideas:

- We wanted a way be able optimize latency by embedding it into the routing overlay.
- We wanted to create a DHT based off of Voronoi tessellations. Unfortunately:
  - Distributed algorithms for this problem don't really exist.
  - Existing approximation algorithms were unsuitable.


# Voronoi Tessellation

(4.19, 12.85)





100



# DHT and Voronoi Relationship

- We can view DHTs in terms of Voronoi tessellation and Delaunay triangulation.
  - The set of keys the node is responsible for is its Voronoi region.
  - The nodes neighbors are its Delaunay neighbors.

# VHash

- Voronoi-based Distributed Hash Table based on this relationship.
- Uses our approximation to solve for Delaunay neighbors, called DGVH.
- Topology updates occur via gossip-based protocol.
- Routing speed is  $O(\sqrt[d]{n})$
- Memory Cost
  - Worst case:  $O(n)$
  - Expected maximum size:  $\Theta(\frac{\log n}{\log \log n})$

9

- Assumption: The majority of Delaunay links cross the corresponding Voronoi edges.
- We can test if the midpoint between two potentially connecting nodes is on the edge of the Voronoi region.
- This intuition fails if the midpoint between two nodes does not fall on their Voronoi edge.

# DGVH Heuristic


- 1: Given node  $n$  and its list of *candidates*.
- 2:  $peers \leftarrow$  empty set that will contain  $n$ 's one-hop peers
- 3: Sort *candidates* in ascending order by each node's distance to  $n$
- 4: Remove the first member of *candidates* and add it to *peers*
- 5: **for all**  $c$  in *candidates* **do**
- 6:      $m$  is the midpoint between  $n$  and  $c$
- 7:     **if** Any node in *peers* is closer to  $m$  than  $n$  **then**
- 8:         Reject  $c$  as a peer
- 9:     **else**
- 10:         Remove  $c$  from *candidates*
- 11:         Add  $c$  to *peers*
- 12:     **end if**
- 13: **end for**

100

5.  $\frac{1}{2} \times \frac{1}{2} = \frac{1}{4}$


\_\_\_\_\_

# Results



**Figure:** As the size of the graph increases, we see approximately 1 error per node.

# Results



**Figure:** These figures show, starting from a randomized network, VHash forms a stable and consistent network topology.



# Results





Figure: Comparing the routing effectiveness of Chord and VHash.


# Conclusions

- DGVH is simple approximation for Delaunay Triangulation that guarantees a fully connected graph.
- VHash can optimize over a metric such as latency and achieve superior routing speeds as a result.


- 
- Georgia State  
University

# System Architecture





**Figure:** The stager sends a map task for each key in the keyfile. In larger networks, this process is streamlined by recursively bundling keys and sending them to the best finger.



**Figure:** Results are sent back via the overlay. If a node receives multiple results, they are reduced before being sent on.

Churn rate per second	Average runtime (s)	Speedup vs 0% churn
0.8%	191.25	2.15
0.4%	329.20	1.25
0.025%	431.86	0.95
0.00775%	445.47	0.92
0.00250%	331.80	1.24
0%	441.57	1.00

**Table:** The results of calculating  $\pi$  by generating  $10^8$  samples under churn. Churn is the chance for each node to join or leave the network. The large speedup is from joining nodes acquiring work during experimental runtime.

# Conclusions

Our experiments established:

- ChordReduce can operate under high rates of churn.
- Execution follows the desired speedup.
- Speedup occurs on sufficiently large problem sizes.

This makes ChordReduce an excellent platform for distributed and concurrent programming in cloud and loosely coupled environments.



# Table of Contents

- Objective
- Distributed Computing and Challenges
- What Are Distributed Hash Tables?
- Why DHTs and Distributed Computing

- The Components and Terminology
- Example DHT: Chord

- VHash
- ChordReduce

#### 4 UrDHT

- Introduction

- Introduction
- Distribution of Keys in A DHT
- Experimental Setup
- Churn
- Random Injection
- Neighbor Injection
- Invitation
- Conclusion

- ## ● Conclusion



# Table of Contents

- Objective
- Distributed Computing and Challenges
- What Are Distributed Hash Tables?
- Why DHTs and Distributed Computing

- The Components and Terminology
- Example DHT: Chord

- VHash
- ChordReduce

- Introduction

## 5 Autonomous Load-Balancing

- Introduction
- Distribution of Keys in A DHT
- Experimental Setup
- Churn
- Random Injection
- Neighbor Injection
- Invitation
- Conclusion

- ## ● Conclusion




# Distribution in Networks of Different Sizes

**Table:** The median distribution of tasks (or files) among nodes. We can see the standard deviation is fairly close to the expected mean workload ( $\frac{\text{tasks}}{\text{nodes}}$ ). Each row is the average of 100 trials. Experiments show there is practically little deviation in the median load of the network.

Nodes	Tasks	Median Workload	$\sigma$
1000	100000	69.410	137.27
1000	500000	346.570	499.169
1000	1000000	692.300	996.982
5000	100000	13.810	20.477
5000	500000	69.280	100.344
5000	1000000	138.360	200.564
10000	100000	7.000	10.492
10000	500000	34.550	50.366
10000	1000000	69.180	100.319

# Distribution of Work in A DHT



**Figure:** The probability distribution of workload in a DHT with 1000 nodes and 1,000,000 tasks or files. The vertical dashed line designates the median.



# Terms and Assumptions

- Time is measured in ticks.
- A tick is enough time to perform aggressive, reactive maintenance<sup>1</sup>
- Jobs are measured in tasks; each task can correspond to a file or a piece of a file

---

<sup>1</sup>This has been implemented and tested.





## Output

- Ideal Runtime
- Runtime
- Runtime Factor
- Task Distribution

# Strategy


- The network load-balances using churn
- `churnRate` chance per tick for each node to leave network
- Pool of potentially joining joins at the same rate

# Runtime

**Table:** Runtime factor of networks of varying sizes and number of tasks, each using the Churn strategy to load-balance. Each result is the average of 100 trials. The networks are homogeneous and each node consumes one task per tick. A runtime of 1 is the ideal and target.


Churn Rate	$10^3$ nodes, $10^5$ tasks	$10^3$ nodes, $10^6$ tasks	100 nodes, $10^4$ tasks	100 nodes, $10^5$ tasks	100 nodes, $10^6$ tasks
0	7.476	7.467	5.043	5.022	5.016
0.0001	7.122	5.732	4.934	4.362	3.077
0.001	6.047	3.674	4.391	3.019	1.863
0.01	3.721	2.104	3.076	1.873	1.309

# Churn vs Runtime factor




**Figure:** This graph shows the effect churn has on runtime in a distributed computation. Runtime is measured as how many times slower the computation runs than an ideal computation, where each node receives an equal number of tasks. The lower the runtime factor, the closer it is

# Churn vs Average Work Per Tick




**Figure:** With more and more churn in the network, new nodes have a higher chance of joining the network and acquiring work from overloaded nodes. This results in more average work being done each tick, as there are less nodes simply idling.



**Figure:** The initial distribution of the workload in both networks. As both networks start with same initial configuration, the distribution is currently identical. This greatly resembles the distribution we saw in Figure 9.


# Churn Distribution after 5 Ticks



**Figure:** This is the distribution of the workloads at the beginning of tick 5. We can see the network using 0.01 churn has fewer nodes with less work and more nodes with a greater workload.



# Churn Distribution after 35 Ticks



**Figure:** After 35 ticks, the effects of churn on the workload distribution become more pronounced. More nodes have consumed all their tasks and are simply idling, but significantly less in the network using churn.

- Diminishing returns
- Maintenance costs can get excessive
- We don't actually have to kill nodes, most of the speedup is from joining.


# Strategy

- Nodes with loads  $\leq \text{sybilThreshold}$  create Sybils
- This check occurs every 5 ticks before work is performed
- These Sybils are randomly placed
- Act as a virtual node so the same node essentially exists in multiple locations
- Sybils are removed if the node that created it has no work

# Effects of Network Size


- A homogeneous, 1000 node/100,000 task network, never have an average runtime factor greater than 1.7
- Minimum was 1.36.
- In the same network with 1,000,000 tasks, these runtimes were 1.25 and 1.12 respectively.
- On average, the 1,000,000 task network had a runtime factor 0.82 less than the 100,000 task network.

# Random injection vs no strategy after 5 ticks



**Figure:** The networks after 5 ticks. The network using random injection has significantly less underutilized nodes, even after only 5 ticks.

# Random Injection vs No Strategy After 35 ticks



**Figure:** The networks after 35 ticks. The network using random injection has significantly less underutilized nodes and substantially more nodes with some or lots of work.

# Random Injection in a Heterogeneous Network





Figure: The workload distribution of heterogenous networks after 35 ticks.

# Random Injection VS Churn



**Figure:** The networks after 35 ticks. The network using random injection load-balances significantly better than the network using Churn.



# Impacts of Variables

- `sybilThreshold` would lower the runtime factor.
- Churn had no significant effect
- Maxsybils (node strength) had no effect in homogeneous networks


# Remarks

- Best runtime factor
- Could still incur high maintenance costs, especially with nodes being deleted as soon as they are made

# Strategy


- Rather than creating Sybils randomly, nodes create one in their successors
- Finding node id uses mashes
- Estimates which successor has most work.
- Tested estimation against smart method.

# Neighbor Injection after 5 Ticks




**Figure:** While the network no strategy appears to have less nodes idling, the active nodes in the network using neighbors are being better utilized.

# Neighbor Injection after 35 Ticks




**Figure:** Despite have more idling nodes, we see that the nodes using the neighbor injection strategy have acquired smaller workloads and have effectively shifted part of the histogram left.

# Smart Neighbor Injection after 5 Ticks



**Figure:** The workload in the networks after 5 ticks. We can see that the network using neighbor injection has directed more nodes that would be idling to perform work. This is especially apparent in comparison to Figure 20.

# Smart Neighbor Injection after 35 Ticks



**Figure:** After 35 ticks, we see the network using the smart neighbor injection strategy has significantly less nodes with little or no work, more nodes with smaller amounts of work, and less nodes with large amounts of tasks.

# Impacts of Variables






# Remarks






# Invitation at 5 Ticks




**Figure:** Here, we see that the invitation strategy performs markedly better at distributing the work than no strategy. At tick 5, there are many more nodes with small work loads. There are also few nodes with large amounts of work.

# Invitation at 35 Ticks




**Figure:** At 35 ticks, we can see the network using the invitation strategy perform markedly better than the network using no strategy. The highest load is around 500 tasks in the network using invitation, compared to approximately 650 tasks in the network using no strategy.

\_\_\_\_\_



**Figure:** A comparison of a network using the smart neighbors strategy and a network using the invitation strategy. Invitation has slightly more nodes on the performing less work, but no significant differences have emerged.

# Invitation vs Smart Neighbors at Tick 35



**Figure:** After 35 ticks, differences between the two strategies have emerged. The network using the invitation strategy has significantly less nodes with a small work load and many more with large work loads.

# Remarks







# Table of Contents

- 1 Introduction
  - Objective
  - Distributed Computing and Challenges
  - What Are Distributed Hash Tables?
  - Why DHTs and Distributed Computing
- 2 Background
  - The Components and Terminology
  - Example DHT: Chord
- 3 Previous Work
  - VHash
  - ChordReduce
- 4 UrDHT
  - Introduction
- 5 Autonomous Load-Balancing
  - Introduction
  - Distribution of Keys in A DHT
  - Experimental Setup
  - Churn
  - Random Injection
  - Neighbor Injection
  - Invitation
  - Conclusion
- 6 Conclusion
  - Conclusion

- 
- Georgia State University