

Proposal Defense

Towards a Framework for DHT Distributed Computing

Andrew Rosen

Georgia State University

July 15th, 2015

Table of Contents

1 Introduction

- What I am doing
- Distributed Computing and Challenges
- What Are Distributed Hash Tables?
- Why DHTs and Distributed Computing

2 Background

- The Components and Terminology
- Example DHTs

3 Previous Work

- ChordReduce
- VHash
- Sybil

4 Proposed Work

- UrDHT
- DHT Distributed Computing

Objective

Our objective is to create a generalized framework for distributed computing using Distributed Hash Tables.

Objective

Our objective is to create a generalized framework for distributed computing using Distributed Hash Tables.

Or

Objective

Our objective is to create a generalized framework for distributed computing using Distributed Hash Tables.

Or

We want to build a completely decentralized distributed computing framework.

What do I Mean by Distributed Computing?

A system where we can take a task and break it down into multiple parts, where each part is worked upon individually.

Challenges of Distributed Computing

Distributed Computing platforms should be:

Scalable The larger the network, the more resources need to be spent on maintaining and organizing the network.

DHT Distributed Computing

└ Introduction

└ Distributed Computing and Challenges

└ Challenges of Distributed Computing

Challenges of Distributed Computing

Distributed Computing platforms should be:

Scalable The larger the network, the more resources need to be spent on maintaining and organizing the network.

Remember, computers aren't telepathic. There's always an overhead cost. It will grow. The challenge of scalability is designing a protocol that grows this organizational cost at an extremely slow rate. For example, a single node keeping track of all members of the system might be a tenable situation up to a certain point, but eventually, the cost becomes too high for a single node.

Challenges of Distributed Computing

Distributed Computing platforms should be:

Scalable The larger the network, the more resources need to be spent on maintaining and organizing the network.

Fault-Tolerant As we add more machines, we need to be able to handle the increased risk of hardware failure.

DHT Distributed Computing

└ Introduction

└ Distributed Computing and Challenges

└ Challenges of Distributed Computing

Challenges of Distributed Computing

Distributed Computing platforms should be:

Scalable The larger the network, the more resources need to be spent on maintaining and organizing the network.

Fault-Tolerant As we add more machines, we need to be able to handle the increased risk of hardware failure.

Hardware failure is a thing that can happen. Individually the chances are low, but this becomes high when we're talking about millions of machines. Also, what happens in a P2P environment.

Challenges of Distributed Computing

Distributed Computing platforms should be:

Scalable The larger the network, the more resources need to be spent on maintaining and organizing the network.

Fault-Tolerant As we add more machines, we need to be able to handle the increased risk of hardware failure.

Load-Balancing Tasks need to be evenly distributed among all the workers.

DHT Distributed Computing

└ Introduction

└ Distributed Computing and Challenges

└ Challenges of Distributed Computing

Challenges of Distributed Computing

Distributed Computing platforms should be:

Scalable The larger the network, the more resources need to be spent on maintaining and organizing the network.

Fault-Tolerant As we add more machines, we need to be able to handle the increased risk of hardware failure.

Load-Balancing Tasks need to be evenly distributed among all the workers.

If we are splitting the task into multiple parts, we need some mechanism to ensure that each worker gets an even (or close enough) amount of work.

Distributed Key/Value Stores

Distributed Hash Tables are mechanisms for storing values associated with certain keys.

- Values, such as filenames, data, or IP/port combinations are associated with keys.
- These keys are generated by taking the hash of the value.
- We can get the value for a certain key by asking any node in the network.

Current Applications

Applications that use or incorporate DHTs:

- P2P File Sharing applications, such as Bittorrent [1] [4].
- Distributed File Storage [2].
- Distributed Machine Learning [3].
- Name resolution in a large distributed database [5].

How Does It Work?

We'll explain in greater detail later, but briefly:

- DHTs organize a set of nodes, each identified by an **ID** (their key).
- Nodes are responsible for the keys that are closest to their IDs.
- Nodes maintain a list of other peers in the network.
 - Typically a size $\log(n)$ subset of all nodes in the network.
- Each node uses a very simple routing algorithm to find a node responsible for any given key.

DHT Distributed Computing

└ Introduction

└ What Are Distributed Hash Tables?

└ How Does It Work?

How Does It Work?

We'll explain in greater detail later, but briefly:

- DHTs organize a set of nodes, each identified by an ID (their key).
- Nodes are responsible for the keys that are closest to their IDs.
- Nodes maintain a list of other peers in the network.
 - Typically a size $\log(n)$ subset of all nodes in the network.
- Each node uses a very simple routing algorithm to find a node responsible for any given key.

We use ID for nodes and keys for data so we always know our context.

Strengths of DHTs

DHTs are designed for large P2P applications, which means they need to be (and are):

Scalable

Fault-Tolerant

Load-Balancing

DHT Distributed Computing

└ Introduction

└ What Are Distributed Hash Tables?

└ Strengths of DHTs

Strengths of DHTs

DHTs are designed for large P2P applications, which means they need to be (and are):

Scalable
Fault-Tolerant
Load-Balancing

- Remember to mention Napster.
- Distributed Hash Tables were designed to be used for completely decentralized P2P applications involving millions of nodes.
- As a result of the P2P focus, DHTs have the following qualities

DHTs Address the Specified Challenges

Uses For DHT Distributed Computing

- Embarrassingly Parallel Computations
 - Brute force cryptography.
 - Genetic algorithms.
 - Markov chain Monte Carlo methods.
 - Any problem that can be framed using Map and Reduce.
- Can be used in either a P2P context or a more traditional deployment.

Table of Contents

- 1 Introduction
 - What I am doing
 - Distributed Computing and Challenges
 - What Are Distributed Hash Tables?
 - Why DHTs and Distributed Computing
- 2 Background
 - The Components and Terminology
 - Example DHTs
- 3 Previous Work
 - ChordReduce
 - VHash
 - Sybil
- 4 Proposed Work
 - UrDHT
 - DHT Distributed Computing

Functions

`put(key, value)` Stores *value* at the node responsible for *key*, where
 $key = hash(value)$.

`get(key)` Returns the *value* associated with *key*.

`lookup(key)` Finds the node responsible for a given key.

DHT Distributed Computing

└─ Background

└─ The Components and Terminology

└─ Functions

Functions

`put(key, value)` Stores value at the node responsible for `key`, where
 $key = \text{hash}(\text{value})$.

`get(key)` Returns the value associated with `key`.

`lookup(key)` Finds the node responsible for a given key.

- There is usually a delete function as well, but it's not important.

Chord

content...

Kademlia

VHash

Maybe, if room

Table of Contents

- 1 Introduction
 - What I am doing
 - Distributed Computing and Challenges
 - What Are Distributed Hash Tables?
 - Why DHTs and Distributed Computing
- 2 Background
 - The Components and Terminology
 - Example DHTs
- 3 Previous Work
 - ChordReduce
 - VHash
 - Sybil
- 4 Proposed Work
 - UrDHT
 - DHT Distributed Computing

ChordReduce

content

Sybil Analysis

content

Table of Contents

1 Introduction

- What I am doing
- Distributed Computing and Challenges
- What Are Distributed Hash Tables?
- Why DHTs and Distributed Computing

2 Background

- The Components and Terminology
- Example DHTs

3 Previous Work

- ChordReduce
- VHash
- Sybil

4 Proposed Work

- UrDHT
- DHT Distributed Computing

This kind of framework does not exist.

DHT Distributed Computing

content

Autonomous Load-Balancing

content



Bram Cohen.

Incentives build robustness in bittorrent.

In *Workshop on Economics of Peer-to-Peer systems*, volume 6, pages 68–72, 2003.



Frank Dabek, M Frans Kaashoek, David Karger, Robert Morris, and Ion Stoica.

Wide-Area Cooperative Storage with CFS.

ACM SIGOPS Operating Systems Review, 35(5):202–215, 2001.



Mu Li, Li Zhou, Zichao Yang, Aaron Li, Fei Xia, David G Andersen, and Alexander Smola.

Parameter server for distributed machine learning.



Andrew Loewenstern and Arvid Norberg.

BEP 5: DHT Protocol.

http://www.bittorrent.org/beps/bep_0005.html, March 2013.



Gabriel Mateescu, Wolfgang Gentzsch, and Calvin J. Ribbens.

Hybrid computing—where {HPC} meets grid and cloud computing.

Future Generation Computer Systems, 27(5):440 – 453, 2011.