- 1. Do) CLEAR your workspace.
- 2. Give your workspace a) WSID.
- 3. Do) SAVE your workspace.
- 4. Turn Dyalog) OF F.
- 5. Start Dyalog and) LOAD your workspace.

Define a function NoSpace to remove spaces:

NoSpace 'here is some text' hereissometext

Define a function RemoveFrom to remove any character:

```
'l' RemoveFrom 'hello world'
heo word
```

```
'o' RemoveFrom 'hello world'
hell wrld
```

Task 4 Redefine the function NoSpace using RemoveFrom:



Save your workspace.

Define a function Mean to return the mean average of its argument:

```
Mean 3 1 4 1 5 9 2 6
3.875
       Mean 4 1 2 5
3
       Mean 6+110
11.5
When you're done, ) fns should show something like this:
       )fns
```

Mean

Task 7

Define a function ID to return an ω by ω identity matrix:

```
ID 3
1 0 0
0 1 0
0 0 1
      ID 5
1 0 0 0 0
0 1 0 0 0
0 0 1 0 0
0 0 0 1 0
0 0 0 0
```

Define a function TimesRows to multiply a matrix left argument and a vector right argument. For example:

mat TimesRows vec

- 6 0 -9
- 10 0 -1
 - 3 0 -3
 - 6 0 -3

Using the Residue function (|), define a function Multiples to return only elements of the vector ω that are exact multiples of α .

```
7 Multiples 6 12 14 8 21 42 56 97 13
14 21 42 56
```

```
3 Multiples 6 9 9 10 9 1 3 5 3 6 7 3 6 9 9 9 3 3 6 3
```

10 Multiples 7 9 13 A empty vector result

Define a function Remove Every to remove every ω^{th} number from the vector α :

```
(110) RemoveEvery 4

1 2 3 5 6 7 9 10
(115) RemoveEvery 3

1 2 4 5 7 8 10 11 13 14
6 2 9 4 1 2 6 RemoveEvery 2

6 9 1 6
```

Define a function Extend which catenates the integer α and the next ω integers.

Using the Extend function you wrote, define a function To which produces integers from α to ω inclusive.

Task 13

Define these variables that we'll use in the next few tasks: names ← 6 7p'Rich Pav HardeepAdam Sally Rodrigo' names Rich Pav Hardeep Adam Sally Rodrigo items←7 5ρ'applecat dog lemurfrog safe lemon' items apple cat dog lemur frog safe lemon

Define a function That Have to select rows of a text matrix α which contain the character ω :

```
names ThatHave 'R'
Rich
Rodrigo
      names ThatHave 'a'
Pav
Hardeep
Adam
Sally
      names ThatHave 'x' A zero-row matrix result!
```

Define a function ThatBeginWith to select rows of a text matrix α which **begin with** the character ω :

```
names ThatBeginWith 'R'
Rich
Rodrigo
names ThatBeginWith 'A'
Adam
names ThatBeginWith 'X' A zero-row result!
```

Define a function TextLengths that takes a matrix ω and counts how many non-spaces there are in each row.

```
TextLengths names 4 3 7 4 5 7
```

```
TextLengths items 5 3 3 5 4 4 5
```

```
TextLength 0 5p'' A no rows; no lengths!
```

Using TextLengths, define a function Of Length to select rows of a text matrix α where text (non-spaces) are of length ω :

```
names OfLength 4
Rich
Adam
      names OfLength 7
Hardeep
Rodrigo
      items OfLength 5
apple
lemur
lemon
```

Define a function RollN that simulates rolling six-sided dice. ω is the number of dice to roll. Then return the total:

```
RollN 3
                       A your result may vary!
11
      RollN 3
                       A your result may vary!
10
      RollN 1000
                       A your result may vary!
3548
      |0.5+0.00001\times+/RollN 1000000
35
```

Save your workspace

Email your_name.dws to workshops@dyalog.com

Make sure to put your name in the email so we know it is from you!