

# **CS331: Homework #7**

Due on April 1, 2013 at 11:59pm

*Professor Zhang 9:00am*

**Josh Davis**

## Problem 1

Let  $K = \{\langle M \rangle : \langle M \rangle \notin L(M)\}$ . Prove that  $K$  is not Turing recognizable.

*Proof.* To prove that  $K$  is not Turing recognizable, we will prove this by coming up with a contradiction.

Assume that  $K$  is Turing recognizable and  $N$  is a Turing machine that recognizes it.  $K$  is the set of all encoded Turing machines that recognize the language that doesn't include their own encoding.

Using this assumption, we can see that if we take the TM that recognizes  $K$ ,  $N$ , we can see there are two cases in which this property of  $K$  still holds.

### Case One

If  $N \in K$  then  $N \notin K$ . This is because if it contains itself, then it must be removed because  $K$  cannot contain the encoding of itself.

### Case Two

If  $N \notin K$  then  $N \in K$ . This is because the encoding of  $N$  must be represented in  $K$  because it is the set of all TM that don't recognize themselves.

Thus  $N \in K \iff N \notin K$ . This is clearly a contradiction and thus we have shown that  $K$  is not Turing recognizable.  $\square$

---

## Problem 2

Prove the following statements:

1.  $L_1 \leq_m L_2$  and  $L_2 \leq_m L_3$  imply  $L_1 \leq_m L_3$ .
2.  $L_1 \leq_T L_2$  implies that  $\overline{L_1} \leq_m \overline{L_2}$ .

### Part One

*Proof.* Let there be three TMs that decide the three languages.  $M_1$  recognizes  $L_1$ ,  $M_2$  recognizes  $L_2$ , and  $M_3$  recognizes  $L_3$ .

According to many-one reduction, if one language reduces to another language, that means there is a computable function such that the function reduces the first language to the second.

Therefore with  $L_1 \leq_m L_2$ , there is a computable function,  $f_{12}$  where for every  $w$ ,  $w \in L_1 \iff f_{12}(w) \in L_2$ .

The same can be said for  $L_2 \leq_m L_3$ , there is a computable function,  $f_{23}$  where for every  $w$ ,  $w \in L_2 \iff f_{23}(w) \in L_3$ .

Now to prove that  $L_1 \leq_m L_2$  and  $L_2 \leq_m L_3$  imply  $L_1 \leq_m L_3$ , we will construct a new TM,  $N$ , that recognizes  $L_1 \leq_m L_3$ . We will construct  $N$  using the following computable function,  $f(w) = f_{23}(f_{12}(w))$ :

$N =$  “ On input string  $w$ :

1. Run  $M_1$  on  $w$ , if it accepts, move on, else reject
2. Compute  $f(w)$  using our new computable function
3. Run  $M_3$  on the previously computed value, output whatever  $M_3$  outputs”

Thus we have shown that when  $L_1$  reduces to  $L_2$  and  $L_2$  reduces to  $L_3$ , we can construct a new many-reduction that reduces  $L_1$  to  $L_3$ . Thus we have proved what we sought to prove and our proof is complete.  $\square$

### Part Two

*Proof.* Since  $L_1$  is Turing reducible to  $L_2$ , that means  $L_1$  is decidable relative to  $L_2$  and there is an oracle TM,  $M^1$ , that can report whether or not any string  $w$  is a member of  $L_1$ . Likewise there is another oracle TM,  $M^2$ , that can report whether or not any string  $w$  is a member of  $L_2$ .

To show that this then implies that  $\overline{L_1} \leq_m \overline{L_2}$ , we can construct a new oracle TM using these existing oracle TMs. Let our new oracle TM be  $N$  and defined as follows:

$N =$  “ On input string  $w$ :

1. Query  $M^1$  with  $w$ , if it answers **no**, continue, else reject
2. Next query  $M^2$  with  $w$ , if it answers **no** accept, else reject”

This is valid because when we query the oracles, since we want the complement of the languages, we just answer the opposite of what the oracle tells us. Thus we can create a new oracle from the oracles for  $L_1$  and  $L_2$  that can show that  $L_1 \leq_T L_2$  implies that  $\overline{L_1} \leq_m \overline{L_2}$ .

Thus we have proven what we wanted to and our proof is complete.  $\square$

### Problem 3

Prove that  $A_{TM} \not\leq_m \overline{A_{TM}}$ , where  $A_{TM} = \{\langle M, w \rangle : M \text{ is a TM and } M \text{ accepts } w\}$

*Proof.* To prove this, we will do a proof by contradiction.

Suppose that  $A_{TM} \leq_m \overline{A_{TM}}$ , or  $A_{TM}$  reduces to  $\overline{A_{TM}}$ . This means that there is a computable function,  $f$  that on every input  $w$ ,  $w \in A_{TM} \iff f(w) \in \overline{A_{TM}}$ . Let  $M$  be the TM that recognizes  $A_{TM}$ .

According to the above, we can construct a new TM,  $N$  that recognizes  $\overline{A_{TM}}$ . Let  $N$  be constructed as follows:

$N =$  “ On input string  $w$ :

1. Compute  $f(w)$
2. Run  $M$  with  $w$ , if  $M$  rejects, then accepts and if  $M$  accepts, then reject”

As we can see, the only way to that  $A_{TM}$  reduces to  $\overline{A_{TM}}$  is if  $A_{TM}$  is decidable. Since we know that  $A_{TM}$  is not decidable, we have a contradiction.

Since we have a contradiction  $A_{TM} \leq_m \overline{A_{TM}}$  cannot be true and we have concluded our proof.  $\square$

### Problem 4

Which of the following PCP problems has a solution? Justify.

1.  $\left\{ \begin{bmatrix} ab \\ a \end{bmatrix}, \begin{bmatrix} bb \\ ab \end{bmatrix}, \begin{bmatrix} aa \\ ba \end{bmatrix}, \begin{bmatrix} cc \\ bc \end{bmatrix}, \begin{bmatrix} aa \\ ca \end{bmatrix}, \begin{bmatrix} d \\ cd \end{bmatrix} \right\}$
2.  $\left\{ \begin{bmatrix} ab \\ a \end{bmatrix}, \begin{bmatrix} bb \\ ab \end{bmatrix}, \begin{bmatrix} aa \\ ba \end{bmatrix}, \begin{bmatrix} c \\ bc \end{bmatrix}, \begin{bmatrix} aa \\ ca \end{bmatrix}, \begin{bmatrix} d \\ cd \end{bmatrix} \right\}$

#### Part One

One possible solution is below:

$$\begin{bmatrix} ab \\ a \end{bmatrix} \begin{bmatrix} cc \\ bc \end{bmatrix} \begin{bmatrix} d \\ cd \end{bmatrix}$$

This is a solution because if we read across the top, we get  $abccd$  and if we read across the bottom we get  $abccd$ . Thus we have solved this given PCB problem.

#### Part Two

One possible solution is below:

$$\begin{bmatrix} ab \\ a \end{bmatrix} \begin{bmatrix} aa \\ ba \end{bmatrix} \begin{bmatrix} bb \\ ab \end{bmatrix} \begin{bmatrix} c \\ bc \end{bmatrix}$$

This is a solution because if we read across the top, we get  $abaabbc$  and if we read across the bottom we get  $abaabbc$ . Thus we have solved this given PCB problem.

---

## Problem 5

Does the following PCP problem P have a solution?

$$\left\{ \begin{bmatrix} a \\ ab \end{bmatrix}, \begin{bmatrix} b \\ ccc \end{bmatrix}, \begin{bmatrix} c \\ b \end{bmatrix}, \begin{bmatrix} c \\ d \end{bmatrix}, \begin{bmatrix} dddd \\ \phantom{d} \end{bmatrix}, \begin{bmatrix} ddde \\ e \end{bmatrix} \right\}$$

Yes, it has a solution. One possible solution is below:

$$\begin{bmatrix} a \\ ab \end{bmatrix} \begin{bmatrix} b \\ ccc \end{bmatrix} \begin{bmatrix} c \\ d \end{bmatrix} \begin{bmatrix} c \\ d \end{bmatrix} \begin{bmatrix} c \\ d \end{bmatrix} \begin{bmatrix} ddde \\ e \end{bmatrix}$$

This is a solution because if we read across the top, we get  $abcccdde$  and if we read across the bottom we get  $abcccdde$ . Thus we have solved this given PCB problem.

## Problem 6

Show that  $BB(k)$  is not a computable function.

*Proof.* We will show that  $BB(k)$  is not a computable function by proof by contradiction.

Assume that  $BB(k)$  is a computable function. Since  $BB(k)$  is a computable function, we can represent this function as a Turing machine. Let's name this TM,  $M_B$ .

$M_B$  = " On input  $k$  and  $w$ , where  $k$  is a natural number and  $w$  is a TM encoding:

1. If  $w$  has  $k$  states, continue, else *reject*.
2. Run  $HALT_{TM}$  with input  $w$ , if it accepts, continue, else reject.

This works because we can reduce our problem of finding the TM that runs the longest to the halting problem.

This is clearly a contradiction because we know that  $HALT_{TM}$  is undecidable thus by reduction,  $M_k$  is also undecidable □