

Factorization-Based Data Modeling

Practical Work 2

Umut Şimşekli, Mathieu Fontaine
Télécom ParisTech, Université Paris-Saclay, Paris, France
`umut.simsekli@telecom-paristech.fr`

Instructions: (please read carefully)

1. This homework can be done in groups of **maximum 2** people.
2. Prepare your report as a pdf file in English by using L^AT_EX or a similar software (Word etc). Do not submit scanned papers.
3. Put all your files (code and/or report) in a zip file: *surname_name_tp2.zip* and submit it to <https://www.dropbox.com/request/fFuzBEepyC9q0h7YhW9Z>. The deadline is **January 5th, 2018**. Late submissions will not be accepted.
4. One submission per group is sufficient.

1 Matrix Factorization with Stochastic Gradient Descent

In this section, you will implement the stochastic gradient descent algorithm for large-scale matrix factorization. The problem that we aim to solve is given as follows:

$$(W^*, H^*) = \arg \min_{W, H} \frac{1}{2} \|M \odot (X - WH)\|_F^2, \quad (1)$$

where $X \in \mathbb{R}^{I \times J}$ is the data matrix, and $W \in \mathbb{R}^{I \times K}$ and $H \in \mathbb{R}^{K \times J}$ are the unknown factor matrices. Here $\|A\|_F$ denotes the Frobenius norm of a matrix A and \odot denotes element-wise multiplication. Finally, $M \in \{0, 1\}^{I \times J}$ is the ‘mask’ matrix, denoting if a particular entry of X is observed or not: $m_{ij} = 1$ if x_{ij} is observed and $m_{ij} = 0$ otherwise.

2 Movie Recommendation

We will work on the MovieLens 1 Million dataset. This dataset contains ~ 1 million ratings applied to $I = 3883$ movies by $J = 6040$ users, resulting in a sparse data matrix X with 4.3% non-zero entries. Our aim will be to decompose this matrix into W and H by only using its observed entries. Once we obtain estimates for W and H , we can then use them for predicting the unobserved entries of X , which will enable us to make recommendations.

3 Exercises

Now go to the file `matrix_factorization_template.m`

1. Complete the stochastic gradient algorithm.

2. At the end of each iteration, compute the root-mean-squared-error, that is given as follows:

$$\text{RMSE} = \sqrt{\frac{\|M \odot (X - WH)\|_F^2}{N}} \quad (2)$$

where N is the number of observed entries in X .

3. Play with the algorithm parameters, i.e. the step-size, the batch-size, initialization, and the rank of the factorization. What do you observe? How do the step-size and the batch-size interact?
4. After estimating W and H , use them to recommend a movie for a given user.