


Named Entity Recognition

Fabian M. Suchanek

Semantic IE



Overview

- Named Entity Recognition
- ...by dictionary
- ...by regex

Named Entity


A **named entity** is an entity that has a name (and is not a literal, class, relation, fact id, or reified statement).



Douglas Adams



Télécom
ParisTech



Marvin

Def: Named Entity Recognition

Named entity recognition (NER) is the task of finding entity names in a corpus.

In Douglas Adams' book "The Hitchhiker's Guide to the Galaxy" the robot Marvin says: "I didn't ask to be made. No one consulted me or considered my feelings in the matter."

NER is difficult

Deposit a penny at the All American Bank...

All State Police helped evacuate...



Cable and Wireless, a major company...

Microsoft and Dell both agreed...



Marvin the Paranoid Android

?

?

Def: Dictionary

A dictionary (also: gazetteer, lexicon) is a set of entity names.

NER by dictionary finds only names of the dictionary.

It can be used if the entities are known upfront.

US states: {Alabama, Alaska, California, ...}

...lived in Los Angeles, **California**, while...

- US states
- countries
- Dow Jones companies
- Actors of a given movie
- ...

Naive Dictionary NER is slow

?

Books by Douglas Adams: {
Life, the Universe and Everything
Hitchhiker's Guide to the Galaxy
Mostly Harmless
... }

The Hitchhiker's Guide to the
Galaxy has "Don't Panic" on it,
in large, mostly friendly letters.

Naive Dictionary NER is slow

?


Books by Douglas Adams: {
Life, the Universe and Everything
Hitchhiker's Guide to the Galaxy
Mostly Harmless
... }

The Hitchhiker's Guide to the Galaxy has "Don't Panic" on it, in large, mostly friendly letters.

$$O(\text{textLength} \times \text{dictSize} \times \text{maxWordLength})$$

Def: Trie


A trie is a tree, where nodes are labeled with booleans and edges are labeled with characters.



A trie contains strings

A trie contains a string, if the string denotes a path from the root to a node marked with “true”.


{ADA, ADAMS, ADORA}



Adding strings (1)

To add a string that is a prefix of an existing string, switch node to “true”.


{ADA, ADAMS, ADORA}
+ ADAM



Adding strings (1)

To add a string that is a prefix of an existing string, switch node to “true”.


{ADA, ADAM,
ADAMS, ADORA}



Adding strings (2)

To add another string, make a new branch.


{ADA, ADAM,
ADAMS, ADORA} + ART



Adding strings (2)

To add another string, make a new branch.

{ADA, ADAM,
ADAMS, ADORA, ART}




Task: Tries

Start with an empty trie.

Add

- bon
- bonbon
- on





Tries can be used for NER

For every character in the doc

- advance as far as possible in the trie and
- report match whenever you meet a “true” node

Adams adores Adora.





Tries have good runtime

$$O(\text{textLength} \times \text{maxWordLength})$$

x phuong add « bon »
B
—>
x Waad add « on »
O
—>
x Issa
N
—>
bingo

Adams adores Adora.




Task: NER with tries

Do NER with the trie from the last task
on the document

on aime un bon bonbon.

One more example




kofi anan eats an ananas in panama, ana!

Tricks with Tries

In practice, you can

- force tries to respect word boundaries
- ignore upcase/lowercase
- preprocess the string
- ignore nested words
- ...



kofi anan eats an ananas in panama, ana!

Dictionary NER

Advantages:

- very efficient,

Disadvantages: dictionaries

- have to be given upfront
- have to be maintained to accommodate new names
- cannot deal with name variants
- cannot deal with infinite or unknown sets of names
(e.g., people's names)

Overview

- Named Entity Recognition
- ...by dictionary
- ...by regex

Some names follow patterns

The trilogy consist of 5 books,
written in 1979, 1980, 1982,
1984, and 1992, respectively.

Years

Dr. Frankie and Dr. Benjy
discuss how to best extract
the data from Arthur's brain.

People
with
titles



Main street 42
West Country

Addresses

Def: Alphabet, Word

An **alphabet** is a set of symbols.

$$A = \{a, b, c, d, e, f, 0, 1, 2, 3, 4, 5, 6, 7, 8, 9\}$$


We will use as alphabet always implicitly the set of all unicode characters.

$$A = \{0, \dots, 9, a, \dots, z, A, \dots, Z, !, ?, \dots\}$$

A **word** over an alphabet A is a sequence of symbols from A .

Since we use the alphabet of unicode characters, words are just strings.

hello!, 42, 3.141592, Douglas and Sally


also with spaces!

Def: Language

A **language** over an alphabet S is a set of words over S .

$L1 = \{\text{Arthur Dent, Ford Prefect, Marvin}\}$

$L2 = \{1900, 1901, 1982, 2013, 2017, \dots\}$

$L3 = \{0, 1, 2, 3, 4, 5, 6, 7, 8, 9\}$

$L4 = \{a, ab, abb, bbba, aaabbab, ababa, \dots\}$

$L5 = \{a, b, aa, bb, aaa, bbb, \dots\}$

$L6 = \{a, aa, aaa, \dots\}$

$L7 = \{ab, abab, ababab, \dots\}$

$L8 = \{c, ca, caa, caaa, \dots\}$

$L9 = \{, a, aa, aaa, \dots\}$



Set of strings

we want to describe

Def: Language

A language over an alphabet S is a set of words over S .

$L1 = \{\text{Arthur Dent, Ford Prefect, Marvin}\}$

$L2 = \{1900, 1901, 1982, 2013, 2017, \dots\}$

$L3 = \{0, 1, 2, 3, 4, 5, 6, 7, 8, 9\}$

$L4 = \{a, ab, abb, bbba, aaabbab, ababa, \dots\}$

$L5 = \{a, b, aa, bb, aaa, bbb, \dots\}$

$L6 = \{a, aa, aaa, \dots\}$

$L7 = \{ab, abab, ababab, \dots\}$

$L8 = \{c, ca, caa, caaa, \dots\}$

$L9 = \{, a, aa, aaa, \dots\} \quad a^*$



Set of strings
we want to describe



Our description
(much shorter than the original set!)

Def: Language

A language over an alphabet S is a set of words over S .

$L1 = \{\text{Arthur Dent, Ford Prefect, Marvin}\}$

$L2 = \{1900, 1901, 1982, 2013, 2017, \dots\}$

$L3 = \{0, 1, 2, 3, 4, 5, 6, 7, 8, 9\}$

$L4 = \{a, ab, abb, bbba, aaabbab, ababa, \dots\}$

$L5 = \{a, b, aa, bb, aaa, bbb, \dots\}$

$L6 = \{a, aa, aaa, \dots\}$

$L7 = \{, ab, abab, ababab, \dots\}$

$L8 = \{c, ca, caa, caaa, \dots\} \quad ca^*$

$L9 = \{, a, aa, aaa, \dots\} \quad a^*$



Set of strings
we want to describe



Our description
(much shorter than the original set!)

Def: Language

A language over an alphabet S is a set of words over S .

$L1 = \{\text{Arthur Dent, Ford Prefect, Marvin}\}$

$L2 = \{1900, 1901, 1982, 2013, 2017, \dots\}$

$L3 = \{0, 1, 2, 3, 4, 5, 6, 7, 8, 9\}$

$L4 = \{a, ab, abb, bbba, aaabbab, ababa, \dots\}$

$L5 = \{a, b, aa, bb, aaa, bbb, \dots\}$

$L6 = \{a, aa, aaa, \dots\}$

$L7 = \{, ab, abab, ababab, \dots\} \quad (ab)^*$

$L8 = \{c, ca, caa, caaa, \dots\} \quad ca^*$

$L9 = \{, a, aa, aaa, \dots\} \quad a^*$



Set of strings
we want to describe



Our description
(much shorter than the original set!)

Def: Language

A language over an alphabet S is a set of words over S .

$L1 = \{\text{Arthur Dent, Ford Prefect, Marvin}\}$

$L2 = \{1900, 1901, 1982, 2013, 2017, \dots\}$

$L3 = \{0, 1, 2, 3, 4, 5, 6, 7, 8, 9\}$

$L4 = \{a, ab, abb, bbba, aaabbab, ababa, \dots\}$

$L5 = \{a, b, aa, bb, aaa, bbb, \dots\}$

$L6 = \{a, aa, aaa, \dots\} \quad aa^* = a^+$

$L7 = \{, ab, abab, ababab, \dots\} \quad (ab)^*$

$L8 = \{c, ca, caa, caaa, \dots\} \quad ca^*$

$L9 = \{, a, aa, aaa, \dots\} \quad a^*$



Set of strings
we want to describe



Our description
(much shorter than the original set!)

Def: Language

A language over an alphabet S is a set of words over S .

$L1 = \{\text{Arthur Dent, Ford Prefect, Marvin}\}$

$L2 = \{1900, 1901, 1982, 2013, 2017, \dots\}$

$L3 = \{0, 1, 2, 3, 4, 5, 6, 7, 8, 9\}$

$L4 = \{a, ab, abb, bbba, aaabbab, ababa, \dots\}$

$L5 = \{a, b, aa, bb, aaa, bbb, \dots\} \quad a^+ \text{ --- } b^+$

$L6 = \{a, aa, aaa, \dots\} \quad aa^* = a^+$

$L7 = \{, ab, abab, ababab, \dots\} \quad (ab)^*$

$L8 = \{c, ca, caa, caaa, \dots\} \quad ca^*$

$L9 = \{, a, aa, aaa, \dots\} \quad a^*$



Set of strings
we want to describe



Our description
(much shorter than the original set!)

Def: Language

A language over an alphabet S is a set of words over S .

$L1 = \{\text{Arthur Dent, Ford Prefect, Marvin}\}$

$L2 = \{1900, 1901, 1982, 2013, 2017, \dots\}$

$L3 = \{0, 1, 2, 3, 4, 5, 6, 7, 8, 9\}$

$L4 = \{a, ab, abb, bbba, aaabbab, ababa, \dots\} \quad (a - b)^+$

$L5 = \{a, b, aa, bb, aaa, bbb, \dots\} \quad a^+ - b^+$

$L6 = \{a, aa, aaa, \dots\} \quad aa^* = a^+$

$L7 = \{, ab, abab, ababab, \dots\} \quad (ab)^*$

$L8 = \{c, ca, caa, caaa, \dots\} \quad ca^*$

$L9 = \{, a, aa, aaa, \dots\} \quad a^*$



Set of strings
we want to describe



Our description
(much shorter than the original set!)

Def: Language

A language over an alphabet S is a set of words over S .

$L1 = \{\text{Arthur Dent, Ford Prefect, Marvin}\}$

$L2 = \{1900, 1901, 1982, 2013, 2017, \dots\}$

$L3 = \{0, 1, 2, 3, 4, 5, 6, 7, 8, 9\} \quad (0 \text{ --- } 1 \text{ --- } \dots \text{ --- } 9) = [0-9]$

$L4 = \{a, ab, abb, bbba, aaabbab, ababa, \dots\} \quad (a \text{ --- } b)^+$

$L5 = \{a, b, aa, bb, aaa, bbb, \dots\} \quad a^+ \text{ --- } b^+$

$L6 = \{a, aa, aaa, \dots\} \quad aa^* = a^+$

$L7 = \{, ab, abab, ababab, \dots\} \quad (ab)^*$

$L8 = \{c, ca, caa, caaa, \dots\} \quad ca^*$

$L9 = \{, a, aa, aaa, \dots\} \quad a^*$



Set of strings
we want to describe



Our description
(much shorter than the original set!)

Def: Language

A language over an alphabet S is a set of words over S .

$L1 = \{\text{Arthur Dent, Ford Prefect, ...}\}$

$L2 = \{1900, 1901, 1982, 2013, 2017, ...\} [0-9][0-9][0-9][0-9] = [0-9]\{4\}$

$L3 = \{0, 1, 2, 3, 4, 5, 6, 7, 8, 9\} (0 \text{ --- } 1 \text{ --- } \dots \text{ --- } 9) = [0-9]$

$L4 = \{a, ab, abb, bbba, aaabbab, ababa, ...\} (a \text{ --- } b)^+$

$L5 = \{a, b, aa, bb, aaa, bbb, ...\} a^+ \text{ --- } b^+$

$L6 = \{a, aa, aaa, ...\} aa^* = a^+$

$L7 = \{, ab, abab, ababab, ...\} (ab)^*$

$L8 = \{c, ca, caa, caaa, ...\} ca^*$

$L9 = \{, a, aa, aaa, ...\} a^*$



Set of strings
we want to describe



Our description
(much shorter than the original set!)

Def: Language

A language over an alphabet S is a set of words over S .

- $L1 = \{\text{Arthur Dent, Ford Prefect, ...}\} \quad [A-Z][a-z]^+ [A-Z][a-z]^+$
 $L2 = \{1900, 1901, 1982, 2013, 2017, ... \} \quad [0-9][0-9][0-9][0-9] = [0-9]\{4\}$
 $L3 = \{0, 1, 2, 3, 4, 5, 6, 7, 8, 9\} \quad (0 \text{ --- } 1 \text{ --- } \dots \text{ --- } 9) = [0-9]$
 $L4 = \{a, ab, abb, bbba, aaabbab, ababa, ... \} \quad (a \text{ --- } b)^+$
 $L5 = \{a, b, aa, bb, aaa, bbb, ... \} \quad a^+ \text{ --- } b^+$
 $L6 = \{a, aa, aaa, ... \} \quad aa^* = a^+$
 $L7 = \{, ab, abab, ababab, ... \} \quad (ab)^*$
 $L8 = \{c, ca, caa, caaa, ... \} \quad ca^*$
 $L9 = \{, a, aa, aaa, ... \} \quad a^*$



Set of strings
we want to describe



Our description
(much shorter than the original set!)

Regular expressions

A regular expression (regex) describes a language.

$L1 = \{\text{Arthur Dent, Ford Prefect, ...}\} \quad [A-Z][a-z]^+ [A-Z][a-z]^+$

$L2 = \{1900, 1901, 1982, 2013, 2017, ... \} [0-9][0-9][0-9][0-9] = [0-9]\{4\}$

$L3 = \{0, 1, 2, 3, 4, 5, 6, 7, 8, 9\} (0 \text{ --- } 1 \text{ --- } \dots \text{ --- } 9) = [0-9]$

$L4 = \{a, ab, abb, bbba, aaabbab, ababa, ... \} \quad (a \text{ --- } b)^+$

$L5 = \{a, b, aa, bb, aaa, bbb, ... \} \quad a^+ \text{ --- } b^+$

$L6 = \{a, aa, aaa, ... \} \quad aa^* = a^+$

$L7 = \{, ab, abab, ababab, ... \} \quad L(E|F) = L(E) \cup L(F)$

$L8 = \{c, ca, caa, caaa, ... \} \quad ca^* \quad L(EF) = \{w_1w_2 : w_1 \in L(E), w_2 \in L(F)\}$

$L9 = \{, a, aa, aaa, ... \} \quad a^* \quad L(E^*) = \{w_1w_2...w_n : w_i \in L(E), n \geq 0\}$

$L(x) = \{x\}$ for symbols x



The language of a regular expression

Def: Regular expressions

A **regular expression** (regex) over an alphabet S is one of the following:

- the empty string
- an element of S
- a string of the form XY
- a string of the form $(X—Y)$
- a string of the form $(X)^*$

where X and Y are regexes

A regex is associated
to a language:

$$L(E|F) = L(E) \cup L(F)$$

$$L(EF) = \{w_1w_2 : w_1 \in L(E), w_2 \in L(F)\}$$

$$L(E^*) = \{w_1w_2...w_n : w_i \in L(E), n \geq 0\}$$

$$L(x) = \{x\} \text{ for symbols } x$$

the regular
expression

its language

Regular expressions cheat sheet

| | |
|--|-------------------------------------|
| $L(a) = \{a\}$ | Simple symbol |
| $L(ab) = \{ab\}$ | Concatenation |
| $L(a \mid b) = \{a, b\}$ | Disjunction |
| $L(a^*) = \{\epsilon, a, aa, aaa, \dots\}$ | Kleene star |
| $L(a^+) := L(aa^*)$ | shorthand for “one or more” |
| $L([a-z]) := L(a \mid b \mid \dots \mid z)$ | shorthand for a range |
| $L(a\{2,4\}) := L(aa \mid aaa \mid aaaa)$ | shorthand for a given number |
| $L(a\{3\}) := L(aaa)$ | shorthand for a given number |
| $L(a?) := L(\epsilon \mid a)$ | shorthand for “optional” |
| $L(.) := \{a \mid b \mid \dots \mid A \mid \dots \mid 0 \mid \dots \mid \backslash \}$ | shorthand for “any symbol” |
| $L(\backslash) := \{\backslash\}$ | escape sequence for special symbols |

Task: Regexes

| | |
|---|-------------------------------------|
| $L(a) = \{a\}$ | Simple symbol |
| $L(ab) = \{ab\}$ | Concatenation |
| $L(a \mid b) = \{a, b\}$ | Disjunction |
| $L(a^*) = \{, a, aa, aaa, \dots\}$ | Kleene star |
| $L(a^+) := L(aa^*)$ | shorthand for “one or more” |
| $L([a-z]) := L(a \mid b \mid \dots \mid z)$ | shorthand for a range |
| $L(a\{2,4\}) := L(aa \mid aaa \mid aaaa)$ | shorthand for a given number |
| $L(a\{3\}) := L(aaa)$ | shorthand for a given number |
| $L(a?) := L(\mid a)$ | shorthand for “optional” |
| $L(.) := \{a \mid b \mid \dots \mid A \mid \dots \mid 0 \mid \dots \mid _ \mid \$ \mid \backslash\}$ | shorthand for “any symbol” |
| $L(\backslash.) := \{.\}$ | escape sequence for special symbols |

Define regexes for

- numbers
- HTML tags
- phone numbers
- Names of the form “Dr. Blah Blub”

Try it

Helpful Web page

<https://regex101.com/>

REGULAR EXPRESSION

`/([A-Z][a-z]*)+/g`

TEST STRING

Elvis Presley

EXPLANATION

- ▼ `/([A-Z][a-z]*)+/g`
 - ▼ **1st Capturing Group** `([A-Z][a-z]*)`
 - + **Quantifier** — Matches between **one** and **unlimited** times, as many times as possible, giving back as needed (**greedy**)
A repeated capturing group will only capture the last

MATCH INFORMATION

Match 1

Full match 0-14 `Elvis Presley`

Group 1. 6-14 `Presley`

Real-world example

Segment N°1
(E-billet)
Départ : Chambéry 04/12/2017 06:24
Arrivée : Paris Gare De Lyon 04/12/2017 09:15
Train : SNCF 6960
Classe : Seconde (TGV PRO 2nde)
Siège de M. Thierry [REDACTED] : Voiture 006, Siège 101

Train

Segment N°2
(E-billet)
Départ : Paris Gare De Lyon 08/12/2017 18:45
Arrivée : Chambéry 08/12/2017 21:40
Train : SNCF 6951
Classe : Seconde (TGV PRO 2nde)
Siège de M. Thierry [REDACTED] : Voiture 007-Loisir, Siège 105

Train

```
Départ[\n\s]*(:)[\n\s]*(?'departure_station_name'.*)  
\s*(?'start_date'\d{2}\V\d{2}\V\d{4})\s*(?'start_time'\d{  
2}:\d{2}})[\n\s]*Arrivée[\n\s]*(:)[\n\s]*(?'arrival_station_  
name'.*)\s*(?'end_date'\d{2}\V\d{2}\V\d{4})\s*(?'end_ti  
me'\d{2}:\d{2}})[\n\s]*Train[\n\s]*(:)[\n\s]*(?'company_  
name'.*)\s+{'train_number'\d{2,5}}
```

Example from Wipolo via Dhouha Bouamor

Named regexes

When using regular expressions in a program, it is a good idea to name them:

```
String digits = "[0-9]+";
```

```
String separator = "( —-)";
```


```
String pattern = digits+separator+digits;
```

But: Human beings, who are almost unique in having the ability to learn from the experience of others, are also remarkable for their apparent disinclination to do so. (Douglas Adams)

Regex groups

A regex group is a sequence of the form (...) in a regex.


the answer to ([a-z]+),
the (([a-z]+) and ([a-z]+))



A red rectangular box highlights the sub-expression `[a-z]+` within the first group `([a-z]+)` of the regex pattern `([a-z]+)`. A red arrow points from the text "1st group" to the top-right corner of this box.

Regex groups

A regex group is a sequence of the form (...) in a regex.



Regex groups

He found the answer to life,
the universe, and everything

the answer to ([a-z]+),
the (([a-z]+) and ([a-z]+))

1st group: life

2nd group: universe and everything

3rd group: universe

4th group: everything

Try it out!

How can we match regexes?

Douglas Adams fictional character names:


`[A-Z][a-z]*ch[a-z]*`

?

The Hitchhiker meets the Golgafrinchan civilisation,
but falls in love with a girl named Fenchurch.

Def: Finite State Machine


A **finite state machine** (FSM) is a directed multi-graph, where each edge is labeled with a symbol or the empty symbol ϵ . One node is labeled “start” (typically by an incoming arrow). Zero or more nodes are labeled “final” (typically by a double circle).



details>91

Def: Acceptance

An FSM **accepts** (also: generates) a string, if there is a path from the start node to a final node whose edge labels are the string.



ad ✓


bccd ✓

bb ✗

details > 91


Task: FSM

Find strings generated by the following FSM (Betelgeuse 7 language):



Notation

- start node



- final node




- empty transition

(can be walked without accepting a symbol)



- multiple edges



Task: FSM

Draw an FSM that accepts the following strings

br

kbr

brbr

kbrbr

brbrbr

kbrbrbr ...

Draw an FSM that accepts the following strings

ling

ping

pong

long

lingping

lingpong

pingpong


Transforming a regex to a FSM (1)

1. Simplify the regex to contain only concatenation, alternation, kleene star

2. Start with this configuration:




3. Handle alternation:




Transforming a regex to a FSM (2)

4. Handle concatenation:



5. Handle Kleene star:



6. Proceed recursively, until all edges are single symbols

[details > 91](#)

FSM = Regex

For every regex, there is an FSM that accepts exactly the words of the language of the regex (and vice versa).

Examples:

- $k?(br)^+$
- $((l-p)(i-o)ng)^*$
- $f\{2,3\}$

Runtime of regexes

Given a word of length l and given an FSM with n states, determining whether the FSM accepts the word

- takes $O(l)$ time if no state has several outgoing edges with the same label
- $O(l \times 2^n)$ else

There is a looooooot more to say about FSMs, e.g.:

- making them deterministic
- compressing them
- making them more powerful
- learning FSMs from examples

Here, we only use them for IE

Regexes in programming

Regex


42(0)+

you

Simplified regex

420(0)*

FSM



your
programming
language

Matcher

His favorite numbers
are 42, 4200, and 19.

Example: Regexes in Java

```
Pattern pattern = Pattern.compile("42(0)+");  
Matcher matcher = pattern.matcher("His favorite numbers are...");  
while(matcher.find())  
    System.out.println(matcher.group());
```

————→ 4200

His favorite numbers
are 42, 4200, and 19.

Entity Recognition

We have seen 2 methods to do entity recognition:

- Tries (if the set of names is known)
- Regexes (if the names follow a pattern)

Douglas N. Adams had the idea for the “Hitchhiker’s Guide” while lying drunk in a field near Innsbruck.

->evaluation

->named-entity-annotation

->disambiguation

Sponsored Link: Dancing Class



Join the free dancing class at Télécom ParisTech
Mondays 19:30-21:30, in English
<https://suchanek.name/dancing>

References

Sunita Sarawagi: Information Extraction

->evaluation

->named-entity-annotation

->disambiguation