

This lecture:

- computing square roots
- Python demo
- git demo

Computing square roots

Hardware arithmetic units can add, subtract, multiply, divide.

Other mathematical functions usually take some software.

Computing square roots

Hardware arithmetic units can add, subtract, multiply, divide.
Other mathematical functions usually take some software.

Example: Compute $\sqrt{2} \approx 1.4142135623730951$

In most languages, `sqrt(2)` computes this.

```
>>> from numpy import sqrt  
>>> sqrt(2.)
```

One possible algorithm to approximate $s = \sqrt{x}$

```
s = 1.      # or some better initial guess
for k in range(kmax):
    s = 0.5 * (s + x/s)
```

where k_{\max} is some maximum number of iterations.

Note: In Python, `range(N)` is $[0, 1, 2, \dots, N - 1]$.

One possible algorithm to approximate $s = \sqrt{x}$

```
s = 1.      # or some better initial guess
for k in range(kmax):
    s = 0.5 * (s + x/s)
```

where k_{\max} is some maximum number of iterations.

Note: In Python, `range(N)` is $[0, 1, 2, \dots, N - 1]$.

Why this works...

If $s < \sqrt{x}$ then $x/s > \sqrt{x}$

If $s > \sqrt{x}$ then $x/s < \sqrt{x}$

One possible algorithm to approximate $s = \sqrt{x}$

```
s = 1.      # or some better initial guess
for k in range(kmax):
    s = 0.5 * (s + x/s)
```

where k_{\max} is some maximum number of iterations.

Note: In Python, `range(N)` is $[0, 1, 2, \dots, N - 1]$.

Why this works...

If $s < \sqrt{x}$ then $x/s > \sqrt{x}$

If $s > \sqrt{x}$ then $x/s < \sqrt{x}$

In fact this is **Newton's method** to find root of $s^2 - x = 0$.

Newton's method


Problem: Find a solution of $f(s) = 0$ (zero or root of f)

Idea: Given approximation $s^{[k]}$,
approximate $f(s)$ by a linear function,
the tangent line at $(s^{[k]}, f(s^{[k]}))$.

Find unique zero of this function and use as $s^{[k+1]}$.

Newton's method

$$f(s) = s^2 - x$$



Newton's method

Problem: Find a solution of $f(s) = 0$ (zero or root of f)

Idea: Given approximation $s^{[k]}$,
approximate $f(s)$ by a linear function,
the tangent line at $(s^{[k]}, f(s^{[k]}))$.

Find unique zero of this function and use as $s^{[k+1]}$.

Updating formula:

$$s^{[k+1]} = s^{[k]} - \frac{f(s^{[k]})}{f'(s^{[k]})}$$
$$S = S - \frac{S^2 - x}{2S} = \frac{1}{2} \left(S + \frac{x}{S} \right)$$

Goals:

- Develop our own version of `sqrt` function.
- Start simple and add complexity in stages.
- Illustrate some Python programming.
- Illustrate use of git to track our development