ABSW1.0T Washing Plant





Water Recycling Advantage

- Designed to **reuse the same water multiple times**, significantly reducing overall consumption.
- Reduces operational costs while being **environmentally friendly**.
- Helps in **compliance with environmental norms** and supports **sustainability certification**.

Material Compatibility

- **Compatible Materials:** PP, HDPE, LDPE, ABS, HIPS, GPPS
- **Note:** ABS, HIPS, GPPS require an **extra conveying syst**

Heater & Usage Details

- **Normal Use Temperature:** 60°C – 80°C
- **Cooling Climate Adjustment:** +10°C possible
- **Functionality:**
    - At **60°C – 80°C** → Removes oil, grease, germs, and chemical content.
    - At **120°C – 140°C** → Chips can directly proceed to extrusion without mixing.

- **Water Recycling Benefits:**
    - Maintains water quality for extended use.
    - Reduces soap oil usage.
    - Minimizes caustic soda requirement.

Additional Notes

- **Cleaning Time:**
    - Normal cleaning → ~10 minutes
    - Material/color change → ~30 minutes
- **Motor Pressure:** High-speed water pressure
- **Material Size Range:** 1 mm – 25 mm
- **Output Material Temperature:**
    - From 80°C – 90°C → can reach 120°C – 140°C
    - From 40°C – 60°C → can achieve ~36°C

MODEL		W250	W500	W750	W1000	W1500	W2000
Capacity(kg/h)		250 kg/h	500 kg/h	750 kg/h	1000 kg/h	1500 kg/h	2000 kg/h
Heater power		36kw	72kw	108kw	144kw	216kw	240kw
Water Motor		5HP	5HP	5HP	7HP	10HP	10HP
Dryer Motor		HP	10HP	15HP	15HP	20HP	20HP
Second washing motor		5HP	5HP	5HP	10HP	10HP	15HP
Material Used		SS 302					
Motor	Brand	Havells					
Starter	Brand	Havells					
Voltage		380V 50H 3Phase					
Water Capacity		800L	1600L	1900L	2100L	2500L	3000L
Size	**L/mm**	3048	3658	4267	4877	5069	5486
	W/mm	609	914	1067	1219	1219	2134
	H/mm	2488	2488	2488	2488	2488	2488
Weight		650kg	1300kg	1500kg	1800kg	2200kg	3000kg

MODEL		W3000	W4000	W5000
Capacity(kg/h)		3000 kg/h	4000 kg/h	5000 kg/h
Heater power		360kw	480kw	600kw
Water Motor		5HP	5HP	40HP
Dryer Motor		10HP	10HP	15HP
Second washing motor		5HP	5HP	5HP
Material Used		SS 302		
Motor	Brand	Havells		
Starter	Brand	Havells		
Voltage		380V,50Hz,3 Phase		
380Water Capacity		800L	1600L	1900L
Size	**L/mm**	3048	3658	4267
	W/mm	609	914	1067
	H/mm	2488	2488	2488
Weight		650kg	1300kg	1500kg

Plastic crusher machine

The Plastic crusher machine is a high-performance size-reduction machine designed for efficient grinding of plastic waste, regrind materials, and production scrap. Available in capacities ranging from 250 kg/h to 2000 kg/h, the grinder is equipped with powerful 20 HP to 60 HP motors to ensure consistent throughput and reliable operation. The grinding chamber sizes range from 600 × 480 mm to 1016 × 762 mm, enabling the machine to handle a wide variety of plastic products. High-strength EN41 steel blades provide excellent wear resistance, long service life, and precise cutting performance for demanding industrial applications.

The grinder operates at a constant speed of 480 rpm and features a minimum 20 mm screen mesh for uniform output particle size. Powered by a 380V, 50Hz, 3-Phase electrical system, it incorporates trusted Havells motors and starters for dependable performance and enhanced safety. Depending on the model, machine dimensions range from 1580 mm to 2240 mm in length, 1100 mm to 1590 mm in width, and 1850 mm to 1950 mm in height, with weights ranging from 800 kg to 2700 kg. Its robust construction, high crushing efficiency, and low maintenance requirements make the G Series Grinder an ideal solution for plastic recycling and processing industries.

MODEL		G250	G500	G750	G1000	G1500	G2000
Crushing ability		250 kg/h	500 kg/h	750 kg/h	1000 kg/h	1500 kg/h	2000 kg/h
Crushing chamber		600×480mm	762×533mm	812×533mm	914×533mm	914×711mm	1016×762mm
Motor Power		20HP	40HP	50HP	50HP	60HP	60HP
Blade Material		EN41					
Motor	Brand	Havells					
Starter	Brand	Havells					
Speed	**r/min**	480	480	480	480	480	480
Screen mesh		Min 20MM					
Voltage		380V 50H 3Phase					
Size	**L/mm**	1580	1670	1790	1950	1950	2240
	W/mm	1100	1250	1250	1250	1530	1590
	H/mm	1850	1850	1850	1850	1950	1950
Weight		800kg	1400kg	1600kg	2000kg	2200kg	2700kg

Screw Conveyor

The CR Series Screw Conveyor is designed for efficient material handling with capacities ranging from 250 kg/h to 2000 kg/h, making it suitable for small, medium, and large-scale industrial applications. The conveyor is equipped with screw diameters from 152 mm to 300 mm and is powered by robust 7 HP to 20 HP Havells motors, ensuring reliable performance and continuous operation. The system operates on 380V, 50Hz, 3-Phase power supply and incorporates high-quality Havells starters for enhanced durability and operational safety.

The conveyor features a compact yet sturdy design with a standard length of 5400 mm across all models. Depending on the model, widths range from 300 mm to 550 mm, heights from 450 mm to 750 mm, and weights from 320 kg to 780 kg. Operating speeds vary between 55 RPM and 105 RPM, allowing optimized material flow according to processing requirements. The CR Series is engineered for smooth conveying, low maintenance, and long service life, making it an ideal solution for bulk material transfer in manufacturing and processing industries.

MODEL		CR250	CR500	CR750	CR1000	CR1500	CR2000
Capacity		250 kg/h	500 kg/h	750 kg/h	1000 kg/h	1500 kg/h	2000 kg/h
Screw OD		152mm	200mm	200mm	250mm	250mm	300mm
Motor Power		7HP	10HP	10HP	15HP	15HP	20HP
Motor	Brand	Havells					
Starter	Brand	Havells					
Speed	**RPM**	55	60	90	70	105	90
Voltage		380V 50H 3Phase					
Size	**L/mm**	5400	5400	5400	5400	5400	5400
	W/mm	300	350	350	450	450	550
	H/mm	450	500	500	600	600	750
Weight		320kg	420kg	450kg	580kg	620kg	780kg

Material Transport Blower Specification

The Material Transport Blower is designed for efficient conveying of plastic flakes, granules, and regrind materials in recycling and processing plants. The blower features a dynamically balanced MS impeller, heavy-duty fabricated steel housing, and a high-efficiency direct-coupled motor for continuous industrial operation. It is suitable for ABS, HIPS, PP, HDPE, LDPE, and PET material handling applications.

The blower is available in capacities ranging from 250 kg/hr to 2000 kg/hr, with motor ratings from 5 HP to 20 HP. The unit operates on 415V, 3-Phase, 50Hz power supply and is fitted with pipe sizes from 4” to 10” depending on the production requirement. The robust construction ensures low maintenance, high conveying efficiency, and reliable performance in demanding recycling environments. The blower assembly is mounted on a heavy-duty MS base frame and finished with industrial-grade paint for long service life.

MODEL		MTB250	MTB500	MTB750	MTB1000	MTB1500	MTB2000
Capacity		250 kg/h	500 kg/h	750 kg/h	1000 kg/h	1500 kg/h	2000 kg/h
Pipe size		100mm	125mm	150mm	150mm	200mm	250mm
Motor Power		5HP	7HP	10HP	10HP	15HP	20HP
Air flow		1800 m³/h	2500 m³/h	3500 m³/h	4000 m³/h	5500 m³/h	6500 m³/h
Static Pressure		250mmWG	300mmWG	350mmWG	350mmWG	400mmWG	450mmWG
Motor	Brand	Havells					
Starter	Brand	Havells					
Material Used		MS					
Speed	**RPM**	2880	2880	2880	2880	2880	2880
Voltage		380V 50H 3Phase					
Size	**L/mm**	700	800	900	1000	1200	1400
	W/mm	500	600	700	700	850	1000
	H/mm	700	800	900	1000	1200	1400
Weight		90kg	120kg	160kg	180kg	250kg	320kg