

Nomad Connect 2023.4

Release Notes

12th of January 2024

Author	Ben Turner
Issue number	2023.4
Number of pages	4

Document control

Version	Version date	Summary of edits	Created By	Approved By
1	12.01.2024	First version of the document	Ben Turner	Dieter Termote

The information in this document is subject to change without notice and should not be construed as a commitment by Nomad Digital Ltd. While reasonable precautions have been taken, Nomad Digital Ltd assumes no responsibility or liability for technical inaccuracies or typographical errors that may appear in this document. Nomad Digital Ltd reserves the right to revise this publication without obligation to provide notification of such revisions.

Features

Key	Summary:
RD-9994	Features were added to ensure that the virtual user could properly function in the CDC to report statistics to the NMS.
RD-10749	A feature was added to the mosquito module allowing for a custom configuration file.
RD-10816	Nomad Connect will now publish a new protobuf-based message to the MQTT bus containing all cellular statistics.
RD-10817	A tool called pb2json is now included in Nomad Connect allowing debugging of the new protobuf-based messages that Nomad Connect supports.
RD-10834	The BIOS version has been added to the engineering pages CCU overview page.
RD-10835	NC support for the 4600-2Ax platform has been added.
RD-10842	Various Debian packages were updated to address software vulnerabilities.
RD-10848	Features were added to Nomad Connect to allow for a custom configuration file for the mosquito MQTT broker.
RD-10872	1st release with full support for 5001b, 5001c 4600v2x, 4600v3 on Debian 12

Defects

Key	Summary:
10836	Under certain circumstances the NMS was not able to display ICCID data correctly generated by Nomad Connect. This has been resolved.
RD-10762	In order to avoid naming issues on ethernet devices, all eth0/1/2 devices will be named lan0/1/2 from now on. This means that ALL configuration referring to eth0/1/2 MUST be changed as the network devices will be named lan0, lan1, etc.
RD-10740	Under certain circumstances the mar3/lte_statistic messages did not contain a correct band and/or bandwidth. This has been resolved.
RD-9996	JAXB versions used by mar3-frontend 2.0.13 set specifically to work properly with Jersey, so NMS authentication and data usage occurs without issue using JAVA 17 on Debian 12.

HW Platforms tested in this release

All formal testing was completed on dedicated QA benches as follows:

CCU	Card / Storage	Modem / mPCIe	Layer 3
R5001c	SSD	EM7565 FN990A40 FN990A28 M8 GPS	Oring Switch Eltec NAP-1022-2GP-M12X NM31 Switch
4600v3	CFAST	FN990A40 FN990A28	Oring Switch Eltec NAP-1022-2GP-M12X NM31 Switch
4600v2	CFAST	EM7455 MC7455 LM940 Onboard GPS	Oring Switch Cybox AP1
R5001B	MicroSD	G25A G227 MC7455 LM940 M8 GPS	Eltec Switch Cybox AP2 x2 G25A G227
4600v1	MicroSD	MC7455 Onboard GPS	MEN NL34 Cybox AP1
B2010	CFAST	MC7455 EM7455 Onboard GPS	