

Nomad Connect 2024.3

Release Notes

15 October 2024

Author	Dieter Termote
Issue number	2024.3
Number of pages	4

Document control

Version	Version date	Summary of edits	Created By	Approved By
1	15.10.2024	First version of the document	Dieter Termote	Ben Turner

The information in this document is subject to change without notice and should not be construed as a commitment by Nomad Digital Ltd. While reasonable precautions have been taken, Nomad Digital Ltd assumes no responsibility or liability for technical inaccuracies or typographical errors that may appear in this document. Nomad Digital Ltd reserves the right to revise this publication without obligation to provide notification of such revisions.

What's new – Key changes

This Nomad Connect release includes:

- New Features
 - MAR5 Algorithms : Round Robin (useful for saturation tests) & Best RTT (link selection based on best latency).
 - CDC failover supported
 - Simplify connection to SW/AP with NC versions
- HW Support
 - Updated modem management : shutdown & switching
 - OBN support Moxa 10gbps switch - NMID912
- Regular maintenance and security updates : Bug fixes & security patches.
 - For asset management: physical disks reported (instead of partitions)

Features

Key	Release Notes
RD-11147	A round-robin vlink type was added to mar5; this is not a vlink that is normally used in production scenarios but can be useful for testing or validation purposes.
RD-11151	As part of the effort to make MAR5 have the same features for MAR3, the best RTT virtual link type was added to MAR5.
RD-11170	Changes were made to the puppet manifests to allow for custom SSH (not sshd) configurations on the CCU. This can handle situations where, for instance, we have older network equipment on-board that might have outdated ciphers that are disallowed by the standard SSH configuration.
RD-11212	Changes were made to the Debian10 → Debian12 upgrade scripts to ensure they were more resilient.
RD-11236	Changes were made to nd-redundancy to allow for a configurable bond mode. Previously this was always balance-xor but it can now also be configured as one of balance-rr (0), active-backup (1), balance-xor (2, default), broadcast (3), 802.3ad (4), balance-tlb (5) or balance-alb (6).
RD-11247	A number of critical Debian security vulnerabilities were addressed.
RD-11254	In order to make things more consistent across the puppet manifests, all sim-switch-xxx packages were renamed to nd-ccu-xxx.
RD-11263	In order to avoid broken installations, Nomad Connect will now only install on a list of known hardware. If an attempt is made to install NC on unsupported hardware, the puppet run will fail with an appropriate message.
RD-11302	The multi_modem_config module now also allows for fixed mac addresses in configured links.
RD-11398	MAR3 can now be configured to use vlan10-29 and report them via MQTT appropriately.
RD-11407	MAR3 now optionally supports a primary-secondary failover mechanism, where a secondary remote endpoint can be configured to be used for the tunnel in cases of the primary remote endpoint is unreachable.
RD-11428	A number of MAC prefixes have been added to the known OBN list of Eltec Cybox APs.

Defects

The following defects were addressed in this release:

Key	Release Notes
RD-11456	The front X1/X2 network devices on the 2.5 and 10 Gbit/s 5001C CPU blades were not being mapped correctly when inserted in other slots in the chassis. This has been resolved.
RD-11315	Support for the 5001C was added to the FN990 modem watchdog.

HW Platforms tested in this release

All formal testing was completed on dedicated QA benches as follows:

CCU	Card / Storage	Modem / mPCIe	Layer 3
R5001c	SSD	FN990A40 FN990A28 M8 GPS	10GB Oring Switch Eltec NAP-1022-2GP-M12X NM31 Switch
4600v3	CFAST	FN990A40 FN990A28 EM7455 EM7421 Compex 600	Oring Switch Eltec NAP-1022-2GP-M12X NM31 Switch
4600v2	CFAST	EM7455 MC7455 LM940 Onboard GPS	Oring Switch Cybox AP1
R5001B	MicroSD	G25A G227 MC7455 LM940 M8 GPS 7P GPS	Eltec Switch Cybox AP2 x2 G25A G227
4600v1	MicroSD	MC7455 Onboard GPS	MEN NL34 Cybox AP1
B2010	CFAST	MC7455 EM7455 Onboard GPS	
R3500	SSD	MC7455 M8 GPS 7P GPS	SATA Blades G501R F22P12