

Nomad Connect 2024.4

Release Notes

7Feb25

Author	Dieter Termote
Issue number	2024.4
Number of pages	4

Document control

Version	Version date	Summary of edits	Created By	Approved By
1	7.02.2025	First version of the document	Dieter Termote	Ben Turner

The information in this document is subject to change without notice and should not be construed as a commitment by Nomad Digital Ltd. While reasonable precautions have been taken, Nomad Digital Ltd assumes no responsibility or liability for technical inaccuracies or typographical errors that may appear in this document. Nomad Digital Ltd reserves the right to revise this publication without obligation to provide notification of such revisions.

What's new – Key changes

This Nomad Connect release includes:

- New Features
 - IPv6 supported as a modem carrier.
 - Setup configurable Syslog client which allows log to be transmitted to an IP endpoint. This can be customized on a project basis.
 - Support Strong Swan Ipsec tunnel
- HW Support
 - Support R2010 with EM7421, FN990A28 and EM7565.
 - Extra monitoring 5001C: temperatures & fan speeds. This can now be setup in NMS/Zabbix for alerts.
- Regular maintenance and security updates : Bug fixes & security patches.
 - Includes update which allows for Nomad Secure to report on Nessus signature & port scan.

Features

Key	Release Notes
RD-9930	Functionality was added to Nomad Connect to allow configurable and scriptable syslog data to be transmitted to an IP endpoint.
RD-10328	Changes were made to Nomad Connect to allow for system updates to succeed even if the /var/log partition is full.
RD-11045	Nomad Connect now comes with an optional ipsec module, supporting Strongswan ipsec tunnels from the CCU to an endpoint.
RD-11181	Full support for the R2010 CCU has been added to Nomad Connect.
RD-11438	Nomad Connect now supports versioned releases of all K8S components.
RD-11470	Nomad Connect now supports Zabbix monitoring of the on-board CMM of the 5001c, allowing for follow-up of items such as inlet temperature and power consumption.
RD-11567	The obn :auto_update_speed_threshold has been added, allowing for the speed at which OBN will start automatic updates to be configured (if enabled).
RD-11275	Nomad Secure - Nessus signatures not being detected in Wazuh 4.9.0 / Debian12 NC
RD-11276	Nomad Secure - Port scans not being detected in Wazuh 4.9.0 / Debian12 NC

Defects

The following defects were addressed in this release:

Key	Release Notes
RD-11584	The whereami command used in the verification scripts was replaced with a standard call to the local GPS API.
RD-11505	A lack of logging was making it hard to debug a dynamic routing issue in the CDC, extra logging was added to rectify this.
RD-11461	A long-standing out-of-memory issue was resolved in the mar3-backend software.
RD-11421	A bug in the mqtt-bridge software was causing it not to recover properly when an error occurred. This has been fixed.

HW Platforms tested in this release

All formal testing was completed on dedicated QA benches as follows:

CCU	Card / Storage	Modem / mPCIe	Layer 3
R5001c	SSD	FN990A40 FN990A28 M8 GPS	10GB Oring Switch Eltec NAP-1022-2GP-M12X NM31 Switch
4600v3	CFAST	FN990A40 FN990A28 EM7455 EM7421 Compex 600	Oring Switch Eltec NAP-1022-2GP-M12X NM31 Switch
4600v2a2	CFAST	EM7455 MC7455 LM940 Onboard GPS	Oring Switch Cybox AP1
R5001B	MicroSD	G25A G227 MC7455 LM940 M8 GPS 7P GPS	Eltec Switch Cybox AP2 x2 G25A G227
4600v1	MicroSD	MC7455 Onboard GPS	MEN NL34 Cybox AP1
B2010	CFAST	MC7455 EM7455 Onboard GPS	
R3500	SSD	MC7455 M8 GPS 7P GPS	SATA Blades G501R F22P12
R2010	CFAST	EM7421 EM7565 FN990A28	