Probe pipeline: prefetched root-table probes for the combined n = 83 K600 one-target index calculus

2026-10-15

Probe pipeline: prefetched root-table probes for the combined n = 83 K600 one-target index calculus

Status (2026-10-15): profile done (diagnostic), fix implemented and checked for exactness, protocol frozen, Tier 1 run started; no result yet. The frozen protocol and schedule were committed before any Tier 1 timing. The run is the push-triggered workflow `.github/workflows/n83-probe-pipeline.yml` on branch `claude/n83-probe-pipeline`. Its receipt, result, result figure and the refreshed PDF are owed after the run. Nothing on this page is a Tier 1 measurement yet.

Question

The n = 83 a = 1 K600 one-target IC's online interval is about 100% `target_PDP`: per probe, a batched S3 root solve, a `to_normal` byte-table conversion, canonicalization, and a lookup into the ~4 GiB root table. Two promoted improvements are now combined (`claude/n83-combined`, protocol frozen, run 38803625711 in flight): `lift_scan` canonicalization (1.52x online) and the Feistel scan order (1.45x on held-out points). The `ic-probe-latency-20261015` experiment measured an IC probe at 574 ns against a bare 4 GiB pointer chase at 140 ns.

Which component dominates the combined producer's probe, and does the fix that matches it lower the one-target online time on new public points, with probes, relation and scalar unchanged? Under AGENTS.md's success criterion, a verified, measured improvement over the current baseline is a success and becomes the new baseline.

1. Profile of the combined probe path (diagnostic)

All numbers in this section come from the cloud-agent VM, a shared 4-vCPU guest. They chose the fix; they are not evidence of a speedup. The raw files are in `smoke/profile/`, the table in `analysis/profile_local.json` (`analysis/make_profile_table.py`).

- **Instrument.** The profiler `ic_probe_profile_r770` (`make_profile_source.py`, a derived copy of the producer that is never a timed arm) walks the first 400 index states of target w11's Feistel order (132,800 probes) and times cumulative variants of the per-state work, all probes and no early exit, 7 rounds in rotated order: roots; + `to_normal`;
  - `lift_scan`; + inline lookup (the combined loop); and, for comparison, the pipelined lookup. Differences are marginal costs in situ. The root table is THP-backed (`glibc.malloc.hugetlb=1`), as on the runner, whose THP mode is `always`.
- **Instruction counts.** callgrind on the same profiler, one variant per run, with 1 and 2 passes; the difference is one pass, so setup cancels. It runs on a constructed K = 40 base (200 states, 66,400 probes), because instructions per probe do not depend on the table size (`smoke/profile/callgrind.sh`).
- **The rest.** The real producer (`KIC_PROBE_PIPELINE=off`, the combined loop) on w11, w08 and w14 ran at 472 ns/probe on the same VM. That is the inline-lookup variant's 474 ns within noise, so everything else (hits, lift, relation check, laps, the Feistel order) is about 0.

component	ns/probe (diagnostic)	share of 472 ns	instructions/probe (callgrind)
root solve (2n inputs + batched S3 solve)	130	28%	132
`to_normal` conversion	16	3%	187
`lift_scan` canonicalization	52	11%	334
root-table lookup (4 GiB)	**276**	**59%**	**22**
rest	about 0 (-2)	0%	

The dominant cost is the root-table lookup, and it is latency-bound: 22 instructions per probe take 276 ns, 59% of the probe. The compute components together are 198 ns. Instruction counts per variant come from a different codegen of each variant, so the per-component instruction split (especially conversion against root solve) is approximate; the latency reading does not depend on it.




Figure 1: Probe-path profile (diagnostic)

So the fix is the latency fix, not a wider batch for the root solve (28%) or a GFNI/clmul conversion (3%).

2. The fix: software-pipelined probes with prefetch

`make_online_source.py` derives the producer in two steps:

1. `make_combined_source.py` is `claude/n83-combined`'s `make_online_source.py` @ 88e1929fb, verbatim. Its output must hash to the combined protocol's frozen producer digest (`f65e518a...`), so the baseline text is exactly the combined producer.
2. Counted, exact replacements add a compile-time selector `P` on the target scan, chosen per process by `KIC_PROBE_PIPELINE`:
   - `off`: `scan_state128`, byte for byte unchanged (the combined loop);
   - `prefetch`: `scan_state128_pipelined`. Same root batch. Then, in the same candidate order (shift outer, stored root inner, solver partner order), every partner's `to_normal` word and `lift_scan` key, each followed by `_mm_prefetch(T0)` of its home slot. Then the lookups, lift and relation check in that same order, with the same probe counter and the same first-hit return.

Exactness. The probe sequence, the counter, the lookup, the lift and the return are those of `off`, so the probes, relation and scalar are identical on every target. The only extra work is computing keys for the probes after the successful one in the final state (at most 4n - 1 canonicalizations), which the clock charges. The rank stage always runs `PIPE_OFF`. Locally, on w11, w08 and w14, both settings gave identical probes (160,866, 161,864, 183,505), relations and scalars, equal to the earlier combined binary's; see `smoke/`.




Figure 2: The two loop structures

In the profiler the pipelined lookup costs 145 ns/probe instead of 276 (474 → 343 ns/probe, diagnostic). A deeper, cross-state pipeline (a state's lookups consumed after the next state's keys) gave the same 342 ns, so the remaining lookup cost is not a short prefetch distance. The lookup-only loops (65-73 ns per lookup with no compute) point at TLB and page-walk cost under the VM's nested paging; that is a hypothesis for the next step, not a measurement.

3. Frozen Tier 1 design

Arm	Canonicalizer	Order	Probe loop	Panel	Role
`pC`	lift	Feistel	off	primary	baseline: the combined producer
`pP`	lift	Feistel	prefetch	primary	candidate
`pPaa`	lift	Feistel	prefetch	primary	A/A control
`pX`	lift + discarded full scan	Feistel	prefetch	primary	planted positive control
`rT`	—	—	—	primary, every point	tuned rho rT770 (Fold/64/DP6), seed 850000 + point seed
`oC`, `oP`	lift	Feistel	off / prefetch	Q0 + B's 16 fresh, 1 block	exactness against the archived Feistel identities; secondary

- **Primary panel.** 384 new public points (`inputs/primary_targets.json`, `make_targets.py`) from B's public hash-to-curve law with the new role `probepipe-primary-v1`, seeds 0..383. They are checked disjoint from Q0, B's 16 fresh points (role `eval`), the 384 scan-order held-out points and the 576 combined primary points (both regenerated from the law). No scalar is known for any of them.
- **One job, one pinned CPU.** Six primary slices of 64 points and one Q0 + fresh block, P1, P2, P3, O1, P4, P5, P6. Within each segment the order is a seeded shuffle. Every primary slice holds one process per IC arm and one rho process per point. Each IC process does its setup once and then gives each target its own one-target online interval.
- **Primary statistic.** R_m = mean `pC` / mean `pP`, online time over all 384 points, bootstrap over points, 10,000 resamples.
- **Decision rule. Improvement** iff the 95% lower bound of R_m exceeds 1; regression iff its upper bound is below 1; otherwise not_separated. The verdict is **invalid** if an exactness gate fails, the A/A (`pP`/`pPaa` inside [0.97, 1.03]) or the planted control (`pX`/`pP` lower bound above

1) fails, or any of the 384 points lacks a valid row in an arm.

- **Also reported.** R_g (paired geometric means), ns/probe per arm, the probe ratio (must be exactly 1), the new `S_rho` for `pC` and `pP` and its delta, the tuned-rho gap on the same points, the slice bootstrap and per-slice ratios, and the Q0 + fresh block.
- **Exactness gates.** On every primary point the four IC arms have identical probes and relation; one scalar across them and the tuned rho; every scalar replays as [d]G = Q in the pinned oracle. On Q0 + 16 fresh, both arms reproduce the archived Feistel probes and relations of run 38786433493, the archived scalars, and Q0's validation sidecar.
- **Power, checked before freezing** (`power_check.py`, `analysis/power.json`). The population is the old held-out panel's measured Feistel times over the measured lift_scan ratio. The per-point effect spread is the 16 measured lift_scan ratios', with timing noise sigma 0.02 per target and 0.01 per process. For a minimal effect of interest of 1.03, power is 0.81 at 64 points, 0.92 at 128 and 1.00 at 384. The smallest size passing 0.80 after two Monte Carlo SEs is 128. The panel is the design floor of 384, so that the slice bootstrap has six clusters.
- **Runtime estimate.** About 1.0 to 1.6 h including the build, with a 300-minute time guard. A last step runs the profiler on Q0 on the runner (`profile_diagnostic_*.json`), diagnostic only; it never enters the decision.

Local validation (cloud-agent VM; no timing claims)

See `smoke/README.md`.

Files

File	Role
`protocol.json`, `make_protocol.py`, `schedule.json`, `make_schedule.py`	frozen protocol, its builder, frozen run order
`make_combined_source.py`, `make_online_source.py`, `online/`, `lift2/`	combined producer (verbatim derivation, digest-checked) plus the probe-pipeline selector; tuned rho; the two-limb canonicalizer crate
`make_profile_source.py`, `analysis/make_profile_table.py`, `analysis/profile_local.json`, `smoke/profile/`	the diagnostic profiler, the profile table and its raw inputs
`restore.py`, `check_log_table.py`	restore and digest-check crypto 770f6a69 and every local source; re-verify B's factor-log table
`make_targets.py`, `inputs/primary_targets.json`	the new primary panel
`inputs/archived_identities.json`	archived probes, relations and scalars of Q0 and the 16 fresh points (from `claude/n83-combined`)
`power_check.py`, `inputs/power_prior.json`, `analysis/power.json`	power simulation, its prior, its result
`arm.py`, `panels.py`, `run_schedule.py`	one arm per pinned process; panels; the schedule runner
`verify_receipt.py`	gates, statistics, decision rule; `result.json`, `result_table.md`
`make_figures.py`, `figures/`	TikZ sources and renders of the profile and the pipeline diagram

Limits

- The profile is a VM diagnostic. Its component split can differ on the runner (an AMD EPYC in recent runs); the runner's profiler step records the same variants there, still as a diagnostic.
- Tier 1, instance-scoped: one runner, one pinned CPU, not host-isolated.
- `pC` is the combined producer's probe loop compiled into the same binary as `pP`, as a separate monomorphization. This experiment does not re-run the combined experiment's own binary; it compares the two loops on the same points in one job.
- The tuned-rho gap is distance remaining, not a claim to beat rho.
- Next step after this run: the residual lookup cost (TLB and page walks under nested paging, by hypothesis). Candidates are a smaller table slot (16 bytes instead of 32) or a two-level table whose first level stays cache- and TLB-resident.