Native execution report: EXP-ECDLP-4bb0ef

Observations only. Deterministic original worksheet reproduction/calibration; no scientific verdict, independent scientific review, attack claim or execution proof.

Run RUN-ECDLP-25c448; hypothesis H-ECDLP-cba67a; goal GOAL-ECDLP-001.
Raw publication commit 54e9d7aa1987486062c50fcf932eacbc83fd6d8c.

Native status: output_validated. Requested 1, output_validated 1, failed 0, timed out 0. Native elapsed 1.019636 seconds is derived as finished_at minus started_at. Measured manifest interval seconds=0.09927695100031997, child CPU seconds=0.088693, per-process RSS maximum bytes=15859712. Missing measurements are null, never zero. There is one deterministic worksheet, not a sampled inference; no uncertainty interval was recorded.

Execution commit 07c58258c7c354fb70a67809feabb69ef06b520f; recorded dirty state True. Host/platform and Python are retained in report-data.json; detailed CPU model is missing.

Legacy identities EXP-ECDLP-bfbe6f / RUN-ECDLP-8f5190; raw bytes match original archive: True.

Recorded metrics


```
{
  "planted_ok": true,
  "matrix_holds": true,
  "beyond_matrix": false
}
```


Exact supervisor command and resource prefix


```
{
  "supervisor_argv": [
    "python3",
    "tools/experiment_execution.py",
    "run",
    "--plan",
    "experiments/EXP-ECDLP-4bb0ef/trial-plan.json",
    "--owner",
    "executor-ideas-20261018",
    "--epoch",
    "1"
  ],
  "outer_environment_prefix": {},
  "native_launch_argv": [
    "env",
    "GIT_CONFIG_COUNT=1",
    "GIT_CONFIG_KEY_0=core.preloadIndex",
    "GIT_CONFIG_VALUE_0=false",
    "python3",
    "tools/legacy_trial_manifest.py",
    "run",
    "--trial-plan",
    "experiments/EXP-ECDLP-4bb0ef/trial-plan.json",
    "--run-dir",
    "/workspace/crypto-autoresearcher/experiments/EXP-ECDLP-4bb0ef/runs/RUN-ECDLP-25c448"
  ],
  "git_prefix_location": "frozen native trial argv"
}
```


Immutable record path: experiments/EXP-ECDLP-4bb0ef/runs/RUN-ECDLP-25c448. Parameters, controls, null-seed semantics, full environment whitelist and source/input hashes are retained in report-data.json and the sealed run. Missing declared outputs: [].

Failure: None

This reports operational outputs only. Original predictions are historical calibration targets; repeated deterministic bytes are not fresh confirmatory data. Input seed remains null: no new random draw. Any original fixture/seed labels remain untouched. A null curve_id does not certify an exact cross-repository subgroup identity. No discrete-log/decomposition certificate is claimed. The native checker is a source/control check, not independent scientific review. The first run's metadata Git utility failed to create threaded lstat under 256 MiB; its slot remains immutable. The subsequent three used the explicitly authorized process-local Git preload limit shown in command.json, with unchanged source/argv/scientific inputs and supervisor ceiling. This additive replacement prospectively binds that Git-only resource prefix in both frozen trial argv arrays; its outer supervisor command needs no environment override.

Canonical graph scope checked: knowledge/frontiers/ecdlp/ index and the batch's existing source/approval references. No scientific frontier, hypothesis status or isogeny graph was changed by these operational reproductions. A pipeline diagram is used because this experiment has one deterministic fixture, without two comparable experimental arms.



Sources: ../../runs/RUN-ECDLP-25c448/execution-receipt.json, manifest.yaml when present, raw-result.json when present, legacy-execution.json when present; report-data.json and runtime-diagnostic.json. All numbers are recorded measurements unless expressly labeled derived.