Same-map replay profiling

GOAL-ISOU-f30a07 / TASK-20261016-659e0a / archive TASK-20261016-b08ee1

50341 baseline: replay censored at3600019ms

Same sealed map → instrument unchanged stages → controls + clean build

Later frozen /run → durable stage evidence → choose measured optimization

Observed baseline

RUN-ISOU-f9546d constructed one partial-eigenline map in131134ms,7656861bytes. Independent replay reached its3600019ms watchdog with sampled peak153567232bytes, score null and CENSORED/TIMEOUT. Exact total CPU was not recorded. This is a right-censored replay duration, not a point runtime or mathematical rejection. Full raw evidence and the original shell INCOMPLETE fallback are preserved in terminal snapshot9e3309ffdb.

Ranked implementation

Preserve the sealed map and existing acceptance predicates. Parent adds an opt-in absolute fresh JSONL trace with flushed begin/end/error markers, monotonic elapsed time, phase and PID. Stage boundaries cover loading, kernel GCD/torsion, inverse/composition, codomain, denominator equality, numerator-denominator GCD, exact substitution, subgroup order and20 transports. Unfinished stages remain unfinished after watchdog termination.

Controls and gate

Fixed small valid/adversarial maps must have identical trace-off/on mathematical outcomes. Test existing-file refusal, explicit write failure and durable interruption markers. Keep default no-op observers compatible. Required repository checks and clean installed source/binary hashes precede a later separate scientific protocol. No50341 replay, regeneration, larger construction or M8191 execution is authorized by this implementation task.

Limits

The internal bottleneck is unknown; current polynomial code already uses Karatsuba/reciprocal reduction and composition blocking. No speedup ratio follows from a censored baseline. A/A pairing and spread are mandatory for later timing claims. Concurrency1,3600s replay and8GiB sampled RSS are planned host-protection bounds for the later /run, not spending limits. No challenge score or canonical claim graph changes. This pipeline diagram is used because completed comparable replay measurements are unavailable.