Hard norm search and affine-cone checkpoint

Date: 2026-10-17T04:12:29.916547+00:00

The first actual60-second full norm-primary search was inconclusive:0 verified models, no exact norm count, no original-root completion. It made12208 decisions and7317 conflicts. Gaussian reasoning was active with2 initialized matrices, peak7753 rows/20159 columns, and0 row/column cap rejections. Fewer clauses did not establish practical search completion.

The exact affine-cone representation has16133 variables and2879 long-XOR rows, retaining13247 nonlinear AND atoms and174 primary bits. Formal incidence components fit the configured matrix caps, but this is NOT native admission. Longest row4555; total nonzero coefficients1797763. Existing native interface accepts at most3 variables per row and must be replaced and validated before this representation can search.

Original prepropagation incidence was44885 rows/58139 columns; native simplification already produced smaller matrices. Do not attribute the failed search to caps or claim the formal reduction is a measured solver speedup.16384 exhaustive tiny primary assignments preserve every reachable affine form;73216 literal norm checks remain.

Next: long-XOR-capable native interface with frozen source/configuration and full tiny model-set checks; then a distinctly preregistered hard search. Separately test exact S5 representative search with full permutation restoration. Original ghost/exception/auxiliary-fiber closure and matched genuine F4/F5/F6 gate remain required.

Source code is in PR2049. No novel-priority, qualified8x gain or completed original root set is established. Reports remain local because automatic approval review rejected publication without explicit report-payload authorization.