N83 K992 layout control - run record

Four fresh processes on one previously exposed public point

Instance and protocol

Curve: GF(2^83), y^2 + xy = x^3 + x^2 + 1; prime subgroup order 8569786107849059.
Fixed point: research/n83_cold_factor_base_20261016/targets.jsonl.
Arms: K928/root11, K960/root11, K992/root11, K992/root22.
Each process rebuilt the base, dynamic 75%-load root index, and factor-base logs.
Symmetric S3, sparse canonical map, four rank threads, one target thread.
CPU: shared Apple M4 Pro, L0; timing is exploratory, with no isolation gate.

Source and immutable inputs

IC source SHA-256:
8a2fe55dd90dc33892c197d27260182bf783fc8212fb485d8297daf2bbba8e12
Executed binary SHA-256:
d71a9662c9d4e2dde58443bfc646a05737c6b9ca6b3d5e831b632ce09384c906
Exposed point SHA-256:
2c068d2f659588edcdbaa685fc73bb146e2bfee3be123d377d537658f8021c6d

Verification and custody

Independent replay rebuilt every base point and summed each four-point relation.
It checked the recovered scalar and the exclusive target-online phase sum.
All four rows: PASS_INDEPENDENT_ARITHMETIC_REPLAY.
The 28-member raw archive was checked against the versioned manifest.
Raw archive SHA-256:
02993c7b3b7b7bf85af28bf999acfc48b41df2d61afa9408dfde3d9f440d5f55