N83 adjacent-base screen - run record

Three fresh processes on one previously exposed public point

Instance and method

Curve: GF(2^83), y^2 + xy = x^3 + x^2 + 1; prime subgroup order 8569786107849059.
Arms: K984/root11, K1000/root11 and K1016/root11.
Each process rebuilt its base, dynamic 75%-load root index and factor-base logs.
Symmetric S3, sparse canonical map, four rank threads, one target thread.
CPU: shared Apple M4 Pro, L0 exploratory; one previously exposed public point.

Frozen source and input hashes

IC source SHA-256:
8a2fe55dd90dc33892c197d27260182bf783fc8212fb485d8297daf2bbba8e12
Executed binary SHA-256:
d71a9662c9d4e2dde58443bfc646a05737c6b9ca6b3d5e831b632ce09384c906
Exposed point SHA-256:
2c068d2f659588edcdbaa685fc73bb146e2bfee3be123d377d537658f8021c6d

Replay and archive

All three full solves reached rank K and recovered the fixed scalar.
Independent replay rebuilt every base and summed every four-point relation.
It checked scalar replay and the exclusive target-online phase sums.
All rows: PASS_INDEPENDENT_ARITHMETIC_REPLAY.
The 23-member raw archive matched its versioned file manifest.
Raw archive SHA-256:
1ebe3cc221b03ce2003078806f4dc2d8fc6f8c26a7976b4368386f62daced5c3