Run report: ic_semiregular_law_20261005, round 1

Observations only. Interpretation is in `RESULTS.md` of the same study.

What ran

- **Command:** `lanes.sh` (study directory), which runs `examples/macaulay_dense.rs` once per (cell, draw, arm, degree D), scanning D = 1, 2, … to the registered cap d_reg + 2 and stopping at the first refuting D.
- **Registration:** commit `1c1092005` (PREREGISTRATION.md, predictions.jsonl, dump.sha256), before any registered draw ran.
- **Systems:** exported by `examples/rr_degree_ladder.rs --dump-dir`, seed 20261005, four rootless draws per cell; hashes in `runs/registered/dump.sha256`.
- **Hosts:** this container (2 lanes × 2 threads, 4 cores, 16 GB), 2026-10-05 16:58Z to 2026-10-11 23:27Z, with one restart; three remote 4-core hosts (lanes c, d, e). Isolation: none beyond one process per lane; degrees are deterministic, wall times advisory.
- **Budget per process:** 86,400 CPU-s, 13.5 GB address space; the engine refuses a basis above 12 GB.

Runs requested and completed

- 68 units registered (17 cell-arm pairs × 4 draws); 68 resolved, none censored, none killed or refused.
- Remote lanes a, b and f stopped at the account's weekly usage limit before measuring past D = 8. Their six units were re-run from D = 1 locally. Lane b's partial log is kept in `runs/registered-remote-b` and not read.
- Excluded by registration: cell K1n61l4 (seen in a smoke test); `x4` on K1n23l6 (not run, as registered).

Measured refutation degrees (one reading per draw)

`triv` marks a draw whose system contains the constant 1 (refutes at D = 1). Window = registered `[d_reg, d_reg + 1]`; fit = the fixed-ℓ value.

cell	arm	readings	window	fit	in window
K0n61l4	rr	5 5 5 5	(5, 6)	6	yes
K0n61l4	x4	8 8 8 8	(8, 9)	9	yes
K0n61l6	rr	6 6 6 6	(6, 7)	8	yes
K0n61l6	x4	10 10 10 10	(9, 10)	11	yes
K1n23l5	rr	7 7 triv 7	(7, 8)	8	yes
K1n23l5	x4	10 10 10 10	(9, 10)	10	yes
K1n23l6	rr	8 8 8 8	(7, 8)	8	yes
K1n29l5	rr	6 6 6 7	(6, 7)	8	yes
K1n29l5	x4	10 10 10 10	(9, 10)	10	yes
K1n45l5	rr	6 6 6 6	(6, 7)	8	yes
K1n45l5	x4	9 9 9 9	(9, 10)	10	yes
K1n59l6	rr	6 6 6 6	(7, 8)	8	below
K1n59l6	x4	10 10 10 10	(10, 11)	11	yes
K1n61l5	rr	5 5 5 5	(6, 7)	8	below
K1n61l5	x4	9 9 9 9	(9, 10)	10	yes
K1n61l6	rr	6 6 6 6	(6, 7)	8	yes
K1n61l6	x4	10 10 10 10	(9, 10)	11	yes

Resolved draws: 68. Inside the window: 60. Below: 8. Above: 0.



Figure 1: Recorded refutation degree for every resolved draw (dots), one column per cell, with each cell's registered window (shaded band) and the fixed-ℓ fit (dashed). Run ic_semiregular_law_20261005 round 1; 4 draws per cell; values from `runs/registered*/K*.jsonl`. Trace-constant draws and the excluded cell are omitted.

Raw records

- `runs/registered/K*.jsonl`, `*.stderr`, `progress.txt` (local lanes)
- `runs/registered-remote-c`, `-d`, `-e` (remote lanes, with `HOST.txt`)
- `runs/registered/readout.md` (printed by `analyze.py`)
- `runs/registered/topforms.jsonl` (post-hoc diagnostic; not part of the registered readout)