N83 prebuilt factor-base result

Protocol: `PROTOCOL.md`, frozen at commit `2d3a7f3723925311e74a29ff1cdc7c74a0a97f50`
Curve: `icv1-f2m83-tm6151469093347-debefd74` primary; the degree-83 `a=1` curve is a separate diagnostic.
Host: shared macOS arm64, L0, 2026-10-16.

N83 retained factor-base panel: three local repetitions
Seconds, local L0 host; each panel contains 54 compressed objects (83,328,324 bytes).

Interval	0 → 180 s; bar length = 0.52 mm/s	Seconds
Build 1		59.518
Build 2		74.022
Build 3		169.555
Replay 1		46.66
Replay 2		52.15
Replay 3		31.43

Blue: native construction + compression + object writes (internal interval).
Green: separate full generic arithmetic replay of a saved manifest against byte-identical reconstructed objects (outer interval).
All six producer/replay data rows completed; the original `/usr/bin/time -l` wrapper failed after each build because sandboxed `sysctl kern.clockrate` was unavailable. Build and replay perform different work; no speed ratio is inferred.

Run ID: `run-20261016T2352Z`
Source: `runs/run-{1,2,3}/manifest.json` and `replay-recovery.stderr`.

Three fresh native builds each completed all 54 declared objects. Each panel contains 83,328,324 compressed bytes. The canonical listing of point sets, plain bytes and compressed bytes is identical across the three builds, one later reconstruction and the historical content-addressed S3 panel. Its SHA-256 is `e0079cf8ad843084243a1319de1aefa7ccf65ed1f71a92aaddd588761e514e3d`.

Panel	Build, internal s	Outer real s	Generic replay s
1	59.518	60.07	46.66
2	74.022	74.73	52.15
3	169.555	172.78	31.43

The three generic multi-limb replays passed 54 checks each, using the original manifests and byte-identical reconstructed objects. The first three replay attempts failed because temporary object paths had been cleared; those failure receipts remain in `runs/`. The timing wrapper exited 1 after each completed build because sandboxed `sysctl kern.clockrate` was unavailable; peak RSS is missing. The 2.85-fold build interval spread prevents an isolated wall-performance inference. Build and replay perform different work and their times are not a speed ratio.

For the primary K=600 orbit base, the exact multiset counting ceilings for a uniform nonidentity subgroup target are 2.051462e-15, 6.810989e-11 and 1.695987e-6 at two, three and four summands. They bound one-query full-smooth probability under that model; actual relation yield and useful rank remain unmeasured. The stored dimension-12 structured base has 2,001 signed-Frobenius columns and an exact four-summand count/order ratio of 0.000209791390, also a ceiling rather than measured yield.

Decision: Ahead-of-time construction and checked reuse are demonstrated at the factor-base stage. Selecting the best symmetric base at two to four summands requires a matched natural-query oracle and rank comparison of the near-size-matched K=2,048 explicit-orbit and 2,001-column structured bases, followed by complete cold accounting and controls. See `RESULT.md`, `REVIEW.md`, `VALIDATION.md`, `runs/` and `problems/n83-prebuilt-base-quality-m2-m4.md`. No canonical performance graph changes: there is no admitted end-to-end improvement measurement.