

Degree-83 Koblitz factor-base sweep

Design, replayed artifacts and bounded pilot evidence

Public known-answer research

October 9, 2026

Objective. Find the factor base and solver configuration with the lowest fully charged index-calculus runtime for one public target. This report distinguishes design coverage, artifact correctness and complete-pipeline performance. A runtime winner requires complete, comparable, verified measurements.

Exact instances

The primary curve is $y^2 + xy = x^3 + 1$ over $\mathbf{F}_{2^{83}}$, using $z^{83} + z^{45} + z^2 + z + 1$. Its subgroup order is 2417851639230796216685689, with cofactor 4.

Primary model: `icv1-f2m83-tm6151469093347-debefd74`

The diagnostic $a = 1$ curve has subgroup order 8569786107849059 and cofactor 1128547018.

Diagnostic model: `icv1-f2m83-t6151469093347-cdcc5432`


Both generators and exact encodings are pinned in the exporter and every artifact header. The 81-bit and 53-bit subgroups are separate workloads.

Finite exhaustive coverage

The declared design contains 1,050 base specifications and 43,200 solver tuples per base: **45,360,000 configurations**. Every tuple has a mixed-radix ordinal and one compatibility disposition. Counts sum to the full population, including resource-gated and unimplemented cases. This establishes coverage of the finite design; execution coverage is reported separately. Every other factor base, parameter value, field representation, solver version and heuristic remains outside it.

Choice	Declared levels
Base policies	Sequential, hash-derived and Gray-prefix public x; polynomial, random linear and affine subspaces; 2- and 4-torsion coordinates; Frobenius-invariant module blocks
Orbit columns	32, 64, 128, 256, 600, 900
Subspace dimension	4, 8, 12, 16, 20, 28, 41, 82; invariant-block dimensions 1, 82, 83
Closures and seeds	None, sign, signed Frobenius; three frozen public seeds where applicable
Summands and splitting	2–6 summands; 0, 4, 8, 12 split bits
Symmetry	None, summand ordering, signed Frobenius, rational 2-torsion, rational 4-torsion
Backends	Compact S3 four-sum, MITM, F4, SAT-CDCL, WDSat, Gray FES, Moe-bius FES, Monica FES
Other axes	Binary/Gray order; zero/one/two large primes; 1/4/12 threads; dense or sparse single-word, or BigUint modular LA

Evidence path



The construction and replay path supplies exact factor-base artifacts. It does not supply natural relation yield, full rank, an individual logarithm or a total-time winner.

Structural gate

Native modular computation gives $\text{ord}_{83}(2) = 82$. The nontrivial cyclotomic block in $X^{83} - 1$ is irreducible over $\mathbf{F}_2$. Invariant linear-subspace dimensions are 0, 1, 82 and 83; the small rational-torsion component vanishes under primary cofactor clearing. General subspaces and compact unions of point orbits remain distinct alternatives. A small orbit base is not an invariant linear subspace. The pinned field modulus is checked with the prime-degree irreducibility criterion, using generic polynomial arithmetic.

Accounting and acceptance


Cold cost includes curve and base construction, orbit/index setup, relation generation and encoding, every failed attempt, solving and lifting, partial-relation processing, linear algebra, individual logarithm, verification and artifact I/O. Record exclusive intervals and the calibrated operation unit. A missing phase makes the total unknown. Retain timeouts, OOMs, UNKNOWN outcomes and censored completions; none is a win.

The requested runtime comparison needs identical one-target workloads, frozen resource envelopes, A/A controls, at least five interleaved paired rounds, disjoint tuning/holdout targets and a paired 95% interval outside the admitted noise floor. Use an L2-capable host for wall-time claims. The local Apple M4 Pro host has 14 logical CPUs and 48 GiB of memory, but macOS provides L0 measurement isolation here. Its elapsed construction values are descriptive only. Counted candidates, exact point sets and verification predicates remain valid evidence.

Pilot population and storage

The authorized active-process pilot is capped at 3,600 seconds and crosses two curve arms, three public-x policies, three seeds and $K = 64, 256, 600$. All 54 planned bases were constructed. Every complete signed-Frobenius base has $166K$ distinct subgroup points, checked individually by replay. The panel contains 2,748,960 point records, 16,560 orbit-column records and 83,328,324 compressed bytes. Its 54 variants represent 42 distinct point sets; 12 diagnostic sequential/Gray variants duplicate a set exactly. These are artifact counts, not independent experiments.

Orbit columns K	Points per base	Bases at this size in full panel
64	10,624	18
256	42,496	18
600	99,600	18



Full JSONL point sets are gzip-compressed and named by BLAKE3 of the exact compressed bytes, with a separate uncompressed hash and a sorted point-set hash for duplicate detection. The destination is `s3://crypto-autoresearcher/factor-bases/icv1/etc/` followed by the study, curve arm and content-addressed object path. The uploader requires a matching replay, validates local content, uploads only to this prefix, downloads every object and checks its hash. Manifests and receipts have a separate content-addressed panel path. Generic-versus-wide replay is on the same host and repository; independent-host review remains an additional obligation.

Replay verified 54 bases, 2,748,960 points and 16,560 representatives; S3 matched all 54 objects. Over 1,728 dependent probes, 87,966,720 two-summand lookups found zero relations. Higher-arity yield, rank and full runtime remain unknown.

The separate 53-bit diagnostic arm has three capped cold checks: ordered-pair $K = 256$ consumed 606.68 seconds of process wall, ordered-pair $K = 64$ consumed 601.32 seconds, and exploratory unordered-pair $K = 64$ consumed 600.59 seconds. Each reached its 600-second solver cap with `UNKNOWN_budget`; none yielded a completed rank and target record. The unordered $K = 64$ index itself completed in 0.771 seconds with 172,640 regular states and 339,776 root-table entries. The ordered runs lack matching phase checkpoints, so the index observation cannot establish a speedup. The recorded construction, replay, probe, upload and cold stages used about 3,530.85 seconds of active execution within the 3,600-second local pilot allowance. The first stage uses an internal timer; the others use process wall. The 81-bit primary arm has no complete cold measurement.

An exact multiset screen gives uniform-target full-smooth hit ceilings for primary $a = 0$, $K = 600$ of 1.70×10^{-6} at four summands and 0.0338 at five; at six the bound is vacuous. These are neither fixed-fixture yields nor runtime predictions. Exact fractions and the proof are in `SUPPORT_MOMENTS.md`.

Prior art and open implementation gates

The repository has divisor and explicit-orbit bases, torsion-symmetrized systems, F4 splitting, WDSat ANF/capacity tooling, derivative Gray FES, exact single/double-large-prime machinery and the native ecbench accounting harness. Their interfaces have different field, equation and subgroup capacities. The degree-83 primary subgroup exceeds a single word, and the current large-prime field/point adapter is also single-word. FES equation representation and complete verification must cover the full original system; higher-arity chains are not automatically quadratic. WDSat needs sealed source ANF and binary/configuration capacities. Symmetry must preserve the actual domain. Torsion conditions need verification for each coordinate construction.

Cofactor clearing moves x-coordinates outside an input subspace in general. A raw-subspace oracle therefore needs an explicit cofactor-aware lifting and relation equation, including any torsion residue; it cannot simply treat the projected coordinates as unchanged subspace variables. Partial relations must preserve exact modular signs and Frobenius coefficients and be group-checked before cycle filtering. Count graph growth, duplicates, singleton vertices, cycle lengths, matrix density and rank gain, including unsuccessful work.

Historical degree-83 $a = 1$ compact-orbit results measured online work after reusable setup. They use a smaller subgroup and a recorded alternative field representation. They do not establish the requested primary cold-cost optimum. Source and historical evidence are pinned in `PRIOR_ART.md`. The initial inspected main revision failed before the exporter compiled; the recorded earlier library revision is used for local verification. All actual build and test outcomes, including failures, are retained in `verification/`.

Primary literature

- Galbraith, Granger, Merz and Petit, [On Index Calculus Algorithms for Subfield Curves](#): invariant factor-base domains and Frobenius symmetry.
- Trimoska, Ionica and Dequen, [Parity \(XOR\) Reasoning for the Index Calculus Attack](#): ANF-aware WDSat and branching preprocessing.
- Bouillaguet et al., [Fast Exhaustive Search for Quadratic Systems in F2 on FPGAs](#): derivative Gray enumeration, with explicit equation and hardware assumptions.
- [Index calculus with double large prime variation for curves of small genus with cyclic class group](#): class-group large-prime variation, with transfer to the exact elliptic point representation still an obligation.