An encyclopedia of the factor bases we have tried

Date: 2026-10-15. **Scope:** every factor-base construction for elliptic-curve and Jacobian index calculus that this repository (`aburan28/crypto`, at `a80b15bbc`) or the research program (`aburan28/crypto-autoresearcher`, at `4446b91c2f`) has designed, built, measured or closed on paper. The two sibling repositories `aburan28/cryptanalysis` and `aburan28/ml-cryptanalysis` are included where they hold a family that is not mirrored here. **Kind of document:** a search round over code, notes and records (AGENTS.md "Research searches must leave visual reports"). It compiles results that are already recorded and runs nothing new. Every number below is quoted from the file cited next to it. Numbers marked derived here are this note's own arithmetic on quoted numbers, and the working is shown. **Report PDF:** `REPORT.pdf`, built from this file. **Figures:** `figures/taxonomy.svg` and `figures/cost_vs_rho.svg` map the families; `figures/pkm_solving_degree.svg` plots the two flagship families. The data is in `figures/data.json` and the drawing code in `figures/plot.py`.

Path conventions:

- a bare path is in `aburan28/crypto`;
- `AR:` marks `aburan28/crypto-autoresearcher`;
- `CA:` marks `aburan28/cryptanalysis`;
- `ML:` marks `aburan28/ml-cryptanalysis`.

`S` is the repository's cost unit: group-addition equivalents divided by `√r`. Rho's `S` is about 1.25–1.3 without the negation map and 0.886 with it. "× rho" always means the ratio the cited source recorded against its own matched rho arm. These ratios come from different curve sizes and different accounting, so two rows are not comparable unless the text says they are.

---

0. The two flagship families, and what was actually run on them

The prime-field factor bases that matter most for deployed curves are Petit, Kosters and Messeng's tower bases (PKC 2016). Their factor base is

```
F = { P ∈ E(F_p) : x(P) ∈ V },   V = L⁻¹(c),   L = L_t ∘ … ∘ L_1,
```

where each `L_j` has low degree and the preimage tree of `L` splits completely over `F_p`. Then `|V| = 2^t` (for degree-2 steps). Membership of `x` in `V` is written as `t` low-degree equations in auxiliary variables `y_0 = x, y_1, …, y_{t−1}`:

```
T_j : y_{j+1} − L_{j+1}(y_j) = 0        (0 ≤ j < t−1)
T_t : L_t(y_{t−1}) − c = 0
```

so no membership equation has degree above 2, even though V has 2^t elements. This is the prime-field stand-in for the F_2-subspace of binary Weil descent. The repository's design is in RESEARCH_PKM_TOWER_ORACLE.md (the PKM note), §2.1, lines 205–254, fixed in commit c2157282 before any run.

Two of its tower kinds correspond to the two factor-base shapes PKM's slides attach to NIST curves:

	0.1 Kummer: a coset of a smooth subgroup of F_p^×	**0.2 Isogeny: x-coordinates from an isogeny chain on an auxiliary curve**
NIST curve it fits	**P-224**: p − 1 = 2^96·(2^128 − 1), so $v_2(p-1) = 96$	**P-192**: $v_2(p-1) = 1$, so no Kummer tower exists; $v_2(p+1) = 64$
V	g· μ_{2^t}, the coset of the 2^t-th roots of unity through g	x(R' + ⟨Q⟩) for a point Q of order 2^t on an auxiliary curve E'/F_p
step map	$y \mapsto y^2$, with y_0 = x/g and $y_{t-1}^2 = 1$	the x-map of a 2-isogeny (Vélu): $y_{j+1}(y_j - \xi_j) = y_j^2 - \xi_j y_j + \tau_j$
existence	2^t | p − 1	none on p: E' is searched for
build cost	one exponentiation for ζ, then 2^t multiplications	an auxiliary-curve search, about 2^t point counts, charged to the factor-base phase
implementation	prime-kummer:t=T[,g=G] in src/cryptanalysis/ic_framework/prime_tower.rs (an ic.pipeline plug-in), and examples/pkm_tower_pilot.rs	examples/pkm_tower_pilot.rs only (lines 497–590); no plug-in
largest instance run	t = 11 (N = m·t ≤ 22) at p_1 = 2013265921	t = 10 (N ≤ 20) at p_0 = 786433
run at NIST size?	**No**	**No**

Neither family has been run on a NIST prime. Every tower run used a generated prime of 20–32 bits. The NIST primes enter only through the 2-adic

valuation table of the PKM note §10.10 (lines 1142–1162), which the note calls "properties of the primes, not measurements", and through PKM's own slide remark, quoted in research/pdp_root_finder_requirements_20261012/README.md lines 104–119: "NIST P-224 has p − 1 = 2^{96}·N'". The code cannot hold a NIST prime either. prime_tower.rs works in u64, and primitive_two_power_root refuses t ≥ 63 (lines 27–36). The pilot counts points naively in O(p). The autoresearcher ledger has no P-224 coset base and no P-192 isogeny-chain base. Its only P-192 factor-base object is a class-group base, entry E3 below.

0.1 Kummer tower: g·μ_{2^t} (the P-224 shape)

Definition. Fix t with 2^t | p − 1, a primitive 2^t-th root of unity ζ, and g ∈ F_p^×. Then V = g·μ_{2^t} = {g·ζ^k : 0 ≤ k < 2^t}, and F = {P ∈ E(F_p) : x(P) ∈ V}. About half of V lifts to points, and both signs are kept. The tower is y_0 = x/g, y_{j+1} = y_j², and y_{t−1}² = 1.

Algebra (PKM note §2.4, Lemma 1, lines 296–319). The tower equations are a Gröbner basis with square-free standard monomials, and the quotient ring is R = F_p[y]/(towers) ≅ F_p^{V^m}. For Kummer, R is the group algebra F_p[(Z/2^t)^m], and x_i^e = g^e·∏_{j ∈ bits(e)} y_{i,j}.

What theory predicted (§3.2–3.4, lines 336–418).

- A PKM system has the field-equation half of Weil descent, a finite quotient with a square-free monomial basis. It lacks the conjugate-equation half, which needs a Galois group that F_p does not have. So it is a one-generator system over a 2^N-point quotient, N = m·t ≈ log₂ r.
- Proposition 2: the XL (Macaulay) solving degree is at least d + δ, where δ is generically about N.
- Kummer and Dickson towers are degenerate at infinity, with Bardet–Faugère–Salvy degree of regularity N + 1. Isogeny towers are not.
- §3.7, the linear-algebra floor: the optimum costs about r^{2/(m+1)}, so m ≤ 3 can never beat rho. m = 4 gives r^{2/5} and m = 5 gives r^{1/3}, so "the decisive Stage A cells are m ≥ 4".

The pre-registered prediction failed in the bounded direction at first. F4's solving degree D did not grow like N. Later rounds showed it is not bounded either. The f4_fp_tower results, all Kummer at p₁ = 15·2^27 + 1, are consolidated from research/pdp_root_finder_requirements_20261012/README.md lines 238–255:

m	N	D	width (columns)	F4 multiply-adds	peak memory	F4 time
2	12	5	1,231	6.50e7	8 MB	0.05 s

2	16	5	4,789	6.18e9	36 MB	1.1 s
2	18	5	8,644	4.60e10	91 MB	6 s
2	20	**6**	33,446	4.84e11	473 MB	57 s
2	22	6	51,909	—	2.3 GB	10 min
3	9	6	1,186	1.59e8	11 MB	0.1 s
3	12	6	5,019	1.06e10	64 MB	2.0 s
3	15	**7**	31,397	3.19e12	1.1 GB	6.0 min
3	18	7	106,288	8.99e13	12.7 GB	176 min
4	8	6	1,049	4.84e7	9 MB	0.1 s
4	12	**7**	9,452	8.55e10	171 MB	9.4 s
4	16	7	76,837	2.7e13	8.1 GB	55.5 min

The rounds and controls behind that table:

- **Pilot, §10.2** (2026-09-24, $p_0 = 786433 = 3 \cdot 2^{18} + 1$). $m = 2$, $N = 2 \ldots 18$ gives $D = 4,4,4,4,4,5,5,5,5$.
  - The `naive` presentation, one dense degree-2^t membership polynomial, gives exactly $D = 2^t + 2$: 66 against 5 at $N = 12$. The tower presentation is what keeps the degree low.
  - A shape-matched **null** tower gives the same D, width and steps, so the low degree comes from the tower algebra and its monomial support, not from the curve.
  - `dickson` gives the same D, width and step count as `kummer` at every N. It is the same F4 computation on different numbers, so it is not an independent replication.
- **Round 2, §11** (2026-09-25): D rises to 6 at $N = 20, 22$ for $m = 2$, in the Kummer and the isogeny family and in the null. This refuted the pilot's Conjecture 3 ($D \le 5$ for all t).
- **Round 3, §12**: $m = 4$, $N = 16$ gives $D = 7$ on both targets in 55 minutes and 8.1 GB. From $N = 12$ to $N = 16$, the width grew ×8.1 and the multiply-adds ×316.
- **Round 4, §13**: a signature engine (F5/GVW, `sig_fp_tower`) needs rows 1–2 degrees higher than F4 on 18 of 18 systems, so F4 stays the instrument.
- **Round 6, §15**: an early exit cuts 39% of the multiply-adds at $m = 4$, $N = 12$. This is engineering.
- **Round 7, §16** (2026-10-06): $m = 3$, $N = 18$ gives $D = 7$, so the $m = 3$ line reads 6, 6, 7, 7. $N = 21$ needs more than this host's 14 GB.

Pre-registered reading (rule A1, lines 1506–1513 and 3169–3171):

cell	D sequence	reading
m = 2	5 5 5 5 6 6	"H0, at the threshold"
m = 3	6 6 7 7	inconclusive
m = 4	6 7 7	inconclusive

log₂(multiply-adds) grows 1.6, 2.1 and 2.4 bits per tower variable at m = 2, 3, 4, where plain enumeration grows 0.50, 0.67 and 0.75: "F4 grows three to seven times faster than plain enumeration" (requirements README lines 260–266).

What a deployed size would require. The requirements README §6.4 (lines 420–438) works this out for a 256-bit p at m = 4: t = 64, N = 256, T_dec ≲ p^{1/4}/32 ≈ 2^59. "Admissible degree: 3 at m = 4, 4–5 at m = 5; measured: 7 at m = 4, N ≤ 16, rising." Derived here: for P-224 at m = 4, the same sizing gives t ≈ 56 (N ≈ 224). That is well inside v₂(p − 1) = 96, but 52 levels past the largest t = 4 measured at m = 4.

End to end in ecbench (research/pkm_tower_ecbench_20261013/README.md). The prime-kummer:t=8…11 base was run on five curves of 20–28 bits with 2-adicity 12, with every group operation charged. 896 runs, all verified.

bits	rootfind ÷ rho (S, 95% CI)	tower ÷ plain base of equal size
20	34.0 [27.9, 42.6]	1.006 [0.982, 1.032]
22	41.9 [34.3, 53.4]	1.001 [0.996, 1.006]
24	29.4 [23.7, 37.3]	1.012 [0.989, 1.035]
26	96.6 [77.8, 124.1]	1.005 [0.994, 1.020]
28	140.6 [113.0, 182.3]	0.999 [0.994, 1.004]

"PKM's structure helps an algebraic solver, not a table." The ratio grows 0.26 ± 0.28 bits per bit of r. Class: engineering.

Related falsifier and root-finding results.

- **C4 falsifier** (research/ic_exponent_falsifiers_20261013/README.md): is e_a + e_b + e_c mod 2^k biased on the t = 8 base at p = 946177? It is not. The largest class share is 0.680, 0.508, 0.393 … against 0.680, 0.511, 0.396 … for the null, while the positive control reads 1.000. "C4's simplest form is falsified on this base."
- **Root-finding oracles on the same cells** (research/pdp_root_finder_20261012/README.md): they were exact on 707 of 707 brute-force checks, with $4.6 \cdot 10^{11}\times$

less counted work than F4 at `m = 3`, `N = 18`. Their slopes sit on the pair-table and enumeration floors. Class: engineering.

Autoresearcher siblings.

- Engine sweep (`AR:src/crypto_autoresearcher/index_calculus/README.md`). It uses a high-degree, non-tower `subgroup` base (`x ∈ g·μ_d`, entry A4b) and measures exponent 0.97 [0.95, 0.99] at `m = 2`, the same as `small_x`.
- Twisted group algebra (`AR:IDEA-20260808-9ef88c`, proposed). Its Stage-0 analysis predicts solving degree `B − 1` for the binomial membership `x^B − c^B`, and a cost `Õ(B^m)`, "still worse than MITM at theta = ceil(m/2)".

Status. Open, and inconclusive on the solver axis: at `m ≥ 4` there is no data past `N = 16`. End to end it is engineering: a tower base costs the same as a plain base in a table oracle. It is not run at P-224 size.

0.2 Isogeny tower: `x(R' + ⟨Q⟩)` on an auxiliary curve (the P-192 shape) **Definition** (PKM note lines 222, 233–242).

- Search auxiliary curves `E'_0 = E'/F_p` until one has a rational point `Q_0` of order `2^t`, and pick `R' ∈ E'(F_p)` with `2R' ∉ ⟨Q⟩`.
- For `j = 0…t−1`, take the kernel point `K_j = 2^{t−1−j}·Q_j`, with `ξ_j = x(K_j)` and `τ_j = 3ξ_j² + a'_j`.
- The Vélu step is `x ↦ x + τ_j/(x − ξ_j)`, onto the codomain `a'_{j+1} = a'_j − 5τ_j`, `b'_{j+1} = b'_j − 7ξ_jτ_j`.
- With `c = x(Φ(R'))`, the equation `L(x) = c` has exactly the `2^t` rational roots `x(R' + ⟨Q⟩)`, and `V` is that set.
- Mixed radix (`degrees=2,2,3`) is a parameter.

Why it is the generic family. It places no condition on `p`. So on P-192 (`v₂(p − 1) = 1`) it is the route that remains. A Dickson torus tower (`2^t | p + 1`, `t ≤ 64`) would also exist there, but the torus case was never measured at a P-192-like prime (§10.10). The PKM note §4.5 (lines 600–603) makes this the only family that can support a statement about generic primes: "Conclusions about generic primes come only from `kind = isogeny`." It is also the one tower that is not degenerate at infinity (§3.4).

Measured (only at `p₀ = 786433`, `t ≤ 10`). The pilot, round 2 and the A1 table give these values of `D`:

m	N	isogeny D	width	Kummer D at the same N

2	2…18 (pilot, `f4_fp`)	4,5,5,5,5,5,5,5,5	9 … 17,754	4,4,4,4,4,5,5,5,5
2	2…20 (round 2, raw presentation)	3 5 5 5 5 5 5 5 5 6	35,158 at `N = 20`	3 4 4 4 4 5 5 5 5 6
3	6, 9, 12	6, 6, 6	399; 3,543; 13,249	5, 6, 6
4	8, 12	6, 7	1,897; 21,841	6, 7

- "It rises at the same level as Kummer's, `t = 10`" (line 1423). The A1 reading for the isogeny `m = 2` cell is inconclusive (line 1511).
- Generator-count ladder at `N = 12` (instrument power): isogeny `D` = 5, 5, 5, 5, 4 for `g = 1, 2, 4, 8, 12`. The instrument registers a fall, but the isogeny system resists adding generators longer than Kummer does.

The auxiliary-curve search. These counts are the `aux_curves_tried` field of `research/pkm_tower_pilot_20260924/runs/*.jsonl` (naive `O(p)` counting at p_0):

`t`	1	2	3	4	5	6	7	8	9	10
curves tried	1	3–4	1–5	8–54	88	3–142	196	404	584	425

The `E'` found had order 786,688 at `t = 8` and 787,456 at `t = 10`. The pilot reported this search but did not charge it. The design rule (§2.1, §5.4) lists "charging the auxiliary-curve search as free" as inadmissible, so any priced run must add it.

Derived here: at P-192 size with `m = 4`, `t ≈ 48`, so the note's own estimate (line 246) is about `2^48` SEA point counts per factor base. PKM's cheaper alternative builds `E'` by CM through $x^2 - Dy^2 = 4N$ (requirements README lines 110–119). It was not implemented.

Status. Open on the solver axis, and measured only at a 20-bit prime. It is not wired into `ic_framework` or ecbench, never priced end to end, and not run at P-192 size. The autoresearcher program cites the construction (`AR:KN-LIT-025`) but never built it: `AR:H-RELN-96e3ba` calls the PKM arm "unmaterialised".

---


1. How each entry reads

Each entry gives as many of these fields as the record supports:

- **Definition**: the set `V` of abscissae, or the set of points.
- **Existence**: conditions on `p`, `n` or the curve.

- **Build**: how the base is constructed, what it costs, and whether that cost is charged.
- **Fold**: the symmetry quotiented out (negation, Frobenius, automorphisms, 2-torsion).
- **Oracle**: the decomposition oracle or solver paired with the base.
- **Measured**: the results, with the sizes they were measured at.
- **Verdict**: the recorded class or decision (refuted, rejected_scoped, weakened, inconclusive, engineering, accounting, open), with the mechanism when the source names one.
- **Sources**: where the record lives.

Families are grouped by field regime: §2 prime fields, §3 odd-characteristic extension fields, §4 binary fields, §5 Koblitz curves, §6 Jacobians and covers. §7 collects the results that bound every family at once, and §8 lists the open lines.



2. Prime fields $E(F_p)$

A1. Small abscissae / x-interval (Semaev's prime-field base): the baseline

- **Definition.** $F = \{P : x(P) < B\}$, both signs, one column per abscissa. $|F|$ is about $\#E^{1/3}$ for $m = 3$.
  - The membership polynomial $\prod(x - x_j)$ is dense, of degree $|F|$.
  - Variants: a stride-s scan, a centred interval, the high-bit window $[p - W, p)$ (AR:H018), and an offset interval.
- **Build.** One Legendre symbol and one square root per abscissa, charged.
  - Plug-in: `prime-abscissa:size=N[,stride=s]` (src/cryptanalysis/ic_framework/plugins.rs L71–133).
  - In the autoresearcher engine: `small_x` (AR:src/crypto_autoresearcher/index_calculus/factor_base.py).
- **Oracles.** Semaev S_3 roots, `subtract`, `mitm` ($m = 2, 3$), `mitm-prime-batch`, `rootfind-*`, S_4 with Cantor–Zassenhaus, Gröbner/msolve, crossbred.
- **Measured.**
  - Boundary ledger §2 (research/notes/index-calculus/RESEARCH_IC_BOUNDARY_LEDGER.md), eight sizes from $2^{9.7}$ to $2^{23.4}$. At $r = 2^{23.4}$, $|F| = 512$: S_3 roots 1,107× rho, subtraction 436×, mitm $m = 2$ 59.1×, mitm $m = 3$ 14.5×. The fitted exponents are 0.905, 0.850, 0.662 and 0.601, against rho's 0.274. Yield over ceiling is 0.75–1.25: the base "behaves like a random set of its size".
  - Deployed shape ($a = -3$, prime order; RESEARCH_ECC2K130_IC_FEASIBILITY.md §5): IC/rho is 19× at 16 bits, 114–199× at 20 bits and 233–403× at 24 bits.
  - AR:EXP-ALPF-022 ($m = 3$): IC/rho is 478.63, 531.07, 1211.60 and 2109.18 at 12, 14, 16 and 18 bits, with fit $\log_2(IC/rho) \approx 0.368 \cdot \log_2 n + 4.42$. Verdict: NEGATIVE (scoped).
  - AR:EXP-ALPF-032: a verified end-to-end solve. The decomposition exponent is 0.889, and the linear algebra alone costs $n^{2/m}$, more than $\sqrt{n}$ at $m = 3$, "even with a free decomposition oracle".
  - AR engine sweep, 12–32 bits:
    - exhaustive IC is about $N^{1.0}$, against rho's 0.50 [0.48, 0.52];
    - MITM $m = 3$ gives 0.67 and $m = 7$ gives 0.58;
    - at 32 bits, $m = 3$ MITM is 34× rho;
    - msolve per target grows as $|F|^{3.80}$ ($m = 2$) and $|F|^{4.41}$ ($m = 3$).
  - ecbench L0 smoke, 20-bit prime, `prime-abscissa:size=32`: $S = 11.329$ (12.3× the negation rho; "not a performance claim"; research/ecbench_factor_bases_20261013/RESULTS.md).

- Small-root route (RESEARCH_PRIME_FIELD_BREAKTHROUGH_PROGRAM.md §2–3):
  - with $x \le p^{\delta}$, a decomposition needs $\delta \ge 1/(2(m-1))$;
  - the Coppersmith reach is $1/(m(m+1)\cdot 2^{m-2})$: 1/6, 1/24 and 1/80 for S_3, S_4 and S_5;
  - $m = 4$ needs about $\delta \approx 1/5$, against a reach of 1/80.
- **Verdict.** Refuted as a route past rho.
  - The pair-table family law (§7) is $S = 0.75\cdot r^{1/6}$.
  - AR:KR-IC-5931ee: "Naive Semaev index calculus over prime fields cannot beat generic methods".
  - This base is the control every other prime-field entry is compared with.

A2. Geometry family at matched size (AR:H-FB3-001, six geometries plus two priors)

- **Definitions** (AR:experiments/EXP-FB3-001/amendment-001.yaml).
  - high_bit_interval: the top window of F_p.
  - small_height: the smallest $\max(|u|,|v|)$ with $x = u/v \bmod p$.
  - mixed_two_base: an interval plus small multiples, with typed decompositions.
  - coset_union: "Choose the largest divisor d of $p - 1$ with $d \le B$, let H be the subgroup of order d in F_p^*, and take the union of cosets $g^i\cdot H$", keeping the abscissae of points.
  - greedy_optimized: submodular greedy selection from a pool of $4B$.
  - asymmetric_sizing: base sizes $B_1 \ge B_2 \ge B_3$.
  - The two priors: H016, a quadratic-residue base from an r-adding walk, and H017, small multiples jG.
- **Measured.** $N \approx 2^{14}, 2^{16}, 2^{18}$; 12 prime-order curves; $m = 3$; exact counting over every target; 288 of 288 cells.
  - Mean-yield ratio is exactly **1.000000** for every untyped geometry (high_bit_interval, small_height, coset_union) at every size.
  - mixed_two_base: 0.3726, 0.3700, 0.3749, against a prediction of $6/16 = 0.375$.
  - asymmetric_sizing: 0.034–0.042.
  - greedy_optimized (held out): 0.955–0.981.
  - coset_union coverage reached 1.0012, with a CI that includes 1. Its d was as small as 4, "a union of 59 tiny cosets".
- **Mechanism** (AR:knowledge/findings/KN-FIND-007.md, established). $\Sigma_r c_D(r) = C(B+m-1, m)$ holds for **every** base of size B. "Factor-base geometry cannot change mean yield, only redistribute it." Coverage headroom is at most $\min(1, \mu)/(1 - e^{-\mu}) \le 1.582$. A Bose–Chowla Sidon B_3 base reaches 1.1071.
- **Verdict.** rejected_scoped (AR:DEC-20260724-007, AR:EV-FBG-001, replicated).

A3. Automorphism-orbit bases (`glv-orbit`, j = 0 / j = 1728)

- **Definition.** The closure of the `size` smallest abscissae under `Aut(E)`.
  - `j = 0`: `x ↦ ζx`, 6 points per column.
  - `j = 1728`: `x ↦ −x`, 4 points per column.
  - Each orbit folds onto one column with eigenvalue weights.
  - Plug-in: `glv-orbit:size,group=auto|negation|j0|j1728` (`plugins.rs` L889–948).
  - Ancestors: `ec_index_calculus_j0.rs` here, and `CA:prime_orbit_index_calculus.rs`.
- **Measured** (`RESEARCH_GLV_INVARIANT_FACTOR_BASES.md` E1 and E12).
  - The column ratio is exactly 3 (`j = 0`) and 2 (`j = 1728`).
  - The full-rank ratio is 2.83–5.48 and 2.22–2.96.
  - E12, a pair table over orbit representatives: the table shrinks ÷2.95 and `S` ÷1.18.
  - ecbench prime20 smoke: `S = 22.39`, against 11.33 for `prime-abscissa`.
  - `CA:`: 7–18× below per-target rho, but 0.72–0.89 of the folded batch-rho expectation.
  - `AR:H-STR-002`: an early 0.011 cost ratio disappeared once the appended rows were removed (`AR:EV-STR-003`).
- **Verdict.** Engineering: "The fold by any finite group of endomorphisms is the order of the subgroup of `(Z/rZ)^*` its eigenvalues generate". In other words, a constant `|Aut|`.

A4. Multiplicative subgroup and coset bases, high-degree form

(`V = g·μ_d`, one binomial) This is the same set as the Kummer tower (0.1), written as one binomial instead of a tower. It is the cleanest controlled test of whether the set helps without the presentation.

- **A4a. Sage subgroup base** (`research/ecdlp_autolab/structured_fb_subgroup_result.md`, 2026-05-27).
  - Cells: `x^m − 1` at 13, 16 and 19 bits, with `|FB ∩ H|` = 10, 16 and 31.
  - Gröbner time per query: 12.5, 17.3 and **74.7 ms**, against 4.7, 18.1 and 30.8 ms for a generic base. That is 2.4× slower at 19 bits.
  - Mechanism: the Hilbert regularity depends on `deg F = |FB|`, not on sparsity. This motivated Proposition 1 (§7).
- **A4b. AR engine `subgroup`.** `x ∈ g·μ_d` with `d | p − 1` chosen near `2|F|`; membership is `x^d = g^d`. A prime filter makes the comparison fair.
  - Exponent: 0.97 [0.95, 0.99] at `m = 2` and 1.00 [0.98, 1.01] at `m = 3`; "the high-degree subgroup base behaves like a random set of the same size".
  - msolve: the sparse binomial is about 4× faster than dense at `m = 2` (`|F| = 258`), but 20× slower at `m = 3` ("134 s against 7 s at `|F| = 25`").

- **A4c. Relation-level excess against matched random.** AR:EV-PFDR-ad6274 and AR:EV-PFDR-1faf10, 30–32 bits.
  - κ_{rel} upper bounds are 1.0074–1.0112; the TT4 subgroup reads 1.0633.
  - One unreplicated excursion: z = 4.752.
  - Verdict: weakens.
- **A4d. Character-level.** AR:H-ECDLP-4e1880 (weakened, strong): coset indicators sit at the random Fourier level, e.g. index-3 coset 0.5013 ± 0.0037.
- **A4e. On paper** (RESEARCH_PRIME_FIELD_BREAKTHROUGH_PROGRAM.md §4.6). Cyclic-norm folding in $O(\log B)$ products still yields a degree-$2B$ output, so the per-target cost is $\tilde{O}(B)$.
- **Verdict.** Refuted: no exponent change. The tower presentation of the same ν (0.1) is the only open form.

A5. Dickson bases

- **A5a. Toy.** $x = u + c/u$ with $u \in g \cdot \mu_d$; membership is $D_d(x, c) = \lambda$ (AR:FactorBase.dickson).
  - Indistinguishable from random: "dickson TT4 kappa 1.0172, upper 1.0886" (AR:EV-PFDR-ad6274).
  - As a tower (0.1) it is the same F4 computation as Kummer.
- **A5b. The P-256 Dickson-torus campaign** (24 rounds, 2026-10-04 to 2026-10-06; research/icv1-fp256-…_round{1..24}_*; builds on PR #1327). This is the only tower-type base built on a real NIST prime.
  - **Definition.** P-256 has $v_2(p + 1) = 96$.
    - The generator: the norm-one element $(1,5)^{p-1}$ in $F_p[i]/(i^2 + 1)$, raised to $(p+1)/2^{96}$, gives an element of exact order 2^{96}.
    - The fibre is a depth-18 trace coset with terminal trace 0.
    - The abscissae are the 2^{18} traces $w + w^{-1}$, the roots of the Dickson chain $z_{j+1} = z_j^2 - 2$.
    - The base is **131,239 negation-folded columns** (262,478 signed points), FB1h2ea06bef7f7a. The best inventory found was 131,458 columns (FB1h2f8621cda105).
  - **The round chain.** Most rounds ran on small-prime analogues ($p = 127$ or 1151); round 8 transferred to the real P-256 modulus.
    - Rounds 2–4: $D = 4$.
    - Round 5: branching 3–4 levels gives the first fall to $\mathbf{D = 3}$, in 1,920 components.
    - Round 6: every extra level of residual depth multiplies the total work ×4.
    - Round 14: at real P-256 size the images reach the generic maximum (2, 8, 128, 32768), so there is no compression.
    - Round 18: the charged outer scan costs $\mathbf{2^{272.404}}$, 144.4 bits above rho.

  - Round 19: a multilevel selector brings it to 2^165.156, 32.69 bits above rho. "The depth-18 chain removes zero global combinations."
  - Round 20: a batched collision gives 2^151.885, 19.419 bits above rho.
  - Round 21: **zero** FB1 relations in 8,413,312 small multiples and 5,986,344 Dickson-block sums.
  - Round 24: the selected Dickson base is **394.5× rho**. A K = 1 known-log row reaches 0.964×, but that is a lower bound, not an attack.
- ▸ **Verdict.** A degree fall appears only after splitting into components, and the branch frontier grows exponentially. End to end it is refuted at 16–144 bits above rho.

A6. P-256 affine bit-box `x = offset + Σ_{i<18} 2^i·b_i`, with `b_i² = b_i`

- **Source.** `src/cryptanalysis/p256_bitbox_factor_base.rs`; round 1.
- **Measured.**
  - ▸ S_3 solving degree is 5 against Dickson's 4 at depths 3–4, and 6 against 4 at depth 5.
  - ▸ The base `FB1ha8fa8dae90f9` has 131,440 columns.
- **Verdict.** Refuted ("reject degree and cost", round 22).

A7. P-256 PGL_2 root orbit: Möbius images $M(\mu_d)$ of subgroups of $F_p^\times$

- **Definition.** $M \in PGL_2(F_p)$ is drawn from a hash, and $d \in \{260, 270, 272, 425\}$ divides $p - 1$. The base is closed under $u \mapsto \omega u$. There are 16 arms with 2,131,217 columns in total.
- **Measured** (round 23, `root_orbit_fb_round23_20261006/`). **Zero** cross-column relations in 34,099,472 images. The best arm, `FB1h8fc8b5fd8529`, is 491.494× rho.
- **Verdict.** Refuted: "generator degree two is not solving degree".

A8. Eisenstein-smooth base (j = 0)

- **Definition.** $x_\alpha = (u + v\cdot\omega_p) \bmod p$ for Eisenstein integers $\alpha = u + v\omega$ with $N(\alpha) \le B^2$; needs $p \equiv 1 \pmod 3$ (`ec_index_calculus_j0.rs` L721–790).
- **Measured.** Exponent $\alpha = 0.825$ ($R^2 = 0.992$), against 0.752 for the $j = 0$ orbit base and 0.691 for a generic base (`research/notes/ecdlp-general/RESEARCH_BENCH_LOG.md`).
- **Verdict.** "Empirically falsified … the speculative direction is dead."

A9. Arithmetic progression and mod-ℓ partitions

- **Arithmetic progression** (`research/ecdlp_autolab/structured_fb_additive_result.md`). Gröbner time is flat at 4.6–14.9 ms. The progression found was $x_0 = 0$, $d = 1$, which is just the generic base.

Negative, with that methodology caveat. AR:EXP-FB-001 (interval, progression, random and subgroup bases): "yields within 1.1x of random ... solve time ~d^6 identical across structures".

- **mod-ℓ partition** (research/ecdlp_autolab/phase9_result.md, E(F_1009)). $x(P_1 + P_2) \bmod \ell$ is not a function of $(x_1 \bmod \ell, x_2 \bmod \ell)$ for $\ell \in \{3, 5, 7, 11\}$, over 19,801 pairs each. Structurally negative: the chord-tangent inversion does not commute with reduction mod ℓ.

A10. Fixed-degree and map-image bases (AR: ALPF series, 2026-05-30 to 2026-06-01)

- **Over F_{p^2}: trace-zero, subfield and norm-1 bases** (AR:EXP-ALPF-009).
  - The membership degree is fixed and D_reg is about 7, where the interval base gives 10, 18, 34 and 66 at L = 4, 8, 16, 32.
  - But the fraction of relations landing in E(F_p) is 0.000 (trace-zero) and 0.007 (norm-1): relations land in the wrong subgroup.
  - Verdict: SCOPED_NEGATIVE, "descent blocked".
- **E(F_p)-native candidates** (AR:EXP-ALPF-017, on $y^2 = x^3 + 10 / F_{97}$):
  - the CM eigenset is the whole group, because [56] is a scalar;
  - the **ℓ-isogeny image** is "BIJECTIVE ... image = all of $E_2(F_p)$: no filtering";
  - $t^2 + c$ needs a quadratic-residue test of degree 48;
  - ψ_n is empty on a prime-order curve.
  - Verdict: NEGATIVE.
- **ψ_n torsion base on $n^2 \mid \#E$** (AR:EXP-ALPF-024). "n-torsion DLogs are all multiples of $n \cdot L$ ... Relations carry zero info about k mod L." Pohlig–Hellman territory. FAILED.
- **Rational-map pullback $\varphi(T)$** (AR:EXP-ALPF-007, 011). D_reg falls from 18 to 7, but never both degrees at once. INCONCLUSIVE, because the meter was not validated.
- **e-ring and power-sum presentations** (AR:EXP-ALPF-011/013/021/031).
  - They fired in 16 of 16 cells.
  - The red team showed the effect is a "shared-factor syzygy living entirely in the FB constraints".
  - Verdict: FAILED (a bankable negative).
- **Torus T_2, Weil restriction, theta/Kummer chart** (AR:EXP-ALPF-018/023/025/026). None of them descends, or the solving degree is invariant under restriction. FAILED or INCONCLUSIVE.

A11. Isogeny-related prime-field bases (other than the tower)

- **Augmented $F \cup \varphi^{-1}(F)$** for Elkies $\ell \in \{3\ldots23\}$ at 20–28 bits (AR:H-ICI-063e91, weakened). The augmentation ratio is about $2 - B_{frac}$, the same as a random-bijection null ("$\Delta|aug - null| < 0.004$").
- **Isogeny-class neighbours** (AR:EXP-ALPF-029…031, AR:FINDING-PF-IC-001). $top_form(S_3)$ is independent of (a, b), and the solving degree does not differ.
- **Conductor-gap / fibre-aware bases** (research/isogeny_conductor_gap_ic_20261010/, research/drastic_prime_conductor_gap_*_20261012/). Floor/crater ratios are about 1 at gaps up to 2,033,609, with the same F4 degree (about 3) on both. Negative.
- **Yield label across isogeny classes** (ML:experiments/hardness/report.md, 106,594 nodes in 254 classes). The yield ratio γ/random has a within-class sd of 0.0021, and the best held-out R^2 is 0.021. The only within-class effect is mechanical: a factor-base 2-torsion point, worth about 2%.

A12. Proposals that are closed on paper or still at Stage 0

- **Height box** $F_H = \{P : ht(x(P)) \le H\}$ (AR:H-ECDLP-b97b72, specified). The relation search is pinned at the small-root threshold.
- **Degree-d map bases** $V = u_D^{-1}(W)$ (AR:H-ECDLP-30a2a1, AR:IDEA-20261009-a7733f). The design audit says "keep proposed and do not approve".
  - AR:KN-OPEN-020 (open) proves a bounded-degree no-go by derivation: by Bezout $B \le 3d$, at most B^m targets are reachable, and descent costs $\Omega(N/B^m)$.
- **CM-factor-base intakes** (AR:coordination/intake/cm-factor-base-*). Five diagnostic proposals, unapproved, with no exponent claim.
- **Global lifting** (xedni, small-height points of $E(Q)$), **embedding into $E(F_{p^n})$**, **quasi-subfield polynomials at $n = 1$**, and **Weil-descent analogues over F_p**: all closed on paper.
  - RESEARCH_INDEX_CALCULUS_FACTOR_BASE.md §2 calls the last "structurally hopeless": the missing ingredient is Galois structure.
- **PKM divisor-set audit** (research/notes/cm-isogeny/RESEARCH_PKM_CRITERION.md). An audit score, not a base: P-224 and P-192 both score 0.647, and P-521 scores 0.001. The PKM note §1.3 says it is "neither … PKM's construction".

---

3. Odd-characteristic extension fields $E(F_{p^k})$

B1. Gaudry–Diem subfield base $\{P : x(P) \in F_p\}$

The one textbook positive case: Weil restriction supplies the conjugate equations that F_p lacks.

- **$k = 2$, toy** (RESEARCH_DIEM_DESCENT.md): E/F_{25}; 18 of 25 targets decompose.

- **k = 3** (RESEARCH_RESIDUAL_WALKS.md §11; gaudry_cubic.rs).
  - MITM with a Weil-restricted S_3 pair test: 1,057× rho at $2^{24.2}$, rising to 2,240× at $2^{33.1}$.
  - With Macaulay and engineering, the S_4 solve constant is $C_3 = 0.876 \cdot 10^6$. The best plain variant is 528× rho.
  - The double-large-prime exponent is 0.424 ± 0.016, below 1/2, but at 1,989× rho; parity is extrapolated to lie past 2^{230}.
- **k = 4** (gaudry_quartic.rs). $C_4 = 1.2 \cdot 10^{12}$ per S_5 solve. The linear algebra against rho is $r_\infty = 0.518 \pm 0.031$. Handover is at about 2^{151}.
- **Joux–Vitse (k–1)-point decompositions** (RESEARCH_RHO_PARITY_PROGRAMME.md, RESEARCH_K5_TORSION_JOUX_VITSE.md).
  - $k = 4$: flat at 6,945×.
  - $k = 5$: the Edwards 2-torsion symmetry cuts the solve constant 416×; parity is at 2^{233}.
- **ML: M9b**: 453 curves, $n = 2, 3$; no first fall in 5,592 of 5,592 rows. The yield follows the product law.
- **Verdict.** Bounded away from rho at machine size. "On generic curves no route closes below 2^{200}."

B2. Symmetry-folded extension bases

(RESEARCH_GLV_INDEX_CALCULUS.md; RESEARCH_GLV_INVARIANT_FACTOR_BASES.md E2–E18)

- **ψ-folded subspace on $j = 0$ $E(F_{p^3})$.** Every cost falls exactly ÷3.0, but the result is still 220–540× rho.
- **GLS ψ-stable line gls-line.** $x \in u \cdot s \cdot F_p$ on the GLS twist over F_{p^2}, 4 points per column; the full-rank ratio is 2.20.
- **Frobenius eigenline (E5).** The column ratio is 3, but relations fall only 1.2–1.6×, because the π-fixed $E(F_p)$ confines the folded rows.
- **FGHR Y-line with the τ_T 2-torsion fold (E13).** 12 columns per orbit and a degree-16 resultant oracle; the best arm is **267×** rho.
- **E18, $k = 4$ ψ fold.** $r_\infty = 0.138 \pm 0.008$, against 1.232 plain; handover at $2^{146.0}$.
- **Q-curves (E14) and type-C CM endomorphisms (E4).** Base points survive only at chance rates, or the base has zero invariant points.
- **Verdict.** Engineering or accounting throughout: a fold divides by the group order and nothing more.

B3. Exotic coordinates (Möbius frames, 2- and 3-torsion;

RESEARCH_EXOTIC_COORDINATES.md)

- The S_4 degrees halve, from [4,4,4,4] to [2,2,2,2,1].
- On F_{31^3} the v-line base (86 points) gives the smallest system measured: 3 unknowns of degree 2.

- The Vélu and Klein transports are not F_p-valued.
- **Verdict.** Constant-factor.

---

4. Binary fields $E(F_{2^n})$: subspace shapes

The master inventory is `RESEARCH_FACTOR_BASE_SHAPE_SEARCH.md` §1, table A1–A17, with the closure sweep in `examples/factor_base_closure_sweep.rs`.

C1. Coordinate window $V = \langle 1, z, \ldots, z^{l-1} \rangle$ (FPPR / Petit–Quisquater / Diem)

- **Plug-ins.** `binary-subspace:dimension=l`, alias `koblitz-standard-subspace`.
- **Oracles.** `descent-algebraic`, with 11 engines (F4/F5 variants, crossbred, XL, SAT-CDCL, FES, exhaustive), and the pair table.
- **Measured.**
  - Ledger char-2 rows: `mitm m = 3` is 89× rho at `n = 27` (exponent 0.624). The S_4 pairs-and-solve, a relabelling, is 45,471× rho.
  - ECC2K-130 product law: `2^132.58`, i.e. `2^71.77`× rho.
  - `AR:KN-FIND-aa2efc`: even a **free** oracle costs `2^89.25`, `2^68.58`, `2^56.40` and `2^48.44` at `m = 2…5`, against rho's `2^60.809`.
  - ecbench L0 smoke, Koblitz `n = 17`: `S = 43.10`, 47.2× rho-frob.
  - `CA:experiments/fb-search/`: a model-predicted selection over 1,850 bases has Spearman 0.924 against measured cost. The best base beats prefix `l = 5` by 2.8×, but "every measured cell remains 3.9e3–4.4e4 times the rho reference".
  - `CA:` PDP-degree heuristics: over 656 bases, `D = 2 + [e < −3.5] + [e < −8.5]`, where `e = n − dim V − dim V^{(2)}`. Geometric progressions are optimal (`dim V^{(2)} = 2l − 1`).
  - `CA:` linearized-half (Courtois 2016): `3l − 1 ≤ n` makes S_3 F_2-linear; on ECC2K-130 it costs `2^91.0` and up, +30 bits over rho.
- **Verdict.** Refuted at deployed size. "No engine here beats exhaustive search, and nothing beats rho" (`CA:suite/docs/ic/FRAMEWORK.md` §8).

C2–C8. Other binary shapes

entry	definition	measured	verdict
C2 random subspace	random F_2-subspace	`D*` about 4.0 at `2l = n`, rising with `l` (DREG measurement note)	the hard baseline

C3 subfield F_{2^l}	$V = F_{2^l} \subset F_{2^n}$	D^* about 2.0; unavailable at prime n; on $b = 1$ the points lie in $E(F_{2^l})$ and the yield collapses	structurally empty at prime n
C4 EXP-H shapes	gp, gpscaled, gpsym, Frobenius progression, mixed, trace-zero variants	"No shape beats the coordinate window on class-0 targets"	negative; G1–G6 still open
C5 trace-zero	$V \subset \ker \mathrm{Tr}$ (koblitz-trace-zero)	doubles the yield; class-1 targets have zero decompositions (AR:H-SEMBIN-83a856, 79,751 targets)	engineering
C6 Hamming ball	$\{wt_NB(x) \le w\}$ in a normal basis	MultiSolve calls grow as $\|F_w\|^{1.9–2.5}$; CA: N53 weight-3: 3 DLPs, rho/IC 0.256–0.319	rejected (it saves storage only)
C7 quasi-subfield	$X^{2^{n_0}} - \lambda(X)$	"barren" at $n = 131$; AR:KN-FIND-617d78: $\beta > 1/2$	closed
C8 Galbraith–Gebregiyorgis / Shantz–Teske	special subspace; δ shift	GG "buys variables, not degree" ($D^* = 4$ at $n = 9$, ≥ 5 at $n = 15$); δ lowers D^* by about 1	constant factor
C9 affine plane at N19	$12009 + \mathrm{span}\{257473, 353192\}$, 152 points	coverage 99.44% of the best; SAT 1.23× slower (AR admissi-	negative

		ble-affine study, 2026-09-21)	
C10 curve-adapted full-density subspaces	subspaces dense in `x(E)`	`CA`: density 0.079–0.994 of random at dimension 5; about dimension 10 at `n = 131`, against the 33 needed	negative
C11 orbit-valued quotient	Frobenius-orbit invariants as the base	full degree (`n = 19`: 18); missing entropy at `n = 131`	negative

---

5. Koblitz curves `K_a / F_{2^n}`

D1. Frobenius-invariant subspaces (`koblitz-orbit:divisor=i;j`)

- **Definition.** `V = ker` of a product of linearised factors of `x^n − 1`, i.e. a binary cyclic code. Signed Frobenius orbits fold onto one column with weights `±λ^k`.
- **Existence.** Dimensions are subset sums of 2-cyclotomic coset sizes. **The family is empty at `n = 131` and 163**: only dimensions 0, 1, `n − 1` and `n` exist.
- **Measured.**
  - Toys: relation savings 7.86–12.96×, linear-algebra savings 61.7–168×.
  - Ledger: K falls from 438 to 20 at `n = 23`, and `S` 7%. At `n = 41` it is 300× rho. This is the ledger's one "advance, count" label.
  - ecbench smoke `n = 17`: 18.7× rho-frob.
- **Verdict.** Engineering, and unavailable at deployed `n`. See `AR:KN-FIND-b9a41d` (the gain is at most `n`, and the only faithful stable dimension at 131 and 163 is `n − 1`).

D2. Frobenius-orbit unions (`compact-orbit-scan`)

- **Definition.** The first `K` cofactor-projected signed Frobenius orbits from a raw-x scan (`docs/ic/COMPACT_ORBIT_PRODUCER.md`, PR #714).
- **Measured.**
  - 5 columns give `S = 1.64` (1.55× rho).
  - Isolated `n = 61` online run: 12.9× and 13.9× faster than rho per target online, but the cold ratio is 83.4.
  - Every complete-CPU cold cell is above parity (1.314–22.675×).

- ECC2K-130 total-work verdict: a materialised union bottoms out at `2^124.99`, i.e. `2^64.18`× rho.
- ecbench `n = 17`: 9.985× rho-frob.

- **Verdict.** It wins online after precomputation only.

D3. `Z[τ]`-multiplier closure (`compact-orbit-scan:norm=N`)

- **Definition.** Orbits of `α(P)` for `α = a + bτ` of norm at most `N`.
- **Measured** (`research/ic_leads_20261010/RESULTS_ROUND2.md` L391–400).
  - 2 columns at norm 64 give **`S ≈ 0.94`, 4.5× the matched signed-Frobenius rho**, the best toy row on the ladder.
  - At `n = 41`, `m = 3`, one-target total work falls 9.2×.
- **Verdict.** Engineering, a "precompute trade, not a yield lever" (`docs/ic/RESEARCH_TRANSFER_AWARE_IC_20261010.md` §4).

D4. Cyclotomic γ-weight base (`cyclotomic:w`)

- **Definition.** `C_w = {Σ_{k∈S} γ^k : |S| = w}`, with `γ` a primitive `(2n+1)`-th root of unity.
- **Existence.** `2n + 1` prime and `ord(2) = n` (so `n` is one of 11, 23, 83, 131).
- **Measured.** ecbench `n = 23`, `a = 1`: `S = 3.427`, 9.9× rho. The solver cells timed out.
- **Verdict.** An open engineering lead; the falsifier is not established.

D5–D7. Other Koblitz bases

- **D5. u-frame symmetrised base** (`koblitz-symmetrised`, `F_u = {P : 1/(x+1) ∈ V}`).
  - `S_sym/S_x` is 0.84 at `n = 17` and 0.76 at `n = 23`, but 4.0 at `n = 31`.
  - Every arm is 990–63,500× rho.
  - Refuted at `n = 31`.
- **D6. Prefix-subspace Frobenius closure** (`koblitz-closure`). Hits per system are 1.79× and 2.14×, against predictions of 2 and 3. It costs 50–100× more than the pair table.
- **D7. Isogeny-transported and descendant-native bases** (A16, degree 7).
  - The native base costs 4.012× more.
  - Floor-curve twins are level-blind.
  - `CA`: volcano descendants: E0 needs 0.996× the attempts (CI 0.976–1.017).
  - Negative.

---

6. Jacobians and covers

- **E1. Degree-1 places on genus 2–4 hyperelliptic Jacobians** (Adleman–DeMarrais–Huang / Gaudry; Thériault reduced base with large primes). `RESEARCH_HYPERELLIPTIC_IC_RHO.md`:
  - genus 2: IC/rho about 1;

- genus 3: 0.66, 0.61 and **0.23** at `p = 61`, 101 and 401;
- genus 4: 0.15 at `p = 61`;
- "at reachable sizes the lever is the oracle … not the factor base".
- These curves are not elliptic, so this is not an ECDLP route by itself.

- **E2. Joux–Vitse genus-3 cover base** on `Jac_H(F_{p²})` (`RESEARCH_COVER_DECOMPOSITION_LEDGER.md`).
  - `F = {(Q) − ∞ : x(Q) ∈ F_p}`, for the weak class of `E/F_{q³}` with a genus-3 GHS cover.
  - The sieve variant gives **0.039–0.069× rho at `p = 1009`** and **0.0122× at `p = 1511`**. From a non-weak curve, via an isogeny walk: 0.0049–0.019×.
  - **This is the only factor base in the inventory below rho, and only on the weak class.**
- **E3. P-192 weighted-CM class-relation census** (`research/p192-weak-curve-20261006/REPORT.md` L249–380; `AR:H-SCURVE-ec34c4`).
  - The base is prime ideals of `O_D`, `D = t² − 4p`, split `ℓ ∈ {13, 23, …, 113}`.
  - 9,948,061 vectors gave 103 relations, all scalar.
  - `INDETERMINATE`. It is the only factor-base object ever built on P-192, and it is not an x-coordinate base.
- **E4. GHS / Weil-descent covers of ECC2K-130.** The large horn is at best `2^70.19`× rho; the small horn is empty. `CA:` ECC2K-130 G2 gives `m = 1` or 131, so zero bits are gained.
- **E5. Smith plane-quartic codomain** (`ML:experiments/smith-codomain/report.md`). Diem line relations yield like a generic quartic: `f²/2`, and 10–30× the hyperelliptic yield.


---


7. Results that bound every family

1. **Yield conservation** (`AR:KN-FIND-007`). Mean decomposition yield depends only on `|F|`, so no geometry changes it; coverage headroom is at most 1.582. This closes every "cleverer set of the same size" proposal that relies on a table oracle.
2. **Sparsity invariance, Proposition 1** (`RESEARCH_INDEX_CALCULUS_FACTOR_BASE.md` §1.2). For a fixed set `V`, every generating set of `(F_V)` has the same Hilbert function and the same `D*`. Re-encoding membership cannot get below the Yokoyama bound `Reg ≈ md + d_S − m`. **Its scope excludes towers.** PKM adds auxiliary variables (PKM note §1.3), so this is the exact gap the two flagship families (§0) live in.
3. **The pair-table family law** (boundary ledger §11.2–11.3). `S_family = 0.75·r^{1/6}` on a prime-order curve, which crosses rho only at `r ≈ 22`; about 1.58·10⁶× rho at `2^128`. Base size and folds change only the constant. This is

why A2, A4, the ecbench `prime-kummer` run and every table-oracle row read as "behaves like a random set".

4. **Symmetry inventory** (`RESEARCH_IC_LEADS_AND_CONNECTIONS_20261010.md` §6). Every fold (negation, Frobenius, automorphisms, 2-torsion, S_m, D_4) is a constant or polynomial in `n`. $S \cdot T^2 \gtrsim r/|\mathrm{Aut}|$ covers every table-lookup decomposition.
5. **Bezout bound** (`AR:KN-OPEN-020`). A membership predicate of degree `d` holds at most `3d` points, so a base of `B` points needs degree at least `B/3`. Only an auxiliary-variable presentation, a tower, escapes this.
6. **Subgroup confinement** (`AR:EXP-ALPF-009/024`, `CA:`/AR subfield rows). A base inside a proper subgroup, or in the wrong group after descent, carries no information about the target's logarithm.
7. **"Index calculus is priced by the ambient field; rho is priced by the subgroup"** (`RESEARCH_ECC2K130_DECOMPOSITION.md` §5.2), and "Prime `p` and prime `n` are one obstruction" (leads note §7(d)).





---

8. Open lines, by how directly they test the two flagship families

1. **The `m ≥ 4` PKM solving degree past `N = 16`.** This decides whether either tower family is subexponential at all. It is memory-bound on this host: `N = 21` at `m = 3` needs more than 14 GB.
2. **An isogeny-tower plug-in that is wide-integer and charged.** Port `isogeny()` from `examples/pkm_tower_pilot.rs` into `prime_tower.rs`, beyond `u64`, with SEA or CM construction of `E'` and the search charged to the factor-base phase. Without it, no P-192-shape statement can be priced.
3. **The Dickson torus case** (`2^t | p + 1`). It is unmeasured as a tower, because the pilot prime splits, although P-256 rounds 1–24 built the torus set. It is relevant to P-192 (`t ≤ 64`) and P-256 (`t ≤ 96`).
4. **A tower at a prime whose $v_2(p-1)$ is P-224-like**, to check that nothing about very deep 2-adicity changes the degree. Derived here: this needs `t` well past the `t ≤ 11` run so far, so it is blocked on item 1 first.
5. **Binary shape-search G1–G6** (G4: trace-form, non-subspace Frobenius-stable sets), **the cyclotomic base falsifier** (D4), and **the D_4-symmetrised S_5** (Bézout count 4096 → 512, never run).

9. Method and limits of this note

- **Search.** Three read-only sweeps on 2026-10-15:
  - `crypto`: `research/notes/index-calculus/`, `docs/ic/`, `docs/ecbench/`, the `ic_framework` plug-ins, and `research/*` study directories;
  - `crypto-autoresearcher`: `knowledge/`, `ledger/`, `experiments/`, `coordination/`;
  - `cryptanalysis` and `ml-cryptanalysis`: the IC suite and the experiment reports.
- **Spot checks.** The key figures were checked against their files by hand:
  - the §10.10 2-adic table;
  - the pilot and A1 degree tables;
  - the PKM ecbench ratios;
  - the P-256 round-18 `2^272.404`;
  - the cover sieve's 0.0122;
  - the `Z[τ] S ≈ 0.94`;
  - the C4 table;
  - the `EXP-FB3-001` definitions and ratios;
  - `ALPF-022`;
  - the AR engine's subgroup exponents.
- **What is not re-derived.** Entries condensed from long notes keep their source's status label and are not re-derived here. If a source and this page disagree, the source wins.
- **Nothing here is a new measurement**, and nothing here is a statement about a deployed curve: no factor base in the inventory has been run at P-192 or P-224 size.
- **Renderer.** Pandoc 3.1.3 converts this file to Typst, and Typst (Python wheel 0.15.0) compiles the PDF. The figures are drawn by `figures/plot.py` from `figures/data.json`, which holds only quoted values.
- **Conductor.** The control plane was not reachable in the authoring container (`connection refused` on `localhost:8080`), so no task was reserved.