wide-n83: ecbench follow-up

Session ECBS1hb7a0c78a3184

Source 0cbc86b2c828f1aa7fae62282913cce9ea6e099d

Binary 50a5739fadcb08ab8f170d4fe03ba3427fb0fd387c1a5918843fcda4d68ff1fb

4 attempts; 0 verified recoveries; 0 exact standard replays.

Fresh public single-target workloads, seed20261015. Cold setup repeated; no planted scalar. Host ECBENV2h96c931cc33fa, L0; wall times inadmissible. Exhausted/error outcomes have a separate native replay.

Points and ranges use verified runs only: native mean and observed min/max, not confidence intervals. Failed work remains in the resource vectors. Count quotients do not bound full-cost ratios. Shape panels plot independently constructed coordinate counts; wide panels show recorded bounded outcomes.

orbit-c16: 0/2 recovered; 512 total queries; 0 checked relations; 42402 total stored entries

orbit-c4: 0/2 recovered; 512 total queries; 0 checked relations; 2634 total stored entries

Exact E0 GF(2^83) → unknown-log base → quotient pair table → bounded target pin search

Evidence: research/ecbench_leads_20261015/sessions/wide-n83; wide-n83.audit.json; failed-replays-v2.json; wide-n83.resources.json.