

GeeksforGeeks

A computer science portal for geeks

GeeksQuiz

- [Home](#)
- [Algorithms](#)
- [DS](#)
- [GATE](#)
- [Interview Corner](#)
- [Q&A](#)
- [C](#)
- [C++](#)
- [Java](#)
- [Books](#)
- [Contribute](#)
- [Ask a Q](#)
- [About](#)

[Array](#)

[Bit Magic](#)

[C/C++](#)

[Articles](#)

[GFacts](#)

[Linked List](#)

[MCQ](#)

[Misc](#)

[Output](#)

[String](#)

[Tree](#)

[Graph](#)

Divide and Conquer | Set 6 (Tiling Problem)

Given a n by n board where n is of form 2^k where $k \geq 1$ (Basically n is a power of 2 with minimum value as 2). The board has one missing cell (of size 1×1). Fill the board using L shaped tiles. A L shaped tile is a 2×2 square with one cell of size 1×1 missing.




Figure 1: An example input

This problem can be solved using Divide and Conquer. Below is the recursive algorithm.

```
// n is size of given square, p is location of missing cell
Tile(int n, Point p)
```

- 1) Base case: $n = 2$, A 2×2 square with one cell missing is nothing but a tile and can be filled with a single tile.
- 2) Place a L shaped tile at the center such that it does not cover the $n/2 \times n/2$ subsquare that has a missing square. **Now all four subsquares of size $n/2 \times n/2$ have a missing cell** (a cell that doesn't need to be filled). See figure 2 below.
- 3) Solve the problem recursively for following four. Let p_1, p_2, p_3 and p_4 be positions of the 4 missing cells in 4 squares.
 - a) `Tile($n/2$, p_1)`
 - b) `Tile($n/2$, p_2)`
 - c) `Tile($n/2$, p_3)`
 - d) `Tile($n/2$, p_4)`

The below diagrams show working of above algorithm




Figure 2: After placing first tile




Figure 3: Recurring for first subsquare.




Figure 4: Shows first step in all four subsquares.

Time Complexity:

Recurrence relation for above recursive algorithm can be written as below. C is a constant.

$$T(n) = 4T(n/2) + C$$

The above recursion can be solved using [Master Method](#) and time complexity is $O(n^2)$

How does this work?

The working of Divide and Conquer algorithm can be proved using Mathematical Induction. Let the input square be of size $2^k \times 2^k$ where $k \geq 1$.

Base Case: We know that the problem can be solved for $k = 1$. We have a 2×2 square with one cell missing.

Induction Hypothesis: Let the problem can be solved for $k-1$.

Now we need to prove to prove that the problem can be solved for k if it can be solved for $k-1$. For k , we put a L shaped tile in middle and we have four subsquares with dimension $2^{k-1} \times 2^{k-1}$ as shown in figure 2 above. So if we can solve 4 subsquares, we can solve the complete square.

References:

<http://www.comp.nus.edu.sg/~sanjay/cs3230/dandc.pdf>

This article is contributed by **Abhay Rathi**. Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above.

Related Topics:

- [Find Union and Intersection of two unsorted arrays](#)
- [Pythagorean Triplet in an array](#)
- [Maximum profit by buying and selling a share at most twice](#)

- [Design a data structure that supports insert, delete, search and getRandom in constant time](#)
- [Print missing elements that lie in range 0 – 99](#)
- [Iterative Merge Sort](#)
- [Group multiple occurrence of array elements ordered by first occurrence](#)
- [Given a sorted and rotated array, find if there is a pair with a given sum](#)

Tags: [Divide and Conquer](#)



Writing code in comment? Please use ideone.com and share the link here.

3 Comments

GeeksforGeeks

1 Login ▾ Recommend Share

Sort by Newest ▾



Join the discussion...

**Anton Lisovenko** · 2 months ago

Very elegant solution, though pretty difficult to come to it independently...

  · Reply · Share ›**mknarayan1711** · 2 months agoHow do we know which $n/2 * n/2$ subsquare has a missing Tile when we are trying to place a L shaped subsquare

Ok got it the position of the missing cell is mentioned

  · Reply · Share ›**Someone** · 2 months ago

Ah, interesting solution ! Mine is less astute.

Consider a square area whose side is of size 2^k . We separate this area in four areas of size 2^{k-1} . We want to fill 3 of these 4 areas (drawing a 'L'). We will call this shape a L of size k. We know how to draw a L of size 1 (this is the base shape). Suppose we know how to draw a L of size (k-1). We have a (unique) way of putting together four L of size (k-1) to draw a L of size k.

So, to fill the board, we separate it in 4 squares, we fill the 3 squares not containing the black cell and and drawingwe continue with the remaining square.

Now, we can generalize...

  · Reply · Share › Subscribe Add Disqus to your site Privacy

DISQUS

Google™ Custom Search



-
-
- - [Interview Experiences](#)
 - [Advanced Data Structures](#)
 - [Dynamic Programming](#)
 - [Greedy Algorithms](#)
 - [Backtracking](#)
 - [Pattern Searching](#)
 - [Divide & Conquer](#)
 - [Mathematical Algorithms](#)
 - [Recursion](#)
 - [Geometric Algorithms](#)
-

• Popular Posts

- [All permutations of a given string](#)
- [Memory Layout of C Programs](#)
- [Understanding “extern” keyword in C](#)
- [Median of two sorted arrays](#)
- [Tree traversal without recursion and without stack!](#)
- [Structure Member Alignment, Padding and Data Packing](#)
- [Intersection point of two Linked Lists](#)
- [Lowest Common Ancestor in a BST](#)
- [Check if a binary tree is BST or not](#)
- [Sorted Linked List to Balanced BST](#)



• Recent Comments

- [Ashish Aggarwal](#)

Try Data Structures and Algorithms Made Easy -...

[Algorithms](#) · [17 minutes ago](#)

- Vlad

Thanks. Very interesting lectures.

[Expected Number of Trials until Success](#) · [1 hour ago](#)

- [cfh](#)

My implementation which prints the index of the...

[Longest Even Length Substring such that Sum of First and Second Half is same](#) · [1 hour ago](#)

- [Gaurav pruthi](#)

forgot to see that part ;)

[Bloomberg Interview | Set 1 \(Phone Interview\)](#) · [1 hour ago](#)

- [saeid aslami](#)

thanks

[Greedy Algorithms | Set 7 \(Dijkstra's shortest path algorithm\)](#) · [1 hour ago](#)

- [Cracker](#)

Implementation:...

[Implement Stack using Queues](#) · [2 hours ago](#)

•

@geeksforgeeks, [Some rights reserved](#) [Contact Us!](#)

Powered by [WordPress](#) & [MooTools](#), customized by geeksforgeeks team