

GeeksforGeeks

A computer science portal for geeks

GeeksQuiz

- [Home](#)
- [Algorithms](#)
- [DS](#)
- [GATE](#)
- [Interview Corner](#)
- [Q&A](#)
- [C](#)
- [C++](#)
- [Java](#)
- [Books](#)
- [Contribute](#)
- [Ask a Q](#)
- [About](#)

[Array](#)

[Bit Magic](#)

[C/C++](#)

[Articles](#)

[GFactS](#)

[Linked List](#)

[MCQ](#)

[Misc](#)

[Output](#)

[String](#)

[Tree](#)


[Graph](#)

Lower bound for comparison based sorting algorithms

The problem of sorting can be viewed as following.

Input: A sequence of n numbers $\langle a_1, a_2, \dots, a_n \rangle$.

Output: A permutation (reordering) $\langle a'_1, a'_2, \dots, a'_n \rangle$ of the input sequence such that $a'_1 \leq a'_2 \dots \leq a'_n$.

A sorting algorithm is comparison based if it uses comparison operators to find the order between two numbers. Comparison sorts can be viewed abstractly in terms of decision trees. A decision tree is a [full binary tree](#) that represents the comparisons between elements that are performed by a particular sorting algorithm operating on an input of a given size. The execution of the sorting algorithm corresponds to tracing a path from the root of the decision tree to a leaf. At each internal node, a comparison a_i  a_j is

made. The left subtree then dictates subsequent comparisons for $a_i < a_j$, and the right subtree dictates subsequent comparisons for $a_i > a_j$. When we come to a leaf, the sorting algorithm has established the ordering. So we can say following about the decision tree.

- 1) Each of the $n!$ permutations on n elements must appear as one of the leaves of the decision tree for the sorting algorithm to sort properly.
- 2) Let x be the maximum number of comparisons in a sorting algorithm. The maximum height of the decision tree would be x . A tree with maximum height x has at most 2^x leaves.

After combining the above two facts, we get following relation.

$$n! \leq 2^x$$

Taking Log on both sides.

$$\log_2 n! \leq x$$

Since $\log_2 n! = \Theta(n \log n)$, we can say
 $x = \Omega(n \log_2 n)$

Therefore, any comparison based sorting algorithm must make at least $\Omega(n \log_2 n)$ comparisons to sort the input array, and Heapsort and merge sort are asymptotically optimal comparison sorts.

References:

[Introduction to Algorithms](#), by Thomas H. Cormen, Charles E. Leiserson, Ronald L. Rivest and Clifford Stein

Related Topics:

- [Linearity of Expectation](#)
- [Iterative Tower of Hanoi](#)
- [Count possible ways to construct buildings](#)
- [Build Lowest Number by Removing n digits from a given number](#)
- [Set Cover Problem | Set 1 \(Greedy Approximate Algorithm\)](#)
- [Find number of days between two given dates](#)
- [How to print maximum number of A's using given four keys](#)
- [Write an iterative O\(Log y\) function for pow\(x, y\)](#)



Tweet

0

+1

0

Writing code in comment? Please use ideone.com and share the link here.

11 Comments

GeeksforGeeks

1 Login

Recommend

Share

Sort by Newest



Join the discussion...



Heta Vaishnani • 4 months ago

why does it need $n!$ permutationz?

^ | v • Reply • Share ›



jayasuya_j → Heta Vaishnani • 3 months ago

say for example three numbers : 1,2,3 permutation of them gives the possible arrangements i.e 123,213,231,312,, etc thus one among these must be the answer. So number of possibilities is $n!$ out of which one is the answer. These possibilities form the leaves of the tree,where we choose only one leaf (which gives sorted sequence) by following a path from root to the leaf

1 ^ | v • Reply • Share ›



sd • 7 months ago

Mention of Stirlings Approximation can be helpful.

^ | v • Reply • Share ›



GeeksforGeeks • 8 months ago

nice explanation

1 ^ | v • Reply • Share ›



Kanhaiya Kumawat • a year ago

there is typo in the last line: "Therefore, any comparison based sorting algorithm must make at least comparisons to sort the input array, and Heapsort and merge sort are asymptotically optimal comparison sorts."

its $n \log n$ rather than $\log n$.

^ | v • Reply • Share ›



GeeksforGeeks Mod → Kanhaiya Kumawat • a year ago

Thanks for pointing this out. We have corrected the typo.

^ | v • Reply • Share ›



wgpshashank • 4 years ago

More Info ..

<http://www.it-c.dk/courses/ITM/F2003/Sorting.pdf>

^ | v • Reply • Share ›



lovocas • 4 years ago

" A decision tree is a full binary tree"

I am confused by this statement. :-<

A full binary tree is a tree has $2^{(k+1)}-1$ nodes ?k is the height,the root's height is 0?.

I think decision tree is just a binary tree, whose nodes has either 2 or zero nodes?

^ | v • Reply • Share ›



GeeksforGeeks → lovocas • 4 years ago

@lovocas: The statement looks correct. Please see the following [Wiki definition of Full Binary Tree](#).

A full binary tree (sometimes proper binary tree or 2-tree or strictly binary tree) is a tree in which every node other than the leaves has two children.

To avoid confusion, we have updated the post and added the Wiki link for full binary tree.

2 ^ | v • Reply • Share ›



Yang → GeeksforGeeks • 2 years ago

What if I write a "really bad" algorithm and it asks the same question every time and gets the same answer every time. Then, the Decision tree will still be full binary tree?

^ | v • Reply • Share ›



lovocas → GeeksforGeeks • 4 years ago

oh, thanks very much , got it!

^ | v • Reply • Share ›



Subscribe



Add Disqus to your site



Privacy

-
-
-
-

- [Interview Experiences](#)
- [Advanced Data Structures](#)
- [Dynamic Programming](#)
- [Greedy Algorithms](#)
- [Backtracking](#)
- [Pattern Searching](#)
- [Divide & Conquer](#)
- [Mathematical Algorithms](#)

- [Recursion](#)
- [Geometric Algorithms](#)

• Popular Posts

- [All permutations of a given string](#)
- [Memory Layout of C Programs](#)
- [Understanding “extern” keyword in C](#)
- [Median of two sorted arrays](#)
- [Tree traversal without recursion and without stack!](#)
- [Structure Member Alignment, Padding and Data Packing](#)
- [Intersection point of two Linked Lists](#)
- [Lowest Common Ancestor in a BST.](#)
- [Check if a binary tree is BST or not](#)
- [Sorted Linked List to Balanced BST](#)

Follow @GeeksforGeeks

• Recent Comments

- [It_k](#)

i need help for coding this function in java...

[Java Programming Language](#) · [1 hour ago](#)

- [Piyush](#)

What is the purpose of else if (recStack[*i])...

[Detect Cycle in a Directed Graph](#) · [1 hour ago](#)

- [Andy Toh](#)

My compile-time solution, which agrees with the...

[Dynamic Programming | Set 16 \(Floyd Warshall Algorithm\)](#) · [1 hour ago](#)

- [lucy](#)

because we first fill zero in first col and...

[Dynamic Programming | Set 29 \(Longest Common Substring\)](#) · [2 hours ago](#)

- [lucy](#)

@GeeksforGeeks i don't n know what is this long...

[Dynamic Programming | Set 28 \(Minimum insertions to form a palindrome\)](#) · [2 hours ago](#)

- [manish](#)

Because TAN is not a subsequence of RANT. ANT...

[Given two strings, find if first string is a subsequence of second](#) · [2 hours ago](#)

•

@geeksforgeeks, [Some rights reserved](#) — [Contact Us!](#)

Powered by [WordPress](#) & [MooTools](#), customized by geeksforgeeks team