

GeeksforGeeks

A computer science portal for geeks

GeeksQuiz

- [Home](#)
- [Algorithms](#)
- [DS](#)
- [GATE](#)
- [Interview Corner](#)
- [Q&A](#)
- [C](#)
- [C++](#)
- [Java](#)
- [Books](#)
- [Contribute](#)
- [Ask a Q](#)
- [About](#)

[Array](#)

[Bit Magic](#)

[C/C++](#)

[Articles](#)

[GFacts](#)

[Linked List](#)

[MCQ](#)

[Misc](#)

[Output](#)

[String](#)

[Tree](#)

[Graph](#)

K'th Smallest/Largest Element in Unsorted Array | Set 2 (Expected Linear Time)

We recommend to read following post as a prerequisite of this post.

[K'th Smallest/Largest Element in Unsorted Array | Set 1](#)

Given an array and a number k where k is smaller than size of array, we need to find the k'th smallest element in the given array. It is given that all array elements are distinct.

Examples:

Input: arr[] = {7, 10, 4, 3, 20, 15}
k = 3

Output: 7

Input: arr[] = {7, 10, 4, 3, 20, 15}
k = 4

Output: 10

We have discussed three different solutions [here](#).

In this post method 4 is discussed which is mainly an extension of method 3 (QuickSelect) discussed in the [previous](#) post. The idea is to randomly pick a pivot element. To implement randomized partition, we use a random function, [rand\(\)](#) to generate index between l and r, swap the element at randomly generated index with the last element, and finally call the standard partition process which uses last element as pivot.

Following is C++ implementation of above Randomized QuickSelect.

```
// C++ implementation of randomized quickSelect
#include<iostream>
#include<climits>
#include<cstdlib>
using namespace std;

int randomPartition(int arr[], int l, int r);

// This function returns k'th smallest element in arr[l..r] using
// QuickSort based method. ASSUMPTION: ALL ELEMENTS IN ARR[] ARE DISTINCT
int kthSmallest(int arr[], int l, int r, int k)
{
    // If k is smaller than number of elements in array
    if (k > 0 && k <= r - l + 1)
    {
        // Partition the array around a random element and
        // get position of pivot element in sorted array
        int pos = randomPartition(arr, l, r);

        // If position is same as k
        if (pos-l == k-1)
            return arr[pos];
        if (pos-l > k-1) // If position is more, recur for left subarray
            return kthSmallest(arr, l, pos-1, k);

        // Else recur for right subarray
        return kthSmallest(arr, pos+1, r, k-pos+1-1);
    }

    // If k is more than number of elements in array
    return INT_MAX;
}

void swap(int *a, int *b)
{
    int temp = *a;
    *a = *b;
    *b = temp;
}
```

```

}

// Standard partition process of QuickSort(). It considers the last
// element as pivot and moves all smaller element to left of it and
// greater elements to right. This function is used by randomPartition()
int partition(int arr[], int l, int r)
{
    int x = arr[r], i = l;
    for (int j = l; j <= r - 1; j++)
    {
        if (arr[j] <= x)
        {
            swap(&arr[i], &arr[j]);
            i++;
        }
    }
    swap(&arr[i], &arr[r]);
    return i;
}

// Picks a random pivot element between l and r and partitions
// arr[l..r] around the randomly picked element using partition()
int randomPartition(int arr[], int l, int r)
{
    int n = r-l+1;
    int pivot = rand() % n;
    swap(&arr[l + pivot], &arr[r]);
    return partition(arr, l, r);
}

// Driver program to test above methods
int main()
{
    int arr[] = {12, 3, 5, 7, 4, 19, 26};
    int n = sizeof(arr)/sizeof(arr[0]), k = 3;
    cout << "K'th smallest element is " << kthSmallest(arr, 0, n-1, k);
    return 0;
}

```

Output:

K'th smallest element is 5

Time Complexity:

The worst case time complexity of the above solution is still $O(n^2)$. In worst case, the randomized function may always pick a corner element. The expected time complexity of above randomized QuickSelect is $\Theta(n)$, see [CLRS book](#) or [MIT video lecture](#) for proof. The assumption in the analysis is, random number generator is equally likely to generate any number in the input range.

Sources:

[MIT Video Lecture on Order Statistics, Median](#)

[Introduction to Algorithms by Clifford Stein, Thomas H. Cormen, Charles E. Leiserson, Ronald L.](#)

This article is contributed by **Shivam**. Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above

Related Topics:

- [Find Union and Intersection of two unsorted arrays](#)
- [Pythagorean Triplet in an array](#)
- [Maximum profit by buying and selling a share at most twice](#)
- [Design a data structure that supports insert, delete, search and getRandom in constant time](#)
- [Print missing elements that lie in range 0 – 99](#)
- [Iterative Merge Sort](#)
- [Group multiple occurrence of array elements ordered by first occurrence](#)
- [Given a sorted and rotated array, find if there is a pair with a given sum](#)



Tweet

3

g+1

2

Writing code in comment? Please use ideone.com and share the link here.

12 Comments

GeeksforGeeks

1 Login ▾

♥ Recommend

🔗 Share

Sort by Newest ▾



Join the discussion...



Goku • 2 months ago

Cleaner Solution using the same method.

<http://ideone.com/VXOiWH>

Language : C++14

^ | v • Reply • Share ›



Guest • 4 months ago

can some one explain kthSmallest(arr, pos+1, r, k-pos+l-1) ..
why (k-pos+l-1)??

^ | v • Reply • Share ›



cfh ➔ Guest • 2 months ago

this is the case when $(pos-l < k-1)$, this="" means="" that="" kth="" smallest="" element="" will="" not="" be="" in="" left="" part="" arr[l...pos]="" when="" sorted,="" thus="" will="" be="" in="" right="" part="" a[pos+1...r].="" thus="" in="" right="" part="" we="" look="" for="" the="" $(k-(pos-l+1))$ th="" element="" i.e.="" $(k-pos+l-1)$ th="" element="" :="">

^ | v • Reply • Share ›



Rhagwat Singh • 5 months ago

**Bhagwat Singh** • 5 months ago

I think in place of "%" there should be * . int pivot = rand() % n;
It should be rand()*n;

^ | v • Reply • Share ›

**GeeksforGeeks** Mod → Bhagwat Singh • 5 months ago

The above implementation looks correct. Please refer <http://www.cplusplus.com/refer...> for rand()

^ | v • Reply • Share ›

**Bhagwat Singh** → GeeksforGeeks • 5 months ago

WHAT IF THE NUMBER IS GREATER THAN 32767 BECAUSE THE STANDARD MAX IS THIS ONLY.

^ | v • Reply • Share ›

**Raj** • 5 months ago

```
#include<iostream>
#include <queue> // std::priority_queue
#include <functional> // std::greater
using namespace std;

class mycomparison;

typedef std::priority_queue<int,std::vector<int>,mycomparison> mypq_type;

//By default priority queue is max heap means max value will be in front
//if you want to max it min heap just implement below mycomparison class
int swapValue =0;
class mycomparison
{
    bool reverse;
public:
    mycomparison(const bool& revparam=false)//True for ascending
    {reverse=revparam;}
    bool operator() (const int& lhs, const int& rhs) const
```

[see more](#)

^ | v • Reply • Share ›

**kaushik** • 5 months ago

we can use min heap or maxheap and easily we can get kth min or max in linear time.

^ | v • Reply • Share ›

**K.** → kaushik • 5 months ago

Shouldn't that be $O(k \cdot \lg n)$?

^ | v • Reply • Share ›



Deepak Mishra → K. • 5 months ago

Shouldn't we evaluate first $(k * \log n)$ is greater or (n) before applying the algorithm

^ | v • Reply • Share ›



Deepak Mishra → Deepak Mishra • 5 months ago

Sorry my mistake heap sort is $n * \log k$

^ | v • Reply • Share ›



kaushik → K. • 5 months ago

yes I got

^ | v • Reply • Share ›

Subscribe

Add Disqus to your site

Privacy

-
-
-
-
- - [Interview Experiences](#)
 - [Advanced Data Structures](#)
 - [Dynamic Programming](#)
 - [Greedy Algorithms](#)
 - [Backtracking](#)
 - [Pattern Searching](#)
 - [Divide & Conquer](#)
 - [Mathematical Algorithms](#)
 - [Recursion](#)
 - [Geometric Algorithms](#)
-

• Popular Posts

- [All permutations of a given string](#)
- [Memory Layout of C Programs](#)
- [Understanding “extern” keyword in C](#)
- [Median of two sorted arrays](#)

- [Tree traversal without recursion and without stack!](#)
- [Structure Member Alignment, Padding and Data Packing](#)
- [Intersection point of two Linked Lists](#)
- [Lowest Common Ancestor in a BST.](#)
- [Check if a binary tree is BST or not](#)
- [Sorted Linked List to Balanced BST](#)

Follow @GeeksforGeeks

• Recent Comments

- [It_k](#)

i need help for coding this function in java...

[Java Programming Language](#) · [1 hour ago](#)

- [Piyush](#)

What is the purpose of else if (recStack[*i])...

[Detect Cycle in a Directed Graph](#) · [1 hour ago](#)

- [Andy Toh](#)

My compile-time solution, which agrees with the...

[Dynamic Programming | Set 16 \(Floyd Warshall Algorithm\)](#) · [1 hour ago](#)

- [lucy](#)

because we first fill zero in first col and...

[Dynamic Programming | Set 29 \(Longest Common Substring\)](#) · [2 hours ago](#)

- [lucy](#)

@GeeksforGeeks i don't n know what is this long...

[Dynamic Programming | Set 28 \(Minimum insertions to form a palindrome\)](#) · [2 hours ago](#)

- [manish](#)

Because TAN is not a subsequence of RANT. ANT...

[Given two strings, find if first string is a subsequence of second](#) · [2 hours ago](#)

@geeksforgeeks, [Some rights reserved](#) [Contact Us!](#)

Powered by [WordPress](#) & [MooTools](#), customized by geeksforgeeks team