

# GeeksforGeeks

A computer science portal for geeks

## GeeksQuiz

- [Home](#)
- [Algorithms](#)
- [DS](#)
- [GATE](#)
- [Interview Corner](#)
- [Q&A](#)
- [C](#)
- [C++](#)
- [Java](#)
- [Books](#)
- [Contribute](#)
- [Ask a Q](#)
- [About](#)

[Array](#)

[Bit Magic](#)

[C/C++](#)

[Articles](#)

[GFactS](#)

[Linked List](#)

[MCQ](#)

[Misc](#)

[Output](#)

[String](#)

[Tree](#)

[Graph](#)

## Why is Binary Search preferred over Ternary Search?

The following is a simple recursive **Binary Search** function in C++ taken from [here](#).

```
// A recursive binary search function. It returns location of x in
// given array arr[l..r] is present, otherwise -1
int binarySearch(int arr[], int l, int r, int x)
{
    if (r >= l)
    {
        int mid = l + (r - l)/2;

        // If the element is present at the middle itself
        if (arr[mid] == x) return mid;
```

```

    // If element is smaller than mid, then it can only be present
    // in left subarray
    if (arr[mid] > x) return binarySearch(arr, l, mid-1, x);

    // Else the element can only be present in right subarray
    return binarySearch(arr, mid+1, r, x);
}

// We reach here when element is not present in array
return -1;
}

```

The following is a simple recursive **Ternary Search** function in C++.

```

// A recursive ternary search function. It returns location of x in
// given array arr[l..r] is present, otherwise -1
int ternarySearch(int arr[], int l, int r, int x)
{
    if (r >= l)
    {
        int mid1 = l + (r - l)/3;
        int mid2 = mid1 + (r - l)/3;

        // If x is present at the mid1
        if (arr[mid1] == x) return mid1;

        // If x is present at the mid2
        if (arr[mid2] == x) return mid2;

        // If x is present in left one-third
        if (arr[mid1] > x) return ternarySearch(arr, l, mid1-1, x);

        // If x is present in right one-third
        if (arr[mid2] < x) return ternarySearch(arr, mid2+1, r, x);

        // If x is present in middle one-third
        return ternarySearch(arr, mid1+1, mid2-1, x);
    }
    // We reach here when element is not present in array
    return -1;
}

```

### Which of the above two does less comparisons in worst case?

From the first look, it seems the ternary search does less number of comparisons as it makes  $\lceil \log_3 n \rceil$  recursive calls, but binary search makes  $\lceil \log_2 n \rceil$  recursive calls. Let us take a closer look.

The following is recursive formula for counting comparisons in worst case of Binary Search.

$$T(n) = T(n/2) + 2, \quad T(1) = 1$$

The following is recursive formula for counting comparisons in worst case of Ternary Search.

$$T(n) = T(n/3) + 4, \quad T(1) = 1$$

In binary search, there are  $\lceil 2\log_2 n \rceil + 1$  comparisons in worst case. In ternary search, there are  $\lceil 4\log_3 n \rceil + 1$  comparisons in worst case.

Therefore, the comparison of Ternary and Binary Searches boils down the comparison of expressions  $\lceil 2\log_3 n \rceil$  and  $\lceil \log_2 n \rceil$ . The value of  $\lceil 2\log_3 n \rceil$  can be written as  $\lceil \log_2 n \rceil \cdot (2/\log_2 3)$ . Since the value of  $2/\log_2 3$  is more than one, Ternary Search does more comparisons than Binary Search in worst case.

### Exercise:

Why Merge Sort divides input array in two halves, why not in three or more parts?

This article is contributed by **Anmol**. Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above

### Related Topics:

- [Find Union and Intersection of two unsorted arrays](#)
- [Pythagorean Triplet in an array](#)
- [Maximum profit by buying and selling a share at most twice](#)
- [Design a data structure that supports insert, delete, search and getRandom in constant time](#)
- [Print missing elements that lie in range 0 – 99](#)
- [Iterative Merge Sort](#)
- [Group multiple occurrence of array elements ordered by first occurrence](#)
- [Given a sorted and rotated array, find if there is a pair with a given sum](#)



Tweet

4

g+1

1

Writing code in comment? Please use [ideone.com](http://ideone.com) and share the link here.

2 Comments

GeeksforGeeks

 Login ▾ Recommend Share

Sort by Newest ▾



Join the discussion...

**Times Square** • 5 months ago

Doesn't Binary Search require 2 comparisons per recursive call ? First with the mid element and if its not equal then compare again to find which half to recurse next

```
if (arr[mid] == x) return mid;
```

```
if (arr[mid] > x)
```

1 ^ | v • Reply • Share ›

**GeeksforGeeks** Mod → Times Square • 5 months ago

Thanks for pointing this out. We have updated the post.

^ | v • Reply • Share ›

 Subscribe Add Disqus to your site Privacy

- 
- 
- 
- - [Interview Experiences](#)
  - [Advanced Data Structures](#)
  - [Dynamic Programming](#)
  - [Greedy Algorithms](#)
  - [Backtracking](#)
  - [Pattern Searching](#)
  - [Divide & Conquer](#)
  - [Mathematical Algorithms](#)
  - [Recursion](#)
  - [Geometric Algorithms](#)
- 

## • Popular Posts

- [All permutations of a given string](#)

- [Memory Layout of C Programs](#)
- [Understanding “extern” keyword in C](#)
- [Median of two sorted arrays](#)
- [Tree traversal without recursion and without stack!](#)
- [Structure Member Alignment, Padding and Data Packing](#)
- [Intersection point of two Linked Lists](#)
- [Lowest Common Ancestor in a BST](#)
- [Check if a binary tree is BST or not](#)
- [Sorted Linked List to Balanced BST](#)

Follow @GeeksforGeeks

## • Recent Comments

- [It\\_k](#)

i need help for coding this function in java...

[Java Programming Language](#) · [1 hour ago](#)

- [Piyush](#)

What is the purpose of else if (recStack[\*i])...

[Detect Cycle in a Directed Graph](#) · [1 hour ago](#)

- [Andy Toh](#)

My compile-time solution, which agrees with the...

[Dynamic Programming | Set 16 \(Floyd Warshall Algorithm\)](#) · [1 hour ago](#)

- [lucy](#)

because we first fill zero in first col and...

[Dynamic Programming | Set 29 \(Longest Common Substring\)](#) · [2 hours ago](#)

- [lucy](#)

@GeeksforGeeks i don't n know what is this long...

[Dynamic Programming | Set 28 \(Minimum insertions to form a palindrome\)](#) · [2 hours ago](#)

- [manish](#)

Because TAN is not a subsequence of RANT. ANT...

[Given two strings, find if first string is a subsequence of second](#) · [2 hours ago](#)

Powered by [WordPress](#) & [MooTools](#), customized by geeksforgeeks team