

GeeksforGeeks

A computer science portal for geeks

GeeksQuiz

- [Home](#)
- [Algorithms](#)
- [DS](#)
- [GATE](#)
- [Interview Corner](#)
- [Q&A](#)
- [C](#)
- [C++](#)
- [Java](#)
- [Books](#)
- [Contribute](#)
- [Ask a Q](#)
- [About](#)

[Array](#)

[Bit Magic](#)

[C/C++](#)

[Articles](#)

[GFactS](#)

[Linked List](#)

[MCQ](#)

[Misc](#)

[Output](#)

[String](#)

[Tree](#)

[Graph](#)

Greedy Algorithms | Set 4 (Efficient Huffman Coding for Sorted Input)

We recommend to read following post as a prerequisite for this.

[Greedy Algorithms | Set 3 \(Huffman Coding\)](#)

Time complexity of the algorithm discussed in above post is $O(n \log n)$. If we know that the given array is sorted (by non-decreasing order of frequency), we can generate Huffman codes in $O(n)$ time.

Following is a $O(n)$ algorithm for sorted input.

1. Create two empty queues.
2. Create a leaf node for each unique character and Enqueue it to the first queue in non-decreasing order

of frequency. Initially second queue is empty.

3. Dequeue two nodes with the minimum frequency by examining the front of both queues. Repeat following steps two times

.....**a)** If second queue is empty, dequeue from first queue.

.....**b)** If first queue is empty, dequeue from second queue.

.....**c)** Else, compare the front of two queues and dequeue the minimum.

4. Create a new internal node with frequency equal to the sum of the two nodes frequencies. Make the first Dequeued node as its left child and the second Dequeued node as right child. Enqueue this node to second queue.

5. Repeat steps#3 and #4 until there is more than one node in the queues. The remaining node is the root node and the tree is complete.

// C Program for Efficient Huffman Coding for Sorted input

`#include <stdio.h>`

`#include <stdlib.h>`

// This constant can be avoided by explicitly calculating height of Huffman T
`#define MAX_TREE_HT 100`

// A node of huffman tree

`struct QueueNode`

```
{
    char data;
    unsigned freq;
    struct QueueNode *left, *right;
};
```

// Structure for Queue: collection of Huffman Tree nodes (or QueueNodes)

`struct Queue`

```
{
    int front, rear;
    int capacity;
    struct QueueNode **array;
};
```

// A utility function to create a new Queuenode

`struct QueueNode* newNode(char data, unsigned freq)`

```
{
    struct QueueNode* temp =
        (struct QueueNode*) malloc(sizeof(struct QueueNode));
    temp->left = temp->right = NULL;
    temp->data = data;
    temp->freq = freq;
    return temp;
}
```

// A utility function to create a Queue of given capacity

`struct Queue* createQueue(int capacity)`

```
{
    struct Queue* queue = (struct Queue*) malloc(sizeof(struct Queue));
```

```

queue->front = queue->rear = -1;
queue->capacity = capacity;
queue->array =
    (struct QueueNode**) malloc(queue->capacity * sizeof(struct QueueNode*))
return queue;
}

// A utility function to check if size of given queue is 1
int isSizeOne(struct Queue* queue)
{
    return queue->front == queue->rear && queue->front != -1;
}

// A utility function to check if given queue is empty
int isEmpty(struct Queue* queue)
{
    return queue->front == -1;
}

// A utility function to check if given queue is full
int isFull(struct Queue* queue)
{
    return queue->rear == queue->capacity - 1;
}

// A utility function to add an item to queue
void enqueue(struct Queue* queue, struct QueueNode* item)
{
    if (isFull(queue))
        return;
    queue->array[++queue->rear] = item;
    if (queue->front == -1)
        ++queue->front;
}

// A utility function to remove an item from queue
struct QueueNode* dequeue(struct Queue* queue)
{
    if (isEmpty(queue))
        return NULL;
    struct QueueNode* temp = queue->array[queue->front];
    if (queue->front == queue->rear) // If there is only one item in queue
        queue->front = queue->rear = -1;
    else
        ++queue->front;
    return temp;
}

// A utility function to get from of queue
struct QueueNode* getFront(struct Queue* queue)
{
    if (isEmpty(queue))
        return NULL;

```

```

    return queue->array[queue->front];
}

/* A function to get minimum item from two queues */
struct QueueNode* findMin(struct Queue* firstQueue, struct Queue* secondQueue)
{
    // Step 3.a: If second queue is empty, dequeue from first queue
    if (isEmpty(firstQueue))
        return dequeue(secondQueue);

    // Step 3.b: If first queue is empty, dequeue from second queue
    if (isEmpty(secondQueue))
        return dequeue(firstQueue);

    // Step 3.c: Else, compare the front of two queues and dequeue minimum
    if (getFront(firstQueue)->freq < getFront(secondQueue)->freq)
        return dequeue(firstQueue);

    return dequeue(secondQueue);
}

// Utility function to check if this node is leaf
int isLeaf(struct QueueNode* root)
{
    return !(root->left) && !(root->right) ;
}

// A utility function to print an array of size n
void printArr(int arr[], int n)
{
    int i;
    for (i = 0; i < n; ++i)
        printf("%d", arr[i]);
    printf("\n");
}

// The main function that builds Huffman tree
struct QueueNode* buildHuffmanTree(char data[], int freq[], int size)
{
    struct QueueNode *left, *right, *top;

    // Step 1: Create two empty queues
    struct Queue* firstQueue = createQueue(size);
    struct Queue* secondQueue = createQueue(size);

    // Step 2: Create a leaf node for each unique character and Enqueue it to
    // the first queue in non-decreasing order of frequency. Initially second
    // queue is empty
    for (int i = 0; i < size; ++i)
        enqueue(firstQueue, newNode(data[i], freq[i]));

    // Run while Queues contain more than one node. Finally, first queue will
    // be empty and second queue will contain only one node

```

```

while (!(isEmpty(firstQueue) && isSizeOne(secondQueue)))
{
    // Step 3: Dequeue two nodes with the minimum frequency by examining
    // the front of both queues
    left = findMin(firstQueue, secondQueue);
    right = findMin(firstQueue, secondQueue);

    // Step 4: Create a new internal node with frequency equal to the sum
    // of the two nodes frequencies. Enqueue this node to second queue.
    top = newNode('$' , left->freq + right->freq);
    top->left = left;
    top->right = right;
    enqueue(secondQueue, top);
}

return dequeue(secondQueue);
}

// Prints huffman codes from the root of Huffman Tree. It uses arr[] to
// store codes
void printCodes(struct QueueNode* root, int arr[], int top)
{
    // Assign 0 to left edge and recur
    if (root->left)
    {
        arr[top] = 0;
        printCodes(root->left, arr, top + 1);
    }

    // Assign 1 to right edge and recur
    if (root->right)
    {
        arr[top] = 1;
        printCodes(root->right, arr, top + 1);
    }

    // If this is a leaf node, then it contains one of the input
    // characters, print the character and its code from arr[]
    if (isLeaf(root))
    {
        printf("%c: ", root->data);
        printArr(arr, top);
    }
}

// The main function that builds a Huffman Tree and print codes by traversing
// the built Huffman Tree
void HuffmanCodes(char data[], int freq[], int size)
{
    // Construct Huffman Tree
    struct QueueNode* root = buildHuffmanTree(data, freq, size);

    // Print Huffman codes using the Huffman tree built above

```

```

    int arr[MAX_TREE_HT], top = 0;
    printCodes(root, arr, top);
}

// Driver program to test above functions
int main()
{
    char arr[] = {'a', 'b', 'c', 'd', 'e', 'f'};
    int freq[] = {5, 9, 12, 13, 16, 45};
    int size = sizeof(arr)/sizeof(arr[0]);
    HuffmanCodes(arr, freq, size);
    return 0;
}

```

Output:

```

f: 0
c: 100
d: 101
a: 1100
b: 1101
e: 111

```

Time complexity: $O(n)$

If the input is not sorted, it need to be sorted first before it can be processed by the above algorithm. Sorting can be done using heap-sort or merge-sort both of which run in $\Theta(n \log n)$. So, the overall time complexity becomes $O(n \log n)$ for unsorted input.

Reference:

http://en.wikipedia.org/wiki/Huffman_coding

This article is compiled by [Aashish Barnwal](#) and reviewed by GeeksforGeeks team. Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above.

Related Topics:

- [Linearity of Expectation](#)
- [Iterative Tower of Hanoi](#)
- [Count possible ways to construct buildings](#)
- [Build Lowest Number by Removing n digits from a given number](#)
- [Set Cover Problem | Set 1 \(Greedy Approximate Algorithm\)](#)
- [Find number of days between two given dates](#)
- [How to print maximum number of A's using given four keys](#)
- [Write an iterative \$O\(\log y\)\$ function for \$\text{pow}\(x, y\)\$](#)

Tags: [Greedy Algorithm](#), [Huffman Coding](#)



Tweet

0

+1

1

Writing code in comment? Please use ideone.com and share the link here.

4 Comments

GeeksforGeeks

 1 Login ▾

 Recommend

 Share

Sort by Newest ▾



Join the discussion...

Jeffery yuan • 10 months ago

Could you please provide some proof why this algorithm works?

1 ^ | ▾ • Reply • Share ›



Angel → Jeffery yuan • 2 months ago

lift a pencil and apply your brain man, you will easily figure it out!

^ | ▾ • Reply • Share ›



veggie • a year ago

What about printing it in alphabetical order?

^ | ▾ • Reply • Share ›



Sugarcane_farmer → veggie • a year ago

Maybe save all in map. Sort and print output. This is a after step which most cases wont be required

^ | ▾ • Reply • Share ›

 Subscribe

 Add Disqus to your site

 Privacy

-
-
-
-

- [Interview Experiences](#)
- [Advanced Data Structures](#)
- [Dynamic Programming](#)
- [Greedy Algorithms](#)
- [Backtracking](#)
- [Pattern Searching](#)
- [Divide & Conquer](#)
- [Mathematical Algorithms](#)
- [Recursion](#)

- [Geometric Algorithms](#)

• Popular Posts

- [All permutations of a given string](#)
- [Memory Layout of C Programs](#)
- [Understanding “extern” keyword in C](#)
- [Median of two sorted arrays](#)
- [Tree traversal without recursion and without stack!](#)
- [Structure Member Alignment, Padding and Data Packing](#)
- [Intersection point of two Linked Lists](#)
- [Lowest Common Ancestor in a BST.](#)
- [Check if a binary tree is BST or not](#)
- [Sorted Linked List to Balanced BST](#)

Follow @GeeksforGeeks

• Recent Comments

- [It_k](#)

i need help for coding this function in java...

[Java Programming Language](#) · [1 hour ago](#)

- [Piyush](#)

What is the purpose of else if (recStack[*i])...

[Detect Cycle in a Directed Graph](#) · [1 hour ago](#)

- [Andy Toh](#)

My compile-time solution, which agrees with the...

[Dynamic Programming | Set 16 \(Floyd Warshall Algorithm\)](#) · [1 hour ago](#)

- [lucy](#)

because we first fill zero in first col and...

[Dynamic Programming | Set 29 \(Longest Common Substring\)](#) · [2 hours ago](#)

- [lucy](#)

@GeeksforGeeks i don't n know what is this long...

[Dynamic Programming | Set 28 \(Minimum insertions to form a palindrome\)](#) · [2 hours ago](#)

- [manish](#)

Because TAN is not a subsequence of RANT. ANT...

[Given two strings, find if first string is a subsequence of second](#) · [2 hours ago](#)

•

@geeksforgeeks, [Some rights reserved](#) [Contact Us!](#)

Powered by [WordPress](#) & [MooTools](#), customized by geeksforgeeks team