

GeeksforGeeks

A computer science portal for geeks

GeeksQuiz

- [Home](#)
- [Algorithms](#)
- [DS](#)
- [GATE](#)
- [Interview Corner](#)
- [Q&A](#)
- [C](#)
- [C++](#)
- [Java](#)
- [Books](#)
- [Contribute](#)
- [Ask a Q](#)
- [About](#)

[Array](#)

[Bit Magic](#)

[C/C++](#)

[Articles](#)

[GFactS](#)

[Linked List](#)

[MCQ](#)

[Misc](#)

[Output](#)

[String](#)

[Tree](#)

[Graph](#)


Manacher's Algorithm – Linear Time Longest Palindromic Substring – Part 4

In Manacher's Algorithm [Part 1](#) and [Part 2](#), we gone through some of the basics, understood LPS length array and how to calculate it efficiently based on four cases. In [Part 3](#), we implemented the same.

Here we will review the four cases again and try to see it differently and implement the same.

All four cases depends on LPS length value at currentLeftPosition ($L[iMirror]$) and value of (centerRightPosition – currentRightPosition), i.e. $(R - i)$. These two information are know before which helps us to reuse previous available information and avoid unnecessary character comparison.

(click to see it clearly)



If we look at all four cases, we will see that we 1st set minimum of $L[iMirror]$ and $R-i$ to $L[i]$ and then we try to expand the palindrome in whichever case it can expand.

Above observation may look more intuitive, easier to understand and implement, given that one understands LPS length array, position, index, symmetry property etc.

```
// A C program to implement Manacher's Algorithm
#include <stdio.h>
#include <string.h>

char text[100];
int min(int a, int b)
{
    int res = a;
    if(b < a)
        res = b;
    return res;
}

void findLongestPalindromicString()
{
    int N = strlen(text);
    if(N == 0)
        return;
    N = 2*N + 1; //Position count
    int L[N]; //LPS Length Array
    L[0] = 0;
    L[1] = 1;
    int C = 1; //centerPosition
    int R = 2; //centerRightPosition
    int i = 0; //currentRightPosition
    int iMirror; //currentLeftPosition
    int maxLPSLength = 0;
    int maxLPSCenterPosition = 0;
    int start = -1;
    int end = -1;
    int diff = -1;

    //Uncomment it to print LPS Length array
    //printf("%d %d ", L[0], L[1]);
    for (i = 2; i < N; i++)
    {
        //get currentLeftPosition iMirror for currentRightPosition i
        iMirror = 2*C-i;
        L[i] = 0;
        diff = R - i;
        //If currentRightPosition i is within centerRightPosition R
        if(diff > 0)
            L[i] = min(L[iMirror], diff);

        //Attempt to expand palindrome centered at currentRightPosition i
        //Here for odd positions, we compare characters and
        //if match then increment LPS Length by ONE
    }
}
```

```

//If even position, we just increment LPS by ONE without
//any character comparison
while ( ((i + L[i]) < N && (i - L[i]) > 0) &&
        ( ((i + L[i] + 1) % 2 == 0) ||
          (text[(i + L[i] + 1)/2] == text[(i - L[i] - 1)/2] )))
{
    L[i]++;
}

if(L[i] > maxLPSLength) // Track maxLPSLength
{
    maxLPSLength = L[i];
    maxLPSCenterPosition = i;
}

//If palindrome centered at currentRightPosition i
//expand beyond centerRightPosition R,
//adjust centerPosition C based on expanded palindrome.
if (i + L[i] > R)
{
    C = i;
    R = i + L[i];
}
//Uncomment it to print LPS Length array
//printf("%d ", L[i]);
}
//printf("\n");
start = (maxLPSCenterPosition - maxLPSLength)/2;
end = start + maxLPSLength - 1;
printf("LPS of string is %s : ", text);
for(i=start; i<=end; i++)
    printf("%c", text[i]);
printf("\n");
}

int main(int argc, char *argv[])
{
    strcpy(text, "babcbabcbaccba");
    findLongestPalindromicString();

    strcpy(text, "abaaba");
    findLongestPalindromicString();

    strcpy(text, "abababa");
    findLongestPalindromicString();

    strcpy(text, "abcbabcbabcba");
    findLongestPalindromicString();

    strcpy(text, "forgeeksskeegfor");
    findLongestPalindromicString();

    strcpy(text, "caba");
    findLongestPalindromicString();

    strcpy(text, "abacdfgdcaba");
    findLongestPalindromicString();

    strcpy(text, "abacdfgdcabba");
    findLongestPalindromicString();
}

```

```

strcpy(text, "abacdedcaba");
findLongestPalindromicString();

return 0;
}

```

Output:

```

LPS of string is babcbabcbaccba : abcbabcba
LPS of string is abaaba : abaaba
LPS of string is abababa : abababa
LPS of string is abcbabcbabcba : abcbabcbabcba
LPS of string is forgeeksskeegfor : geeksskeeg
LPS of string is caba : aba
LPS of string is abacdfgdcaba : aba
LPS of string is abacdfgdcabba : abba
LPS of string is abacdedcaba : abacdedcaba

```

Other Approaches

We have discussed two approaches here. One in [Part 3](#) and other in current article. In both approaches, we worked on given string. Here we had to handle even and odd positions differently while comparing characters for expansion (because even positions do not represent any character in string).

To avoid this different handling of even and odd positions, we need to make even positions also to represent some character (actually all even positions should represent SAME character because they MUST match while character comparison). One way to do this is to set some character at all even positions by modifying given string or create a new copy of given string. For example, if input string is “abcb”, new string should be “#a#b#c#b#” if we add # as unique character at even positions.

The two approaches discussed already can be modified a bit to work on modified string where different handling of even and odd positions will not be needed.

We may also add two DIFFERENT characters (not yet used anywhere in string at even and odd positions) at start and end of string as sentinels to avoid bound check. With these changes string “abcb” will look like “^#a#b#c#b#\$” where ^ and \$ are sentinels.

This implementation may look cleaner with the cost of more memory.

We are not implementing these here as it's a simple change in given implementations.

Implementation of approach discussed in current article on a modified string can be found at [Longest Palindromic Substring Part II](#) and a [Java Translation](#) of the same by Princeton.

This article is contributed by **Anurag Singh**. Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above

Related Topics:

- [Recursively print all sentences that can be formed from list of word lists](#)
- [Check if a given sequence of moves for a robot is circular or not](#)
- [Find the longest substring with k unique characters in a given string](#)
- [Function to find Number of customers who could not get a computer](#)

- [Find maximum depth of nested parenthesis in a string](#)
- [Find all distinct palindromic sub-strings of a given string](#)
- [Find if a given string can be represented from a substring by iterating the substring "n" times](#)
- [Suffix Tree Application 6 – Longest Palindromic Substring](#)



Writing code in comment? Please use ideone.com and share the link here.

2 Comments

GeeksforGeeks

1 Login ▾

♥ Recommend

🔗 Share

Sort by Newest ▾



Join the discussion...



Guest • 4 months ago

Hei Anurag... I am getting the error for the following input "aabcdfsdg" . I might be wrong..kindly tell me..thanks :)

^ | ▾ • Reply • Share ›



Anurag Singh → Guest • 4 months ago

It gives output as "aa", which is correct on your input "aabcdfsdg".
Please revert back if you get a different output.

^ | ▾ • Reply • Share ›

✉ Subscribe

D Add Disqus to your site

🔒 Privacy

DISQUS

Google™ Custom Search



-
-
-
- - [Interview Experiences](#)
 - [Advanced Data Structures](#)
 - [Dynamic Programming](#)
 - [Greedy Algorithms](#)
 - [Backtracking](#)
 - [Pattern Searching](#)
 - [Divide & Conquer](#)
 - [Mathematical Algorithms](#)
 - [Recursion](#)
 - [Geometric Algorithms](#)
-

• Popular Posts

- [All permutations of a given string](#)
- [Memory Layout of C Programs](#)
- [Understanding “extern” keyword in C](#)
- [Median of two sorted arrays](#)
- [Tree traversal without recursion and without stack!](#)
- [Structure Member Alignment, Padding and Data Packing](#)
- [Intersection point of two Linked Lists](#)
- [Lowest Common Ancestor in a BST.](#)
- [Check if a binary tree is BST or not](#)
- [Sorted Linked List to Balanced BST](#)



• Recent Comments

- [Ashish Aggarwal](#)

Try Data Structures and Algorithms Made Easy -...

[Algorithms](#) · [17 minutes ago](#)

- Vlad

Thanks. Very interesting lectures.

[Expected Number of Trials until Success](#) · [1 hour ago](#)

- [cfh](#)

My implementation which prints the index of the...

[Longest Even Length Substring such that Sum of First and Second Half is same](#) · [1 hour ago](#)

- [Gaurav pruthi](#)

forgot to see that part ;)

[Bloomberg Interview | Set 1 \(Phone Interview\)](#) · [1 hour ago](#)

- [saeid aslami](#)

thanks

[Greedy Algorithms | Set 7 \(Dijkstra's shortest path algorithm\)](#) · [1 hour ago](#)

- [Cracker](#)

Implementation:...

[Implement Stack using Queues](#) · [2 hours ago](#)

-

@geeksforgeeks, [Some rights reserved](#) [Contact Us!](#)

Powered by [WordPress](#) & [MooTools](#), customized by geeksforgeeks team