

Search ...

QSearch

You are here: [Home](#) > [C](#) > [C Programs](#) > C Program for Implementation of Predictive Parser

# C Program for Implementation of Predictive Parser

Category: [C Programs](#)  
Published: Wednesday, 22 January 2014 16:48  
Written by [RajaSekhar](#)  
Hits: 3250

0 Comments

```
#include<stdio.h>
#include<ctype.h>
#include<string.h>
#include<stdlib.h>
#define SIZE 128
#define NONE -1
#define EOS '\0'
#define NUM 257
#define KEYWORD 258
#define ID 259
#define DONE 260
#define MAX 999
char lexemes[MAX];
char buffer[SIZE];
int lastchar=-1;
int lastentry=0;
int tokenval=DONE;
int lineno=1;
int lookahead;
struct entry
{
    char *lexptr;
    int token;
}
symtable[100];
struct entry
{
    keywords[] = { "if",KEYWORD,"else",KEYWORD,"for",KEYWORD,"int",KEYWORD,"float",KEYWORD,
        "double",KEYWORD,"char",KEYWORD,"struct",KEYWORD,"return",KEYWORD,0,0
};
void Error_Message(char *m)
{
    fprintf(stderr,"line %d, %s \n",lineno,m);
    exit(1);
}
int look_up(char s[ ])
{
    int k;
    for(k=lastentry; k>0; k--)
        if(strcmp(symtable[k].lexptr,s)==0)
            return k;
    return 0;
}
int insert(char s[ ],int tok)
{
    int len;
    len=strlen(s);
    if(lastentry+1>=MAX)
        Error_Message("Symtbl table is full");
    if(lastchar+len+1>=MAX)
        Error_Message("Lexemes array is full");
    lastentry=lastentry+1;
    symtable[lastentry].token=tok;
    symtable[lastentry].lexptr=&lexemes[lastchar+1];
    lastchar=lastchar+len+1;
    strcpy(symtable[lastentry].lexptr,s);
    return lastentry;
}
/*void Initialize()
{
    struct entry *ptr;
    for(ptr=keywords;ptr->token;ptr+1)
```

## User Menu (Login for Full Menu)

- [Instructions to Submit Program](#)
- [Login/Logout](#)
- [New User Registration](#)

## Check Other C-Programs

C Program Example to Initialize Structure Variable
C Program for Arithmetic Operations using Switch
C Program for Binary Search using Recursive and Non-
C program for Fibonacci Series
C Program for Floyd Triangle
C Program for Implementation of Predictive Parser
C Program for INSERTION SORT
C Program for Matrix Multiplication
C Program for MERGING of Two Arrays with out using
C Program for Optimal Page Replacement Algorithm
C Program for String Comparison with out using Built in
C Program for String Concatenation with out using
C Program for Sum of Digits of a Number
C Program for Sum of Digits of a Number using
C Program for Sum of Squares of Numbers from 1 to n
C Program for Swapping of Two Numbers Without Using
C Program to ADD two MATRICES
C Program to ADD two Numbers
C Program to Calculate NCR
C Program to Calculate Sum of Even Values in an Array
C Program to Calculate Sum of Marks to Demonstrate
C Program to Calculate Sum of Odd Values in an Array
C Program to Check Given Number is PRIME or Not
C Program to Check the Leap Year
C Program to Check Whether a Character is a Vowel or

```

        insert(ptr->lexptr,ptr->token);
    }*/
int lexer()
{
    int t;
    int val,i=0;
    while(1)
    {
        t=getchar();
        if(t==' '||t=='\t');
        else if(t=='\n')
            lineno=lineno+1;
        else if(isdigit(t))
        {
            ungetc(t,stdin);
            scanf("%d",&tokenval);
            return NUM;
        }
        else if(isalpha(t))
        {
            while(isalnum(t))
            {
                buffer[i]=t;
                t=getchar();
                i=i+1;
                if(i>=SIZE)
                    Error_Message("Compiler error");
            }
            buffer[i]=EOS;
            if(t!=EOF)
                ungetc(t,stdin);
            val=look_up(buffer);
            if(val==0)
                val=insert(buffer,ID);
            tokenval=val;
            return symtable[val].token;
        }
        else if(t==EOF)
            return DONE;
        else
        {
            tokenval=NONE;
            return t;
        }
    }
}
void Match(int t)
{
    if(lookahead==t)
        lookahead=lexer();
    else
        Error_Message("Syntax error");
}
void display(int t,int tval)
{
    if(t=='+'||t=='-'||t=='*'||t=='/')
        printf("\nArithmetic Operator: %c",t);
    else if(t==NUM)
        printf("\n Number: %d",tval);
    else if(t==ID)
        printf("\n Identifier: %s",symtable[tval].lexptr);
    else
        printf("\n Token %d tokenval %d",t,tokenval);
}
void F()
{
    //void E();
    switch(lookahead)
    {
        case '(' :
            Match('(');
            E();
            Match('');
            break;
        case NUM :
            display(NUM,tokenval);
            Match(NUM);
            break;
        case ID :
            display(ID,tokenval);
            Match(ID);
            break;
        default :
            Error_Message("Syntax error");
    }
}
void T()

```

```

{
    int t;
    F();
    while(1)
    {
        switch(lookahead)
        {
            case '*' :
                t=lookahead;
                Match(lookahead);
                F();
                display(t,NONE);
                continue;
            case '/' :
                t=lookahead;
                Match(lookahead);
                display(t,NONE);
                continue;
            default :
                return;
        }
    }
}
void E()
{
    int t;
    T();
    while(1)
    {
        switch(lookahead)
        {
            case '+' :
                t=lookahead;
                Match(lookahead);
                T();
                display(t,NONE);
                continue;
            case '-' :
                t=lookahead;
                Match(lookahead);
                T();
                display(t,NONE);
                continue;
            default :
                return;
        }
    }
}
void parser()
{
    lookahead=lexer();
    while(lookahead!=DONE)
    {
        E();
        Match(';');
    }
}
main()
{
    char ans[10];

    printf("\n Program for recursive descent parsing ");
    printf("\n Enter the expression ");
    printf("And place ; at the end\n");
    printf("Press Ctrl-Z to terminate\n");
    parser();
}

```

SAMPLE OUTPUT:


```



Program for recursive descent parsing
Enter the expression And place ; at the end
Press Ctrl-Z to terminate
a*b+c;


Identifier: a
Identifier: b
Arithmetic Operator: *
Identifier: c
Arithmetic Operator: +
5*7;

Number: 5
Number: 7
Arithmetic Operator: *
*2;
line 5, Syntax error

```


**0 Comments** [www.programming9.com](#)  **Login** ▾


 **Recommend**  **Share** Sort by Best ▾






Be the first to comment.

**ALSO ON [WWW.PROGRAMMING9.COM](#)**

**A video guide for installing NS2 on UBUNTU 14.04**  
4 comments • 6 months ago  
 programming9 — That is not a problem, those are required supporting packages, you already have the latest versions. Proceed with the ...

**Depth First Search (DFS) Implementation using C**  
1 comment • 6 months ago  
 Christopher Ganda — edges 1 2 1 4 2 4 4 1  
output = 1 2 4 4

 **Subscribe**  **Add Disqus** to your site [Add Disqus](#) [Add](#)  **Privacy**

[back to top](#)  
[C-Programs Hard](#)  
[Compiler Design](#)  
[Prev](#) [Next](#) >




## Login

Username

Password

Remember Me ☐

LOG IN

-  [Forgot your password?](#)
-  [Forgot your username?](#)
-  [Create an account](#)

## Best Free IDEs

**C and C++ Editors:** [CodeBlocks](#)

**Java IDE:** [IntelliJ IDEA](#)

**Raptor:** [Flowchart Designer](#)

**CKEditor:** [HTML Editor](#)

## Main Links

[C Programs Collection](#)

[FlowCharts Collection](#)

[Java Programs Collection](#)

[C++ Codes Collection](#)

[HTML Codes](#)

[PI/Sql Programs](#)

## Like Us

